

Specifications



Photo is representative



Eaton 276353

Eaton Moeller® series DILA Contactor relay,
240 V 50 Hz, 3 N/O, 1 NC, Screw terminals,
AC operation

General specifications

PRODUCT NAME	Eaton Moeller® series DILA Control relay
---------------------	---

CATALOG NUMBER	276353
-----------------------	--------

MODEL CODE	DILA-31(240V50HZ)
-------------------	-------------------

EAN	4015082763534
------------	---------------

PRODUCT LENGTH/DEPTH	75 mm
---------------------------------	-------

PRODUCT HEIGHT	68 mm
-----------------------	-------

PRODUCT WIDTH	45 mm
----------------------	-------

PRODUCT WEIGHT	0.237 kg
-----------------------	----------

COMPLIANCES	CE Marked
--------------------	-----------

CERTIFICATIONS

IEC 60947-4-1
UL 508
CSA Std. C22.2 No. 14-05
EN 60947-4-1
VDE
CSA File No.: 012528
IEC/EN 60947
IEC/EN 60947-4-1
CSA
VDE 0660
CE
CSA-C22.2 No. 14-05
EN 60947-5-1
UL File No.: E29184
UL
CSA Class No.: 3211-03
UL Category Control No.:
NKCR



Powering Business Worldwide

Features & Functions

FEATURES

Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module

FITTED WITH:

Positive operation contacts

General

APPLICATION

Contactors relays

DEGREE OF PROTECTION

IP20

SHOCK RESISTANCE

7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

LIFESPAN, MECHANICAL

20,000,000 Operations (AC operated)

MOUNTING METHOD

Screw

CONNECTION

Screw terminals

OPERATING FREQUENCY

9000 Operations/h

OVERVOLTAGE CATEGORY

III

POLLUTION DEGREE

3

PRODUCT CATEGORY

DILA relays

PROTECTION

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)

6000 V AC

VOLTAGE TYPE

AC

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
--	--------

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
--	-------

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	25 °C
---	-------

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
---	-------

AMBIENT STORAGE TEMPERATURE - MIN	40 °C
--	-------

AMBIENT STORAGE TEMPERATURE - MAX	80 °C
--	-------

CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
--------------------------	--

Terminal capacities

TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	1 x (0.75 - 2.5) mm ² , Screw terminals 2 x (0.75 - 2.5) mm ² , Screw terminals
--	--

TERMINAL CAPACITY (SOLID)	1 x (0.75 - 4) mm ² , Screw terminals 2 x (0.75 - 2.5) mm ² , Screw terminals
----------------------------------	--

TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 14, Screw terminals
---	--------------------------

STRIPPING LENGTH (MAIN CABLE)	10 mm
--------------------------------------	-------

SCREW SIZE	M3.5, Terminal screw
-------------------	----------------------

SCREWDRIVER SIZE	0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver
-------------------------	---

TIGHTENING TORQUE	1.2 Nm, Screw terminals
--------------------------	-------------------------

Electrical rating

RATED OPERATIONAL CURRENT (IE)	1 A at 220 V, DC L/R ≤ 15 ms (with 1 contact in series)
	10 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in series)
	6 A at 60 V, DC L/R ≤ 15 ms (with 1 contact in series)
	6 A at 110 V, DC L/R ≤ 15 ms (with 3 contacts in series)
	3 A at 110 V, DC L/R ≤ 15 ms (with 1 contact in series)
	5 A at 220 V, DC L/R ≤ 15 ms (with 3 contacts in series)
	2 A at 110 V, DC L/R ≤ 50 ms (with 3 contacts in series)
	10 A at 60 V, DC L/R ≤ 15 ms (with 2 contacts in series)
	4 A at 24 V, DC L/R ≤ 50 ms (with 3 contacts in series)
	4 A at 60 V, DC L/R ≤ 50 ms (with 3 contacts in series)
	1 A at 220 V, DC L/R ≤ 50 ms (with 3 contacts in series)
	16 A

RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V

4 A

RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V

4 A

RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V

1.5 A

RATED INSULATION VOLTAGE (UI)

690 V

RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX

690 V

SHORT-CIRCUIT PROTECTION RATING WITHOUT WELDING

10 A gG/gL, 500 V, Max. Fuse, Contacts

SAFE ISOLATION

400 V AC, Between coil and auxiliary contacts, According to EN 61140
400 V AC, Between

Magnet system

DUTY FACTOR

100 %

PICK-UP VOLTAGE

0.8 - 1.1 V AC x U_c (voltage tolerance - single-voltage coil 50 Hz and dual-voltage coil 50 Hz, 60 Hz)

POWER CONSUMPTION, PICK-UP, 50 HZ

24 VA, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz

POWER CONSUMPTION, PICK-UP, 60 HZ

24 VA, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz

POWER CONSUMPTION, SEALING, 50 HZ

3.4 VA, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz
1.4 W, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz

POWER CONSUMPTION, SEALING, 60 HZ

1.4 W, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN

240 V

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX

240 V

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN

0 V

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX

0 V

RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN

0 V

RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX

0 V

SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MIN

15 ms

SWITCHING TIME (AC OPERATED, MAKE

21 ms

	auxiliary contacts, According to EN 61140
SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)	15 A, 600 V AC, (UL/CSA) 1 A, 250 V DC, (UL/CSA)
SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	A600, AC operated (UL/CSA) P300, DC operated (UL/CSA)

Communication	
CONNECTION TO SMARTWIRE-DT	No

CONTACTS, CLOSING DELAY) - MAX	
SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MIN	9 ms
SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX	18 ms

Contacts	
CODE NUMBER	31E
CONTROL CIRCUIT RELIABILITY	$\lambda < 5 \times 10^{-7}$ (1 failure at 2,000,000 operations for $U_e = 24$ V DC, $U_{min} = 17$ V, $I_{min} = 5.4$ mA)
NUMBER OF AUXILIARY CONTACTS (CHANGE- OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	3
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	3

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID 0 W

HEAT DISSIPATION CAPACITY PDISS 0 W

HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID 0.5 W

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 15.5 A

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS 1.4 W

10.2.2 CORROSION RESISTANCE Meets the product standard's requirements.

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES Meets the product standard's requirements.

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT Meets the product standard's requirements.

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS Meets the product standard's requirements.

10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION Meets the product standard's requirements.

10.2.5 LIFTING Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 MECHANICAL IMPACT Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 INSCRIPTIONS Meets the product standard's requirements.

10.3 DEGREE OF PROTECTION OF ASSEMBLIES Does not apply, since the entire switchgear needs to be evaluated.

10.4 CLEARANCES AND CREEPAGE DISTANCES Meets the product standard's requirements.

10.5 PROTECTION AGAINST ELECTRIC SHOCK Does not apply, since the entire switchgear needs to be evaluated.

Resources

[Product Range Catalog](#)
[Switching and protecting motors](#)

CATALOGUES

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

CHARACTERISTIC CURVE

[eaton-contactors-dila-relay-characteristic-curve.eps](#)
[eaton-contactors-component-dila-relay-characteristic-curve.eps](#)

DECLARATIONS OF CONFORMITY

[DA-DC-00004792.pdf](#)
[DA-DC-00004810.pdf](#)

DRAWINGS

[eaton-contactors-frame-dilm-dimensions.eps](#)
[eaton-contactors-module-dilm-dimensions.eps](#)
[eaton-contactors-mounting-dilm-dimensions-002.eps](#)
[eaton-contactors-mounting-dilm-dimensions.eps](#)
[eaton-contactors-dilm-3d-drawing-007.eps](#)

ECAD MODEL

[ETN.276353.edz](#)

INSTALLATION INSTRUCTIONS

[eaton-contactors-dila-dilm7-15-dilmp20-instruction-leaflet-il03407013z.pdf](#)

INSTALLATION VIDEOS

[WIN-WIN with push-in technology](#)

MCAD MODEL

[DA-CS-dil_m7_15](#)
[DA-CD-dil_m7_15](#)

SYSTEM OVERVIEW

[eaton-contactors-dila-system-overview.eps](#)

WIRING DIAGRAMS

[2100SWI-110](#)

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

