

Specifications

Photo is representative

Eaton 276393

Eaton Moeller® series DILA Contactor relay,
208 V 60 Hz, 2 N/O, 2 NC, Screw terminals,
AC operation

General specifications

| | |
|-----------------------------|---|
| PRODUCT NAME | Eaton Moeller® series DILA Control relay |
| CATALOG NUMBER | 276393 |
| MODEL CODE | DILA-22(208V60HZ) |
| EAN | 4015082763930 |
| PRODUCT LENGTH/DEPTH | 75 mm |
| PRODUCT HEIGHT | 68 mm |
| PRODUCT WIDTH | 45 mm |
| PRODUCT WEIGHT | 0.237 kg |

| | |
|-----------------------|---|
| CERTIFICATIONS | CE IEC/EN 60947 CSA UL File No.: E29184 CSA File No.: 012528 EN 60947-5-1 UL Category Control No.: NKCR UL 508 VDE 0660 CSA-C22.2 No. 14-05 UL CSA Class No.: 3211-03 IEC/EN 60947-4-1 |
|-----------------------|---|

Features & Functions

| | |
|---------------------|--|
| FEATURES | Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module |
| FITTED WITH: | Positive operation contacts |

General

| | |
|---|--|
| APPLICATION | Contactor relays |
| DEGREE OF PROTECTION | IP20 |
| SHOCK RESISTANCE | 5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms |
| LIFESPAN, MECHANICAL | 20,000,000 Operations (AC operated) |
| MOUNTING METHOD | DIN-rail/screw |
| CONNECTION | Screw terminals |
| OPERATING FREQUENCY | 9000 Operations/h |
| OVERVOLTAGE CATEGORY | III |
| POLLUTION DEGREE | 3 |
| PRODUCT CATEGORY | DILA relays |
| PROTECTION | Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) |
| RATED IMPULSE WITHSTAND VOLTAGE (UIMP) | 6000 V AC |
| VOLTAGE TYPE | AC |

Climatic environmental conditions

| | |
|---|--|
| AMBIENT OPERATING TEMPERATURE - MIN | -25 °C |
| AMBIENT OPERATING TEMPERATURE - MAX | 60 °C |
| AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN | 25 °C |
| AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX | 40 °C |
| AMBIENT STORAGE TEMPERATURE - MIN | 40 °C |
| AMBIENT STORAGE TEMPERATURE - MAX | 80 °C |
| CLIMATIC PROOFING | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |

Terminal capacities

| | |
|--|--|
| TERMINAL CAPACITY (FLEXIBLE WITH FERRULE) | 2 x (0.75 - 2.5) mm ² , Screw terminals 1 x (0.75 - 2.5) mm ² , Screw terminals |
| TERMINAL CAPACITY (SOLID) | 2 x (0.75 - 2.5) mm ² , Screw terminals 1 x (0.75 - 4) mm ² , Screw terminals |
| TERMINAL CAPACITY (SOLID/STRANDED AWG) | 18 - 14, Screw terminals |
| STRIPPING LENGTH (MAIN CABLE) | 10 mm |
| SCREW SIZE | M3.5, Terminal screw |
| SCREWDRIVER SIZE | 0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver |
| TIGHTENING TORQUE | 1.2 Nm, Screw terminals |

Electrical rating

| | |
|---|---|
| RATED OPERATIONAL CURRENT (IE) | 10 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in series) 5 A at 220 V, DC L/R ≤ 15 ms (with 3 contacts in series) 2 A at 110 V, DC L/R ≤ 50 ms (with 3 contacts in series) 4 A at 24 V, DC L/R ≤ 50 ms (with 3 contacts in series) 6 A at 110 V, DC L/R ≤ 15 ms (with 3 contacts in series) 1 A at 220 V, DC L/R ≤ 50 ms (with 3 contacts in series) 10 A at 60 V, DC L/R ≤ 15 ms (with 2 contacts in series) 1 A at 220 V, DC L/R ≤ 15 ms (with 1 contact in series) 4 A at 60 V, DC L/R ≤ 50 ms (with 3 contacts in series) 6 A at 60 V, DC L/R ≤ 15 ms (with 1 contact in series) 3 A at 110 V, DC L/R ≤ 15 ms (with 1 contact in series) 16 A |
| RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V | 4 A |
| RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V | 4 A |
| RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V | 1.5 A |
| RATED INSULATION VOLTAGE (UI) | 690 V |
| RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX | 690 V |
| SHORT-CIRCUIT PROTECTION RATING WITHOUT WELDING | 10 A gG/gL, 500 V, Max. Fuse, Contacts |
| SAFE ISOLATION | 400 V AC, Between coil and auxiliary contacts, According to EN 61140 400 V AC, Between |

Magnet system

| | |
|---|--|
| DUTY FACTOR | 100 % |
| PICK-UP VOLTAGE | 0.8 - 1.1 V AC x Uc (voltage tolerance - single-voltage coil 50 Hz and dual-voltage coil 50 Hz, 60 Hz) |
| POWER CONSUMPTION, PICK-UP, 60 Hz | 30 VA, AC, Single-frequency coil at 60 Hz |
| POWER CONSUMPTION, SEALING, 60 Hz | 1.4 W, AC, Single-frequency coil at 60 Hz 4.4 VA, AC, Single-frequency coil at 60 Hz |
| RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 Hz - MIN | 0 V |
| RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 Hz - MAX | 0 V |
| RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 Hz - MIN | 208 V |
| RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 Hz - MAX | 208 V |
| RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN | 0 V |
| RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX | 0 V |
| SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MIN | 15 ms |
| SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MAX | 21 ms |
| SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MIN | 9 ms |
| SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX | 18 ms |

| | |
|---|--|
| | auxiliary contacts, According to EN 61140 |
| SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE) | 1 A, 250 V DC, (UL/CSA) 15 A, 600 V AC, (UL/CSA) |
| SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY) | P300, DC operated (UL/CSA) A600, AC operated (UL/CSA) |

Communication

| | |
|---------------------------------------|----|
| CONNECTION TO SMARTWIRE-DT | No |
|---------------------------------------|----|

| | |
|--|---|
| Contacts | |
| CODE NUMBER | 22E |
| CONTROL CIRCUIT | $\lambda < 5 \times 10^{-7}$ (1 failure at 2,000,000 operations for |
| RELIABILITY | $U_e = 24$ V DC, $U_{min} = 17$ V, $I_{min} = 5.4$ mA) |
| NUMBER OF AUXILIARY CONTACTS (CHANGE- OVER CONTACTS) | 0 |
| NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS) | 2 |
| NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS) | 2 |
| NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS) | 2 |
| NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS) | 2 |

Design verification

| | |
|---|--|
| EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID | 0 W |
| HEAT DISSIPATION CAPACITY PDISS | 0 W |
| HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID | 0.5 W |
| RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) | 15.5 A |
| STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS | 1.4 W |
| 10.2.2 CORROSION RESISTANCE | Meets the product standard's requirements. |
| 10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES | Meets the product standard's requirements. |
| 10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT | Meets the product standard's requirements. |
| 10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS | Meets the product standard's requirements. |
| 10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION | Meets the product standard's requirements. |
| 10.2.5 LIFTING | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 MECHANICAL IMPACT | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 INSCRIPTIONS | Meets the product standard's requirements. |
| 10.3 DEGREE OF PROTECTION OF ASSEMBLIES | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 CLEARANCES AND CREEPAGE DISTANCES | Meets the product standard's requirements. |
| 10.5 PROTECTION AGAINST ELECTRIC SHOCK | Does not apply, since the entire switchgear needs to be evaluated. |

Resources

CATALOGUES

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[Product Range Catalog](#)
[Switching and protecting motors](#)

CHARACTERISTIC CURVE

[eaton-contactors-dila-relay-characteristic-curve.eps](#)

[eaton-contactors-component-dila-relay-characteristic-curve.eps](#)

DECLARATIONS OF CONFORMITY

[DA-DC-00004792.pdf](#)
[DA-DC-00004810.pdf](#)

DRAWINGS

[eaton-contactors-mounting-dilm-dimensions-002.eps](#)

[eaton-contactors-mounting-dilm-dimensions.eps](#)

[eaton-contactors-frame-dilm-dimensions.eps](#)

[eaton-contactors-module-dilm-dimensions.eps](#)

[eaton-contactors-dilm-3d-drawing-007.eps](#)

ECAD MODEL

[ETN.276393.edz](#)

INSTALLATION INSTRUCTIONS

[eaton-contactors-dila-dilm7-15-dilmp20-instruction-leaflet-il03407013z.pdf](#)

INSTALLATION VIDEOS

[WIN-WIN with push-in technology](#)

MCAD MODEL

[DA-CS-dil_m7_15](#)
[DA-CD-dil_m7_15](#)

SYSTEM OVERVIEW

[eaton-contactors-dila-system-overview.eps](#)

WIRING DIAGRAMS

[2100SWI-108](#)

| | |
|---|--|
| 10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS | Is the panel builder's responsibility. |
| 10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS | Is the panel builder's responsibility. |
| 10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH | Is the panel builder's responsibility. |
| 10.9.3 IMPULSE WITHSTAND VOLTAGE | Is the panel builder's responsibility. |
| 10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL | Is the panel builder's responsibility. |
| 10.10 TEMPERATURE RISE | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 SHORT-CIRCUIT RATING | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 ELECTROMAGNETIC COMPATIBILITY | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 MECHANICAL FUNCTION | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

