


Specifications



Photo is representative



Eaton 276470

Eaton Moeller® series DILA Contactor relay,
110 V 50 Hz, 120 V 60 Hz, 3 N/O, 1 NC,
Spring-loaded terminals, AC operation

General specifications

PRODUCT NAME	Eaton Moeller® series DILA Control relay
CATALOG NUMBER	276470
MODEL CODE	DILAC- 31(110V50HZ,120V60HZ)
EAN	4015082764708
PRODUCT LENGTH/DEPTH	75 mm
PRODUCT HEIGHT	68 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.225 kg
CERTIFICATIONS	CSA-C22.2 No. 14-05 UL CE UL 508 UL File No.: E29184 EN 60947-5-1 CSA Class No.: 3211-03 CSA File No.: 012528 IEC/EN 60947 UL Category Control No.: NKCR CSA IEC/EN 60947-4-1 VDE 0660
CATALOG NOTES	This item can only be ordered until December 31, 2023 with a maximum delivery date of May 31, 2024.

Features & Functions

FEATURES

Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module

FITTED WITH:

Positive operation contacts

General

APPLICATION

Contactors relays

DEGREE OF PROTECTION

IP20

SHOCK RESISTANCE

5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

LIFESPAN, MECHANICAL

20,000,000 Operations (AC operated)

MOUNTING METHOD

DIN-rail/screw

CONNECTION

Spring-loaded terminals

OPERATING FREQUENCY

9000 Operations/h

OVERVOLTAGE CATEGORY

III

POLLUTION DEGREE

3

PRODUCT CATEGORY

DILA relays

PROTECTION

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)

6000 V AC

VOLTAGE TYPE

AC

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
--	--------

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
--	-------

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	25 °C
---	-------

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
---	-------

AMBIENT STORAGE TEMPERATURE - MIN	40 °C
--	-------

AMBIENT STORAGE TEMPERATURE - MAX	80 °C
--	-------

CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
--------------------------	--

Terminal capacities

TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	2 x (0.75 - 1.5) mm ² , Spring-loaded terminals with or without ferrule DIN 46228 1 x (0.75 - 1.5) mm ² , Spring-loaded terminals with or without ferrule DIN 46228
--	--

TERMINAL CAPACITY (SOLID)	1 x (0.75 - 2.5) mm ² , Spring-loaded terminals 2 x (0.75 - 2.5) mm ² , Spring-loaded terminals
----------------------------------	--

TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 14, Spring-loaded terminals
---	----------------------------------

STRIPPING LENGTH (MAIN CABLE)	10 mm
--------------------------------------	-------

SCREWDRIVER SIZE	0.6 x 3.5 mm, Spring-loaded terminals
-------------------------	---------------------------------------

Electrical rating

RATED OPERATIONAL CURRENT (IE)	3 A at 110 V, DC L/R ≤ 15 ms (with 1 contact in series)
	1 A at 220 V, DC L/R ≤ 15 ms (with 1 contact in series)
	10 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in series)
	10 A at 60 V, DC L/R ≤ 15 ms (with 2 contacts in series)
	5 A at 220 V, DC L/R ≤ 15 ms (with 3 contacts in series)
	2 A at 110 V, DC L/R ≤ 50 ms (with 3 contacts in series)
	4 A at 60 V, DC L/R ≤ 50 ms (with 3 contacts in series)
	4 A at 24 V, DC L/R ≤ 50 ms (with 3 contacts in series)
	1 A at 220 V, DC L/R ≤ 50 ms (with 3 contacts in series)
	6 A at 110 V, DC L/R ≤ 15 ms (with 3 contacts in series)
	6 A at 60 V, DC L/R ≤ 15 ms (with 1 contact in series)
	16 A

RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V

4 A

RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V

4 A

RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V

1.5 A

RATED INSULATION VOLTAGE (UI)

690 V

RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX

690 V

SHORT-CIRCUIT PROTECTION RATING WITHOUT WELDING

10 A gG/gL, 500 V, Max. Fuse, Contacts

SAFE ISOLATION

400 V AC, Between auxiliary contacts, According to EN 61140
400 V AC, Between coil

Magnet system

DUTY FACTOR

100 %

PICK-UP VOLTAGE

0.8 - 1.1 V AC x U_c (voltage tolerance - single-voltage coil 50 Hz and dual-voltage coil 50 Hz, 60 Hz)

POWER CONSUMPTION, PICK-UP, 50 HZ

24 VA, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz

POWER CONSUMPTION, PICK-UP, 60 HZ

24 VA, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz

POWER CONSUMPTION, SEALING, 50 HZ

1.4 W, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz
3.4 VA, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz

POWER CONSUMPTION, SEALING, 60 HZ

1.4 W, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN

110 V

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX

110 V

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN

120 V

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX

120 V

RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN

0 V

RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX

0 V

SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MIN

15 ms

SWITCHING TIME (AC OPERATED, MAKE

21 ms

	and auxiliary contacts, According to EN 61140
SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)	15 A, 600 V AC, (UL/CSA) 1 A, 250 V DC, (UL/CSA)
SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	A600, AC operated (UL/CSA) P300, DC operated (UL/CSA)

Communication	
CONNECTION TO SMARTWIRE-DT	No

CONTACTS, CLOSING DELAY) - MAX	
SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MIN	9 ms
SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX	18 ms

Contacts	
CODE NUMBER	31E
CONTROL CIRCUIT RELIABILITY	$\lambda < 5 \times 10^{-7}$ (1 failure at 2,000,000 operations for $U_e = 24$ V DC, $U_{min} = 17$ V, $I_{min} = 5.4$ mA)
NUMBER OF AUXILIARY CONTACTS (CHANGE- OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	3
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	3

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.5 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	15.5 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	1.4 W
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.

Resources

CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf Product Range Catalog Switching and protecting motors
CHARACTERISTIC CURVE	eaton-contactors-component-dila-relay-characteristic-curve.eps eaton-contactors-dila-relay-characteristic-curve.eps
DECLARATIONS OF CONFORMITY	DA-DC-00004810.pdf DA-DC-00004792.pdf
DRAWINGS	eaton-contactors-frame-dilm-dimensions.eps eaton-contactors-mounting-dilm-dimensions-002.eps eaton-contactors-mounting-dilm-dimensions.eps eaton-contactors-contact-dilm-dimensions.eps eaton-contactors-dilm-3d-drawing-008.eps
ECAD MODEL	ETN.276470.edz
INSTALLATION INSTRUCTIONS	eaton-contactors-dila-dilm7-15-dilmp20-instruction-leaflet-il03407013z.pdf
INSTALLATION VIDEOS	WIN-WIN with push-in technology
MCAD MODEL	DA-CD-dil_mc7_15 DA-CS-dil_mc7_15
SYSTEM OVERVIEW	eaton-contactors-dila-system-overview.eps 2100SWI-110
WIRING DIAGRAMS	eaton-contactors-contact-diler-relay-wiring-diagram-002.eps

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

