

# Specifications



Photo is representative



## Eaton 276564

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 3 kW, 1 N/O, 12 V DC, DC operation, Screw terminals

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series DILM contactor
<b>CATALOG NUMBER</b>	276564
<b>MODEL CODE</b>	DILM7-10(12VDC)
<b>EAN</b>	4015082765644
<b>PRODUCT LENGTH/DEPTH</b>	75 mm
<b>PRODUCT HEIGHT</b>	68 mm
<b>PRODUCT WIDTH</b>	45 mm
<b>PRODUCT WEIGHT</b>	0.296 kg
<b>CERTIFICATIONS</b>	UL 508 CSA Class No.: 2411-03, 3211-04 CSA-C22.2 No. 14-05 IEC/EN 60947 CSA CSA File No.: 012528 UL IEC/EN 60947-4-1 UL Category Control No.: NLDX UL File No.: E29096 VDE 0660 CE
<b>CATALOG NOTES</b>	Contacts according to EN 50012
<b>GLOBAL CATALOG</b>	276564

## Product specifications

<b>ELECTRICAL</b>	
<b>CONNECTION TYPE FOR AUXILIARY- AND CONTROL-CURRENT CIRCUIT</b>	Screw connection
<b>NUMBER OF POLES</b>	Three-pole
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.

## Resources

### CATALOGS

[SmartWire-DT Catalog](#)  
[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

### CHARACTERISTIC CURVE

[eaton-contactors-short-time-loading-dilm-characteristic-curve.eps](#)  
[eaton-contactors-switch-dilm-characteristic-curve.eps](#)  
[eaton-contactors-switch-dilm-characteristic-curve-002.eps](#)  
[eaton-contactors-component-dilm-characteristic-curve-003.eps](#)

### DECLARATIONS OF CONFORMITY

[DA-DC-00004810.pdf](#)  
[DA-DC-00004792.pdf](#)

### DRAWINGS

[eaton-contactors-mounting-dilm-dimensions-002.eps](#)  
[eaton-contactors-mounting-dilm-dimensions.eps](#)  
[eaton-contactors-module-dilm-dimensions.eps](#)  
[eaton-contactors-frame-dilm-dimensions.eps](#)  
[eaton-contactors-module-dilm-dimensions-002.eps](#)  
[eaton-general-ie-ready-dilm-contactor-standards.eps](#)  
[eaton-contactors-dilm-3d-drawing-007.eps](#)

### ECAD MODEL

[ETN.276564.edz](#)

### INSTALLATION INSTRUCTIONS

[eaton-contactors-dila-dilm7-15-dilmp20-il03407013z.pdf](#)

<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>FITTED WITH:</b>	Varistor suppressor circuit
<b>OPERATING FREQUENCY</b>	9000 mechanical Operations/h (DC operated)
<b>POLLUTION DEGREE</b>	3
<b>CLIMATIC PROOFING</b>	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>CONNECTION TO SMARTWIRE-DT</b>	No
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	8000 V AC
<b>UTILIZATION CATEGORY</b>	AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-4: Normal AC induction motors: starting, plugging, reversing, inching AC-3: Normal AC induction motors: starting, switch off during running
<b>CONNECTION</b>	Screw terminals

<b>INSTALLATION VIDEOS</b>	<a href="#">WIN-WIN with push-in technology</a>
<b>MCAD MODEL</b>	<a href="#">DA-CS-dil_m7_15</a> <a href="#">DA-CD-dil_m7_15</a>
<b>SYSTEM OVERVIEW</b>	<a href="#">eaton-contactors-dilm-contactor-system-overview.eps</a>
<b>WIRING DIAGRAMS</b>	<a href="#">eaton-contactors-contact-dilm-wiring-diagram.eps</a>

<b>FRAME SIZE</b>	FS1
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	60 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b>	40 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b>	25 °C
<b>AMBIENT STORAGE TEMPERATURE - MAX</b>	80 °C
<b>AMBIENT STORAGE TEMPERATURE - MIN</b>	40 °C
<b>ASSIGNED MOTOR POWER AT 115/120 V, 60 HZ, 1-PHASE</b>	0.25 HP
<b>ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 3-PHASE</b>	1.5 HP
<b>ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 1-PHASE</b>	1 HP
<b>ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 3-PHASE</b>	2 HP
<b>ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE</b>	3 HP
<b>ASSIGNED MOTOR POWER AT 575/600 V, 60 HZ, 3-PHASE</b>	5 HP
<b>CONVENTIONAL THERMAL CURRENT ITH (1-POLE, ENCLOSED)</b>	45 A
<b>CONVENTIONAL THERMAL CURRENT ITH (3-POLE, ENCLOSED)</b>	18 A
<b>CONVENTIONAL THERMAL CURRENT ITH AT 55°C (3-POLE, OPEN)</b>	21 A
<b>CONVENTIONAL THERMAL CURRENT ITH OF MAIN CONTACTS (1-POLE, OPEN)</b>	50 A
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	0.3 W

<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0.1 W
<b>SWITCHING TIME (DC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MAX</b>	31 ms
<b>SWITCHING TIME (DC OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX</b>	12 ms
<b>APPLICATION</b>	Contactors for Motors
<b>PRODUCT CATEGORY</b>	Contactors
<b>PROTECTION</b>	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
<b>ARCING TIME</b>	10 ms
<b>ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT</b>	Screw connection
<b>SCREWDRIVER SIZE</b>	0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver
<b>VOLTAGE TYPE</b>	DC
<b>DEGREE OF PROTECTION</b>	IP20
<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)</b>	0
<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)</b>	1
<b>NUMBER OF CONTACTS (NORMALLY CLOSED) AS MAIN CONTACT</b>	0
<b>NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)</b>	1
<b>NUMBER OF MAIN CONTACTS (NORMALLY OPEN CONTACT)</b>	3
<b>POWER CONSUMPTION (PICK-UP) AT DC</b>	3 W
<b>POWER CONSUMPTION</b>	3 W

<b>(SEALING) AT DC</b>	
<b>RATED BREAKING CAPACITY AT 220/230 V</b>	70 A
<b>RATED BREAKING CAPACITY AT 380/400 V</b>	70 A
<b>RATED BREAKING CAPACITY AT 500 V</b>	50 A
<b>RATED BREAKING CAPACITY AT 660/690 V</b>	40 A
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50</b>	0 V
<b>HZ - MAX</b>	
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50</b>	0 V
<b>HZ - MIN</b>	
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60</b>	0 V
<b>HZ - MAX</b>	
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60</b>	0 V
<b>HZ - MIN</b>	
<b>DROP-OUT VOLTAGE</b>	At least smoothed two-phase bridge rectifier or three-phase rectifier 0.6 - 0.15 x UC, DC operated
<b>OVERVOLTAGE CATEGORY</b>	III
<b>DUTY FACTOR</b>	100 %
<b>EMITTED INTERFERENCE</b>	According to EN 60947-1
<b>INTERFERENCE IMMUNITY</b>	According to EN 60947-1
<b>LIFESPAN, MECHANICAL</b>	10,000,000 Operations (DC operated)
<b>PICK-UP VOLTAGE</b>	0.85 - 1.1 V DC x Uc (only with auxiliary contact module with 3 or more N/C contacts) 0.8 - 1.1 V DC x Uc
<b>SAFE ISOLATION</b>	400 V AC, Between coil and contacts, According to EN 61140 400 V AC, Between the contacts, According to EN 61140
<b>SCREW SIZE</b>	M3.5, Terminal screw
<b>SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)</b>	1 A, 250 V DC, (UL/CSA) 10 A, 600 V AC, (UL/CSA)

<b>SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)</b>	P300, DC operated (UL/CSA) A600, AC operated (UL/CSA)
<b>TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)</b>	1 x (0.75 - 2.5) mm <sup>2</sup> 2 x (0.75 - 2.5) mm <sup>2</sup> 2 x (0.75 - 2,5) mm <sup>2</sup>
<b>SHOCK RESISTANCE</b>	5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms 3.4 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop- mounted, Half-sinusoidal shock 10 ms 5.7 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half- sinusoidal shock 10 ms 3.4 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop- mounted, Half-sinusoidal shock 10 ms 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms
<b>TERMINAL CAPACITY (SOLID)</b>	1 x (0.75 - 4) mm <sup>2</sup> 2 x (0.75 - 2.5) mm <sup>2</sup>
<b>TERMINAL CAPACITY (SOLID/STRANDED AWG)</b>	Single 18 - 10, double 18 - 14
<b>SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE)</b>	20 A, Maximum motor rating (UL/CSA)
<b>TIGHTENING TORQUE</b>	1.2 Nm, Screw terminals
<b>RATED CONTROL SUPPLY</b>	
<b>VOLTAGE (US) AT DC - MAX</b>	12 V
<b>RATED CONTROL SUPPLY</b>	
<b>VOLTAGE (US) AT DC - MIN</b>	0 V
<b>RATED INSULATION VOLTAGE (UI)</b>	690 V
<b>RATED MAKING</b>	112 A

---

**CAPACITY UP TO 690 V**

**(COS PHI TO IEC/EN**

**60947)**

---

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-1, 22 A**  
**380 V, 400 V, 415 V**

---

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-3, 7 A**  
**220 V, 230 V, 240 V**

---

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-3, 7 A**  
**380 V, 400 V, 415 V**

---

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-3, 7 A**  
**440 V**

---

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-3, 5 A**  
**500 V**

---

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-3, 4 A**  
**660 V, 690 V**

---

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-4, 5 A**  
**220 V, 230 V, 240 V**

---

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-4, 5 A**  
**400 V**

---

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-4, 5 A**  
**440 V**

---

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-4, 4.5 A**  
**500 V**

---

**RATED OPERATIONAL**

**CURRENT (IE) AT AC-4, 4 A**  
**660 V, 690 V**

---

**RATED OPERATIONAL**

**CURRENT (IE) AT DC-1, 20 A**  
**110 V**

---

**RATED OPERATIONAL**

**CURRENT (IE) AT DC-1, 15 A**  
**220 V**

---

**RATED OPERATIONAL**

**CURRENT (IE) AT DC-1, 20 A**  
**V**

---

**RATED OPERATIONAL**

**CURRENT FOR SPECIFIED 7 A**  
**HEAT DISSIPATION (IN)**

---

**RATED OPERATIONAL**

**POWER AT AC-3, 240 V, 50 2.2 kW**

**Hz**

**RATED OPERATIONAL**

**POWER AT AC-3, 380/400 V, 50 Hz** 3 kW

**RATED OPERATIONAL**

**POWER AT AC-3, 415 V, 50 Hz** 4 kW

**Hz**

**RATED OPERATIONAL**

**POWER AT AC-4, 220/230 V, 50 Hz** 1 kW

**RATED OPERATIONAL**

**POWER AT AC-4, 240 V, 50 Hz** 1.5 kW

**Hz**

**RATED OPERATIONAL**

**POWER AT AC-4, 380/400 V, 50 Hz** 2.2 kW

**RATED OPERATIONAL**

**POWER AT AC-4, 415 V, 50 Hz** 2.3 kW

**RATED OPERATIONAL**

**POWER AT AC-4, 440 V, 50 Hz** 2.4 kW

**RATED OPERATIONAL**

**POWER AT AC-4, 500 V, 50 Hz** 2.5 kW

**RATED OPERATIONAL**

**POWER AT AC-4, 660/690 V, 50 Hz** 2.9 kW

**RATED OPERATIONAL**

**POWER (NEMA)** 2.2 kW

**RATED OPERATIONAL**

**VOLTAGE (UE) AT AC - MAX** 690 V

**RESISTANCE PER POLE**

4.6 mΩ

**STATIC HEAT**

**DISSIPATION, NON-CURRENT-DEPENDENT PVS** 3 W

**STRIPPING LENGTH**

**(CONTROL CIRCUIT CABLE)** 10 mm

**STRIPPING LENGTH**

**(MAIN CABLE)** 10 mm

5 kA, SCCR (UL/CSA)

45 A, max. Fuse, SCCR

(UL/CSA)

60 A, max. CB, SCCR

(UL/CSA)

**SHORT-CIRCUIT CURRENT RATING (BASIC RATING)**

25 A, Class RK5/ 20 A Class J, max. Fuse, SCCR

<b>480 V</b>	(UL/CSA) 65 kA, CB, SCCR (UL/CSA) 30/100 kA, Fuse, SCCR (UL/CSA) 16 A, max. CB, SCCR (UL/CSA)
<b>SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V)</b>	30/100 kA, Fuse, SCCR (UL/CSA) 25 A, Class RK5/20 A, Class J, max. Fuse, SCCR (UL/CSA)
<b>SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 400 V</b>	35 A gG/gL
<b>SUITABLE FOR</b>	Also motors with efficiency class IE3
<b>SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 690 V</b>	20 A gG/gL
<b>SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 400 V</b>	20 A gG/gL
<b>SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 690 V</b>	16 A gG/gL
<b>SPECIAL PURPOSE RATING OF BALLAST</b>	12 A (600V 60Hz 3phase, 347V 60Hz 1phase)
<b>ELECTRICAL DISCHARGE LAMPS</b>	12 A (480V 60Hz 3phase, 277V 60Hz 1phase)
<b>SPECIAL PURPOSE RATING OF DEFINITE PURPOSE RATING</b>	42 A, LRA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 7 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA)
<b>SPECIAL PURPOSE RATING OF ELEVATOR CONTROL</b>	3 HP, 600 V 60 Hz 3-ph, (UL/CSA) 0.75 HP, 200 V 60 Hz 3-ph, (UL/CSA) 1.5 HP, 240 V 60 Hz 3-ph, (UL/CSA) 2 HP, 480 V 60 Hz 3-ph, (UL/CSA) 3.7 A, 200 V 60 Hz 3-ph, (UL/CSA) 6 A, 240 V 60 Hz 3-ph, (UL/CSA) 3.4 A, 480 V 60 Hz 3-ph, (UL/CSA)

	3.9 A, 600 V 60 Hz 3-ph, (UL/CSA)
<b>SPECIAL PURPOSE RATING OF REFRIGERATION CONTROL (CSA ONLY)</b>	10 A, FLA 480 V 60 Hz 3phase; (CSA) 60 A, LRA 600 V 60 Hz 3phase; (CSA) 60 A, LRA 480 V 60 Hz 3phase; (CSA) 10 A, FLA 600 V 60 Hz 3phase; (CSA)
<b>SPECIAL PURPOSE RATING OF RESISTANCE AIR HEATING</b>	12 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA) 12 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)
<b>SPECIAL PURPOSE RATING OF TUNGSTEN INCANDESCENT LAMPS</b>	14 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA) 14 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)
<b>CONVENTIONAL</b> <b>THERMAL CURRENT ITH</b>	22 A
<b>AT 40°C (3-POLE, OPEN)</b>	
<b>CONVENTIONAL</b> <b>THERMAL CURRENT ITH</b>	21 A
<b>AT 50°C (3-POLE, OPEN)</b>	
<b>CONVENTIONAL</b> <b>THERMAL CURRENT ITH</b>	20 A
<b>AT 60°C (3-POLE, OPEN)</b>	
<b>RATED OPERATIONAL</b> <b>POWER AT AC-3, 440 V, 50</b>	4.5 kW
<b>Hz</b>	
<b>RATED OPERATIONAL</b> <b>POWER AT AC-3, 500 V, 50</b>	3.5 kW
<b>Hz</b>	
<b>RATED OPERATIONAL</b> <b>POWER AT AC-3, 690 V, 50</b>	3.5 kW
<b>Hz</b>	
<b>ACTUATING VOLTAGE</b>	12 V DC
<b>ALTITUDE</b>	Max. 2000 m
<b>OPERATING VOLTAGE AT</b> <b>AC, 50 Hz - MIN</b>	24 V
<b>OPERATING VOLTAGE AT</b> <b>AC, 50 Hz - MAX</b>	690 V
<b>OPERATING VOLTAGE AT</b> <b>AC, 60 Hz - MIN</b>	24 V
<b>OPERATING VOLTAGE AT</b> <b>AC, 60 Hz - MAX</b>	690 V

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc**

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

