

# Specifications

Photo is representative

## Eaton 278885

Eaton Moeller series xEffect - FAZ MCB. FAZ, 3-pole, tripping characteristic: D, rated current In: 2.5 A

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller series xEffect - FAZ MCB
<b>CATALOG NUMBER</b>	278885
<b>MODEL CODE</b>	FAZ-D2,5/3
<b>EAN</b>	4015082788858
<b>PRODUCT LENGTH/DEPTH</b>	80 mm
<b>PRODUCT HEIGHT</b>	75.5 mm
<b>PRODUCT WIDTH</b>	54 mm
<b>PRODUCT WEIGHT</b>	0.339 kg
<b>COMPLIANCES</b>	UL CSA09 (with supplementary protector only) RoHS conform
<b>CERTIFICATIONS</b>	CSA (File No. 204453) CSA-C22.2 No. 235 UL (File No. E177451) North America (UL recognized, CSA certified) IEC/EN 60947-2 UL (Category Control Number QVNU2, QVNU8) UL 1077 CSA (Class No. 3215-30) CE marking IEC/EN 60898 EN45545-2 IEC 61373

## Delivery Programme

### APPLICATION

- Branch circuits, not as BCPD
- Switchgear for industrial and advanced commercial applications
- xEffect - Switchgear for industrial and advanced commercial applications

**NUMBER OF POLES** Three-pole

**NUMBER OF POLES (TOTAL)** 3

**NUMBER OF POLES (PROTECTED)** 3

**TRIPPING CHARACTERISTIC** D

**RELEASE CHARACTERISTIC** D

**AMPERAGE RATING** 2.5 A

### TYPE

- FAZ
- Miniature circuit breaker

## Technical data - electrical

**VOLTAGE TYPE** AC

**VOLTAGE RATING** 240 V AC / 415 V AC

**VOLTAGE RATING (UL CSA 13)** 480 Y/277 V AC

**RATED OPERATIONAL VOLTAGE (UE) - MAX** 400 V

**RATED INSULATION VOLTAGE (UI)** 440 V

**RATED IMPULSE WITHSTAND VOLTAGE (UIMP)** 4 kV

**FREQUENCY RATING - MIN** 50 Hz

**FREQUENCY RATING - MAX** 60 Hz

**RATED SWITCHING CAPACITY (IEC/EN 60947-2)** 15 kA

**RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 230 V** 10 kA

**RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 400 V** 10 kA

**RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 230 V** 15 kA

**RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 400 V** 15 kA

**OVERVOLTAGE CATEGORY** III

**POLLUTION DEGREE** 2

## Technical data - mechanical

**WIDTH IN NUMBER OF  
MODULAR SPACINGS** 3

**BUILT-IN DEPTH** 70.5 mm

**DEGREE OF PROTECTION** UL/CSA Type: -  
IP20 (IEC)  
IP20

**CONNECTABLE  
CONDUCTOR CROSS  
SECTION (SOLID-CORE) -  
MIN** 1 mm<sup>2</sup>

**CONNECTABLE  
CONDUCTOR CROSS  
SECTION (SOLID-CORE) -  
MAX** 25 mm<sup>2</sup>

**CONNECTABLE  
CONDUCTOR CROSS  
SECTION (MULTI-WIRED)  
- MIN** 1 mm<sup>2</sup>

**CONNECTABLE  
CONDUCTOR CROSS  
SECTION (MULTI-WIRED)  
- MAX** 25 mm<sup>2</sup>

## Design verification as per IEC/EN 61439 - technical data

**RATED OPERATIONAL  
CURRENT FOR SPECIFIED  
HEAT DISSIPATION (IN)** 2.5 A

**HEAT DISSIPATION PER  
POLE, CURRENT-  
DEPENDENT** 0 W

**EQUIPMENT HEAT  
DISSIPATION, CURRENT-  
DEPENDENT** 2.9 W

**STATIC HEAT  
DISSIPATION, NON-  
CURRENT-DEPENDENT** 0 W

**HEAT DISSIPATION  
CAPACITY** 0 W

**AMBIENT OPERATING  
TEMPERATURE - MIN** -25 °C

**AMBIENT OPERATING  
TEMPERATURE - MAX** 75 °C

## Design verification as per IEC/EN 61439

<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF</b>	Is the panel builder's responsibility.

## Additional information

<b>CURRENT LIMITING CLASS</b>	3
<b>FEATURES</b>	Additional equipment possible
<b>SPECIAL FEATURES</b>	Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity
<b>USED WITH</b>	FAZ Miniature circuit breaker

---

**INSULATING MATERIAL**

---

**10.10 TEMPERATURE RISE**

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

**10.11 SHORT-CIRCUIT RATING**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.12 ELECTROMAGNETIC COMPATIBILITY**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.13 MECHANICAL FUNCTION**

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

---

## Resources

CATALOGUES	<a href="#">eaton-xeffect-industrial-switchgear-range-catalog-ca003002en-en-us.pdf</a>
CHARACTERISTIC CURVE	<a href="#">eaton-xeffect-faz-mcb-characteristic-curve.jpg</a>
DECLARATIONS OF CONFORMITY	<a href="#">DA-DC-03 FAZ-DU</a> <a href="#">DA-DC-03 FAZ-B-C-D</a>
DRAWINGS	<a href="#">eaton-xeffect-faz-mcb-dimensions-003.jpg</a> <a href="#">eaton-mcb-faz-xeffect-faz-3d-drawing-003.eps</a> <a href="#">eaton-xeffect-faz-mcb-3d-drawing-012.jpg</a> <a href="#">eaton-xeffect-faz-mcb-3d-drawing-011.jpg</a> <a href="#">eaton-xeffect-faz-mcb-3d-drawing-003.jpg</a>
ECAD MODEL	<a href="#">DA-CE-ETN.FAZ-D2,5 3</a>
INSTALLATION INSTRUCTIONS	<a href="#">eaton-rccb-rcho-g9-il019140zu.pdf</a>
MCAD MODEL	<a href="#">eaton-faz_mcb_3p-drawing.dwg</a> <a href="#">eaton-faz_mcb_3p-3d-model.stp</a>
PEP ECO-PASSPORT	<a href="#">EATO-00047-V01.01-EN</a>
WIRING DIAGRAMS	<a href="#">eaton-xpole-mmc4-6-m-mcb-wiring-diagram-005.jpg</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

