

# Specifications

Photo is representative

## Eaton 278989

Eaton Moeller series xEffect - FAZ MCB. FAZ, 3-pole+N, tripping characteristic: D, rated current In: 3.5 A

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller series xEffect - FAZ MCB
<b>CATALOG NUMBER</b>	278989
<b>MODEL CODE</b>	FAZ-D3,5/3N
<b>EAN</b>	4015082789893
<b>PRODUCT LENGTH/DEPTH</b>	80 mm
<b>PRODUCT HEIGHT</b>	75.5 mm
<b>PRODUCT WIDTH</b>	72 mm
<b>PRODUCT WEIGHT</b>	0.428 kg
<b>COMPLIANCES</b>	RoHS conform
<b>CERTIFICATIONS</b>	EN45545-2 IEC 61373

## Delivery Programme

### APPLICATION

- Switchgear for industrial and advanced commercial applications
- xEffect - Switchgear for industrial and advanced commercial applications

NUMBER OF POLES	Three-pole + N
-----------------	----------------

NUMBER OF POLES (TOTAL)	4
-------------------------	---

NUMBER OF POLES (PROTECTED)	3
-----------------------------	---

TRIPPING CHARACTERISTIC	D
-------------------------	---

RELEASE CHARACTERISTIC	D
------------------------	---

AMPERAGE RATING	3.5 A
-----------------	-------

TYPE	<ul style="list-style-type: none"> <li>• FAZ</li> <li>• Miniature circuit breaker</li> </ul>
------	--

## Technical data - electrical

VOLTAGE TYPE	AC
--------------	----

RATED OPERATIONAL VOLTAGE (UE) - MAX	400 V
--------------------------------------	-------

RATED INSULATION VOLTAGE (UI)	440 V
-------------------------------	-------

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4 kV
--	------

FREQUENCY RATING - MIN	50 Hz
------------------------	-------

FREQUENCY RATING - MAX	60 Hz
------------------------	-------

RATED SWITCHING CAPACITY (IEC/EN 60947-2)	15 kA
---	-------

RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 230 V	10 kA
---	-------

RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 400 V	10 kA
---	-------

RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 230 V	15 kA
--	-------

RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 400 V	15 kA
--	-------

OVERVOLTAGE CATEGORY	III
----------------------	-----

POLLUTION DEGREE	2
------------------	---

## Technical data - mechanical

<b>WIDTH IN NUMBER OF MODULAR SPACINGS</b>	4
--	---

<b>BUILT-IN DEPTH</b>	70.5 mm
-----------------------	---------

<b>DEGREE OF PROTECTION</b>	IP20
-----------------------------	------

<b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN</b>	1 mm <sup>2</sup>
---	-------------------

<b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX</b>	25 mm <sup>2</sup>
---	--------------------

<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN</b>	1 mm <sup>2</sup>
--	-------------------

<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX</b>	25 mm <sup>2</sup>
--	--------------------

## Design verification as per IEC/EN 61439 - technical data

<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	3.5 A
--	-------

<b>HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT</b>	0 W
--	-----

<b>EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT</b>	4 W
---	-----

<b>STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT</b>	0 W
--	-----

<b>HEAT DISSIPATION CAPACITY</b>	0 W
--------------------------------------	-----

<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
--	--------

<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	75 °C
--	-------

## Design verification as per IEC/EN 61439

<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF</b>	Is the panel builder's responsibility.

## Additional information

<b>CURRENT LIMITING CLASS</b>	3
<b>FEATURES</b>	Concurrently switching N-neutral Additional equipment possible
<b>SPECIAL FEATURES</b>	Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity
<b>USED WITH</b>	Miniature circuit breaker FAZ

---

**INSULATING MATERIAL**

---

**10.10 TEMPERATURE RISE**

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

**10.11 SHORT-CIRCUIT RATING**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.12 ELECTROMAGNETIC COMPATIBILITY**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.13 MECHANICAL FUNCTION**

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

---

## Resources

CATALOGUES	<a href="#">eaton-xeffect-industrial-switchgear-range-catalog-ca003002en-en-us.pdf</a>
CHARACTERISTIC CURVE	<a href="#">eaton-xeffect-faz-mcb-characteristic-curve.jpg</a>
DECLARATIONS OF CONFORMITY	<a href="#">DA-DC-03 FAZ-B-C-D</a> <a href="#">DA-DC-03 FAZ-DU</a>
DRAWINGS	<a href="#">eaton-xeffect-faz-mcb-dimensions-004.jpg</a> <a href="#">eaton-xeffect-faz-mcb-3d-drawing-012.jpg</a> <a href="#">eaton-xeffect-faz-mcb-3d-drawing-011.jpg</a> <a href="#">eaton-xeffect-faz-mcb-3d-drawing-003.jpg</a>
ECAD MODEL	<a href="#">DA-CE-ETN.FAZ-D3,5 3N</a>
INSTALLATION INSTRUCTIONS	<a href="#">eaton-rccb-rcbo-g9-il019140zu.pdf</a>
MCAD MODEL	<a href="#">eaton-fazt_mcb_3pn-3d-model.stp</a> <a href="#">eaton-faz_mcb_3pn-drawing.dwg</a>
PEP ECO-PASSPORT	<a href="#">EATO-00047-V01.01-EN</a>
WIRING DIAGRAMS	<a href="#">eaton-xpole-mmc4-6-m-mcb-wiring-diagram-004.jpg</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

