

TT-SLKK 5-C 3N3-230AC - EMC filter



2798792

<https://www.phoenixcontact.com/us/products/2798792>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Terminal block with radio interference suppression capacitor between clamping connector and DIN rail, separate ground connection, nominal voltage: 3.3 nF, for mounting on NS 35/7.5, terminal width: 6.2 mm, terminal height: 69 mm

Your advantages

- Space-saving and cost-saving with a narrow overall width of just 6 mm
- Cost-optimized with tailored product features
- No useful signal interference with balanced low-pass

Commercial data

Item number	2798792
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	CL02
Product key	CL2227
Catalog page	Page 113 (TT-2011)
GTIN	4017918101480
Weight per piece (including packing)	19.26 g
Weight per piece (excluding packing)	19.26 g
Customs tariff number	85363010
Country of origin	DE

TT-SLKK 5-C 3N3-230AC - EMC filter



2798792

<https://www.phoenixcontact.com/us/products/2798792>

Technical data

Product properties

Product type	EMC filters
Type	Single-level terminal block – separate PE connection
Number of positions	1

Insulation characteristics

Overvoltage category	III
Pollution degree	2

Electrical properties

Nominal voltage U_N	230 V AC
-----------------------	----------

Connection data

Connection method	Screw connection
Screw thread	M3
Tightening torque	0.5 Nm
Conductor cross section flexible	0.2 mm ² ... 4 mm ²
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section AWG	24 ... 12

Dimensions

Width	6.2 mm
Height	66.5 mm
Depth	69.5 mm

Material specifications

Color	black (RAL 9005)
Flammability rating according to UL 94	V-2
Housing material	PA

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Protective circuit

Direction of action	Line-Earth Ground
Maximum continuous voltage U_C	250 V AC
Rated current	30 A (45 °C)
Residual current I_{PE}	typ. 0.5 mA
Cut-off frequency f_g (3 dB), asym. (PE) in 50 Ω system	typ. 2 MHz
Cut-off frequency f_g (3 dB), asym. (PE) in 150 Ω system	typ. 550 kHz (50 Hz)
Cut-off frequency f_g (3 dB), asym. (PE) in 600 Ω system	typ. 170 kHz

TT-SLKK 5-C 3N3-230AC - EMC filter



2798792

<https://www.phoenixcontact.com/us/products/2798792>

Capacity (Core-Earth)	typ. 3.3 nF
	Y2

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20 (with end cover)
Ambient temperature (operation)	-20 °C ... 85 °C

Standards and regulations


Standards/specifications	EN 60947-7-1
Note	2009
Standards/specifications	EN 60947-4-2
Note	2009
Standards/specifications	EN 60384-14

Mounting

Mounting type	DIN rail: 35 mm
---------------	-----------------

Drawings

Diagram




TT-SLKK 5-C 3N3-230AC - EMC filter

2798792

<https://www.phoenixcontact.com/us/products/2798792>



Circuit diagram



TT-SLKK 5-C 3N3-230AC - EMC filter



2798792

<https://www.phoenixcontact.com/us/products/2798792>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2798792>



EAC

Approval ID: EAC-Zulassung



EAC

Approval ID: RU C-DE.*09.B.00169

TT-SLKK 5-C 3N3-230AC - EMC filter



2798792

<https://www.phoenixcontact.com/us/products/2798792>

Classifications

ECLASS

ECLASS-11.0	27130807
ECLASS-13.0	27171501

ETIM

ETIM 9.0	EC001625
----------	----------

UNSPSC

UNSPSC 21.0	39121600
-------------	----------

TT-SLKK 5-C 3N3-230AC - EMC filter



2798792

<https://www.phoenixcontact.com/us/products/2798792>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

TT-SLKK 5-C 3N3-230AC - EMC filter



2798792

<https://www.phoenixcontact.com/us/products/2798792>

Accessories

DP-UKK 3/5 BK - Spacer plate

2770833

<https://www.phoenixcontact.com/us/products/2770833>

Spacer plate, to compensate for level offsets, depth: 25 mm, width: 2.5 mm, height: 56 mm, color: black



D-UKK 3/5 BK - End cover

2770228

<https://www.phoenixcontact.com/us/products/2770228>

End cover, width: 2.5 mm, height: 66.5 mm, color: black



TT-SLKK 5-C 3N3-230AC - EMC filter



2798792

<https://www.phoenixcontact.com/us/products/2798792>

ZBF 6:UNBEDRUCKT - Zack Marker strip, flat

0808710

<https://www.phoenixcontact.com/us/products/0808710>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 10

ZBF 6/WH-100:UNBEDRUCKT - Zack Marker strip, flat

0808736

<https://www.phoenixcontact.com/us/products/0808736>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 1000

TT-SLKK 5-C 3N3-230AC - EMC filter

2798792

<https://www.phoenixcontact.com/us/products/2798792>



ZBF 6,LGS:FORTL.ZAHLEN - Zack Marker strip, flat

0808749

<https://www.phoenixcontact.com/us/products/0808749>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 10

ZB 6:UNBEDRUCKT - Zack marker strip

1051003

<https://www.phoenixcontact.com/us/products/1051003>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

TT-SLKK 5-C 3N3-230AC - EMC filter

2798792

<https://www.phoenixcontact.com/us/products/2798792>



ZB 6,LGS:L1-N,PE - Marker for terminal blocks

1051414

<https://www.phoenixcontact.com/us/products/1051414>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

ZB 6,LGS:U-N - Marker for terminal blocks

1051430

<https://www.phoenixcontact.com/us/products/1051430>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: U, V, W, N, GND, U, V, W, N, GND, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

TT-SLKK 5-C 3N3-230AC - EMC filter

2798792

<https://www.phoenixcontact.com/us/products/2798792>



ZB 6,LGS:FORTL.ZAHLEN - Zack marker strip

1051016

<https://www.phoenixcontact.com/us/products/1051016>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6. 15 x 10.5 mm, Number of individual labels: 10

D-UKK 3/5 BK - End cover

2770228

<https://www.phoenixcontact.com/us/products/2770228>



End cover, width: 2.5 mm, height: 66.5 mm, color: black

TT-SLKK 5-C 3N3-230AC - EMC filter

2798792

<https://www.phoenixcontact.com/us/products/2798792>



DP-UKK 3/5 BK - Spacer plate

2770833

<https://www.phoenixcontact.com/us/products/2770833>

Spacer plate, to compensate for level offsets, depth: 25 mm, width: 2.5 mm, height: 56 mm, color: black



SSA 3-6 - Shield connection

2839295

<https://www.phoenixcontact.com/us/products/2839295>

Shield fast connection for 3 ... 6 mm cable diameter. Potential connecting cable: 200 mm, 1 mm², color: black



TT-SLKK 5-C 3N3-230AC - EMC filter

2798792

<https://www.phoenixcontact.com/us/products/2798792>



SSA 5-10 - Shield connection

2839512

<https://www.phoenixcontact.com/us/products/2839512>



Shield fast connection for 5 ... 10 mm cable diameter. Potential connecting cable:
200 mm, 1 mm², color: black

B-STIFT - Marker pen

1051993

<https://www.phoenixcontact.com/us/products/1051993>



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and
waterproof, line thickness 0.5 mm

TT-SLKK 5-C 3N3-230AC - EMC filter

2798792

<https://www.phoenixcontact.com/us/products/2798792>



SZS 0,6X3,5 VDE - Screwdriver

1212602

<https://www.phoenixcontact.com/us/products/1212602>



Screwdriver, slot-headed, VDE insulated, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

SZS 0,4X2,5 VDE - Screwdriver

1205037

<https://www.phoenixcontact.com/us/products/1205037>



Screwdriver, slot-headed, VDE insulated, size: 0.4 x 2.5 x 80 mm, 2-component grip, with non-slip grip

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com