

# PSM-SET-FSMA/4-KT - FO connectors



2799720  
<https://www.phoenixcontact.com/us/products/2799720>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

FO connectors, degree of protection: IP20, number of positions: 2, MM, material: Metal, cable outlet: straight



## Your advantages

- Suitable for quick and easy field assembly or repair
- No bonding or polishing
- Flexible application, thanks to reusable connectors
- Outstanding transmission properties
- Robust connector

## Commercial data

Item number	2799720
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB16
Product key	ABNIAA
Catalog page	Page 376 (C-2-2019)
GTIN	4017918156053
Weight per piece (including packing)	33.6 g
Weight per piece (excluding packing)	32.3 g
Customs tariff number	85367000
Country of origin	PL

# PSM-SET-FSMA/4-KT - FO connectors



2799720

<https://www.phoenixcontact.com/us/products/2799720>

## Technical data

### Product properties

Type	FSMA
Product type	Data connector (cable side)
Number of positions	2
Cable outlet	straight

### Insulation characteristics

Overvoltage category	I
Degree of pollution	2

### Electrical properties

Attenuation	< 1.5 dB (Insertion attenuation)
Transmission medium	FO
Transmission characteristics (category)	MM

### Material specifications

Flammability rating according to UL 94	V0
Housing material	Metal

### Cable/line

Cable type	Plastic-coated fiber
External cable diameter ( )	2.2 mm ... 2.2 mm
Individual wire diameter	2.2 mm
Resistance to oil	yes
Flame resistance	yes

### FO cable

Fiber	980/1000 µm
Fiber type	POF

### Characteristics

Attenuation	< 1.5 dB (Insertion attenuation)
-------------	----------------------------------

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Ambient temperature (assembly)	0 °C ... 50 °C
Resistance to oil	yes

### Standards and regulations

# PSM-SET-FSMA/4-KT - FO connectors



2799720

<https://www.phoenixcontact.com/us/products/2799720>

Flame resistance	yes
Resistance to oil	yes

## Mounting

Mounting type	For field assembly
---------------	--------------------

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)