

2800023

<https://www.phoenixcontact.com/pc/products/2800023>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Attachment plug with Lambda/4 technology as surge protection for coaxial signal interfaces.
Connection: N connectors plug/socket

Your advantages

- Easy installation with system-compliant connection
- Use under extreme ambient conditions with robust design
- Service-friendly with maintenance-free protective circuit
- Exceptional protective properties with Lambda/4 technology

Commercial data

Item number	2800023
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	CL3312
Catalog page	Page 179 (C-4-2017)
GTIN	4046356410083
Weight per piece (including packing)	195.1 g
Weight per piece (excluding packing)	187.8 g
Customs tariff number	85363010
Country of origin	US

CN-LAMBDA/4-5.9-SB - Surge protection device



2800023

<https://www.phoenixcontact.com/pc/products/2800023>

Technical data


Product properties

IEC test classification	C2
	C3
	D1
VDE requirement class	C2
	C3
	D1
Type	Attachment plug
Product type	Surge protection for transceiver systems
Surge protection fault message	none

Connection data

Connection method	N connector 50 Ω
-------------------	-------------------------

Dimensions

Dimensional drawing	
Width	26.1 mm
Height	38 mm
Depth	65 mm

Material specifications

Color	Nickel
Seal material	Silicon
Housing surface material	Nickel
Housing material	Brass (CuZn)
Inner conductor material	BeCu
Inner conductor surface material	Gold
Insulation body material	PTFE

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Protective circuit

Direction of action	Line-Shield/Earth Ground
Rated current	5 A (25 °C)
Nominal discharge current I_n (8/20) μ s (line-ground)	50 kA

CN-LAMBDA/4-5.9-SB - Surge protection device



2800023

<https://www.phoenixcontact.com/pc/products/2800023>

Nominal discharge current I_n (8/20) μ s (line-shield)	50 kA
Pulse discharge current I_{imp} (10/350) μ s	20 kA
Pulse discharge current I_{imp} (10/350) μ s (line-earth)	20 kA
Max. discharge current I_{max} (8/20) μ s maximum (line-earth)	60 kA
Max. discharge current I_{max} (8/20) μ s maximum (line-shield)	60 kA
Impulse discharge current (10/350) μ s, peak value I_{imp}	20 kA
Voltage protection level U_p (line-earth)	≤ 11 V (6 kV / 3 kA)
Voltage protection level U_p (line-shield)	≤ 11 V (6 kV / 3 kA)
Input attenuation aE, asym.	typ. 0.15 dB (≤ 0.25 dB)
Frequency range	2.4 GHz ... 7.6 GHz
Voltage standing wave ratio VSWR in a 50 Ω system	typ. 1.1 (2.4 GHz ... 5.9 GHz) ≤ 1.2 (2.4 GHz ... 7.6 GHz)
Permissible HF power P_{max} at VSWR = xx (50 ohm system)	≤ 500 W ≤ 4 kW (peak)
Surge protection fault message	none
Impulse durability (line-earth)	C2 - 10 kV / 5 kA D1 - 2.5 kA
Impulse durability (line-shield)	C2 - 10 kV/5 kA D1 - 2.5 kA

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP68
Ambient temperature (operation)	-40 °C ... 90 °C

Approvals

Conformity/Approvals

FCC	Part 15, Part 90
-----	------------------

Standards and regulations


VDE requirement class	C2 C3 D1
Standards/specifications	IEC 61643-21
Note	2005

Mounting


Mounting type	Connection-specific intermediate plugging
---------------	---

Drawings

Dimensional drawing



Circuit diagram



CN-LAMBDA/4-5.9-SB - Surge protection device



2800023

<https://www.phoenixcontact.com/pc/products/2800023>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/2800023>



EAC

Approval ID: EAC-Zulassung



EAC

Approval ID: RU C-DE.*09.B.00169

CN-LAMBDA/4-5.9-SB - Surge protection device



2800023

<https://www.phoenixcontact.com/pc/products/2800023>

Classifications

ECLASS

ECLASS-11.0	27130807
ECLASS-13.0	27171504

ETIM

ETIM 9.0	EC000943
----------	----------

UNSPSC

UNSPSC 21.0	39121600
-------------	----------

CN-LAMBDA/4-5.9-SB - Surge protection device



2800023

<https://www.phoenixcontact.com/pc/products/2800023>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com