

CB TM1 12A M1 P - Thermomagnetic device circuit breaker



2800855

<https://www.phoenixcontact.com/pc/products/2800855>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Thermomagnetic device circuit breaker, 1-pos., tripping characteristic M1 (medium-blow), 1 changeover contact, plug for base element.

Your advantages

- Individually adjustable with protective plugs
- Switch higher starting currents with the aid of the M1 characteristic curve
- Protective plug with fixed nominal current value as protection against unintentional changes
- Increased safety with electrical isolation in the event of errors

Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 2800855             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Product key                          | CLA124              |
| Catalog page                         | Page 392 (C-4-2019) |
| GTIN                                 | 4046356690065       |
| Weight per piece (including packing) | 43.3 g              |
| Weight per piece (excluding packing) | 40.7 g              |
| Customs tariff number                | 85362010            |
| Country of origin                    | ID                  |

# CB TM1 12A M1 P - Thermomagnetic device circuit breaker



2800855

<https://www.phoenixcontact.com/pc/products/2800855>

## Technical data

### Notes

|         |                                                                                                                     |
|---------|---------------------------------------------------------------------------------------------------------------------|
| General | When mounted in rows, the nominal device current can be limited to just 80% or must be overdimensioned accordingly. |
|---------|---------------------------------------------------------------------------------------------------------------------|

### Product properties

|                     |                                        |
|---------------------|----------------------------------------|
| Type                | Male                                   |
| Product type        | Thermomagnetic device circuit breakers |
| Product family      | CB TM                                  |
| Number of positions | 1                                      |
| No. of channels     | 1                                      |

### Insulation characteristics

|                     |   |
|---------------------|---|
| Degree of pollution | 2 |
|---------------------|---|

### Electrical properties

|           |                  |
|-----------|------------------|
| Fuse type | Automatic device |
|-----------|------------------|

### General

|                                                        |                                                                      |
|--------------------------------------------------------|----------------------------------------------------------------------|
| Rated voltage                                          | 50 V DC (IEC 60934)                                                  |
|                                                        | 50 V DC (UL 1077)                                                    |
|                                                        | 50 V DC (UL 508 - with plug-in base)                                 |
|                                                        | 240 V AC (U <sub>e</sub> according to IEC 60934)                     |
|                                                        | 277 V AC (UL 1077)                                                   |
|                                                        | 277 V AC (UL 508 - with plug-in base)                                |
| Rated insulation voltage U <sub>i</sub>                | 277 V AC (UL 1077)                                                   |
|                                                        | 250 V AC (IEC 60934)                                                 |
| Rated current I <sub>N</sub>                           | 12 A (IEC 60934)                                                     |
|                                                        | 12 A AC (inductive load according to UL 1077)                        |
|                                                        | 12 A DC (low-induction load according to UL 1077)                    |
|                                                        | 12 A DC (low-induction load according to UL 508 - with plug-in base) |
| Rated surge voltage                                    | 2.5 kV (Increased insulation in actuation area)                      |
| Insulation resistance R <sub>iso</sub>                 | > 100 MΩ (500 V DC)                                                  |
| Auxiliary circuit                                      | 277 V AC / 0.5 A (Low-induction)                                     |
|                                                        | 277 V AC / 1 A (Low-induction, maximum of 2000 cycles)               |
|                                                        | 50 V DC / 1 A (Low-induction)                                        |
| Type of actuation                                      | S type                                                               |
| Tripping method                                        | TM (thermomagnetic)                                                  |
| Tripping level                                         | Trip-free mechanism (positive)                                       |
| Device resistance                                      | 11 mΩ                                                                |
| Required backup fuse                                   | 48 A (I > I <sub>cn</sub> )                                          |
| Rated short-circuit switching capacity I <sub>cn</sub> | 300 A (240 V AC)                                                     |
|                                                        | 600 A (50 V DC)                                                      |

# CB TM1 12A M1 P - Thermomagnetic device circuit breaker



2800855

<https://www.phoenixcontact.com/pc/products/2800855>

|                                  |                                           |
|----------------------------------|-------------------------------------------|
| Short-circuit switching capacity | 1000 A AC (277 V AC)                      |
|                                  | 1000 A DC (50 V DC)                       |
| Dielectric strength              | 3000 V AC (Actuation area)                |
|                                  | 1500 V AC (Main to auxiliary circuit)     |
|                                  | 1500 V AC (Open main circuit)             |
|                                  | 1000 V AC (Open auxiliary circuit)        |
| Switching cycles, max.           | 6000 (at $1 \times I_n$ )                 |
| Fuse                             | M1 (normal blow)                          |
| Power dissipation                | 2.88 W (in nominal operation per channel) |
| Voltage drop                     | 0.13 V (at $1 \times I_n$ )               |


## Auxiliary contact

|                                        |       |
|----------------------------------------|-------|
| Minimum operating voltage $U_{min}$ DC | 10 V  |
| Maximum operating voltage $U_{max}$ DC | 240 V |
| Maximum operating voltage $U_{max}$ AC | 240 V |
| Minimum operating current $I_{min}$    | 10 mA |
| Max. operating current $I_{max}$       | 1 A   |

## Connection data

|                   |           |
|-------------------|-----------|
| Connection method | pluggable |
| Connection method | pluggable |

## Dimensions

|                        |                                                                                      |
|------------------------|--------------------------------------------------------------------------------------|
| Dimensional drawing    |  |
| Width                  | 12.3 mm                                                                              |
| Height                 | 45 mm                                                                                |
| Depth                  | 52 mm                                                                                |
| Complete module width  | 12.3 mm                                                                              |
| Complete module height | 90 mm                                                                                |
| Complete module depth  | 77.3 mm                                                                              |

## Material specifications

|                                        |                  |
|----------------------------------------|------------------|
| Color                                  | gray (RAL 7042)  |
|                                        | black (RAL 9005) |
| Flammability rating according to UL 94 | V-0              |
| Insulating material group              | II               |

## Mechanical properties

### Mechanical data

# CB TM1 12A M1 P - Thermomagnetic device circuit breaker



2800855

<https://www.phoenixcontact.com/pc/products/2800855>

|                 |    |
|-----------------|----|
| Open side panel | No |
|-----------------|----|

## Environmental and real-life conditions

### Ambient conditions

|                                         |                                                |
|-----------------------------------------|------------------------------------------------|
| Degree of protection                    | IP30 (Actuation area)                          |
| Ambient temperature (operation)         | -30 °C ... 60 °C                               |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C                               |
| Humidity test                           | 240 h, 95 % RH, 40 °C                          |
| Shock (operation)                       | 30g (According to IEC 60068-2-27, Test Ea)     |
| Vibration (operation)                   | 8g (in accordance with IEC 60068-2-6, Test Fc) |

## Approvals

### UL approval

|                |                            |
|----------------|----------------------------|
| Identification | UL Listed UL 508           |
|                | UL/C-UL Recognized UL 1077 |

### CSA

|                |                              |
|----------------|------------------------------|
| Identification | CSA CAN/CSA-C22.2 No. 235-04 |
|----------------|------------------------------|

### Shipbuilding approval

|                |        |
|----------------|--------|
| Identification | DNV GL |
|----------------|--------|

## Standards and regulations

|                          |          |
|--------------------------|----------|
| Standards/specifications | EN 60934 |
|--------------------------|----------|

## Mounting

|                   |                 |
|-------------------|-----------------|
| Mounting type     | on base element |
| Connection method | pluggable       |


# CB TM1 12A M1 P - Thermomagnetic device circuit breaker

2800855


<https://www.phoenixcontact.com/pc/products/2800855>

## Drawings

Application drawing



Circuit diagram




CB TM1 12A M1 P - Thermomagnetic device circuit breaker



2800855

<https://www.phoenixcontact.com/pc/products/2800855>


### Diagram



### Trigger characteristic

Gray: DC range, blue: AC range


## Application drawing



# CB TM1 12A M1 P - Thermomagnetic device circuit breaker

2800855

<https://www.phoenixcontact.com/pc/products/2800855>



The figure shows the complete module consisting of a base element and connector

# CB TM1 12A M1 P - Thermomagnetic device circuit breaker



2800855

<https://www.phoenixcontact.com/pc/products/2800855>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/2800855>



**cUL Recognized**  
Approval ID: FILE E 140459



**UL Recognized**  
Approval ID: FILE E 140459



**EAC**  
Approval ID: RU C-DE.\*09.B.00169



**DNV GL**  
Approval ID: TAE00003C7



**VDE Zeichengenehmigung**  
Approval ID: 40034683



**UL Listed**  
Approval ID: FILE E 172140



**CCC**  
Approval ID: 201901030715887



**CSA**  
Approval ID: 2786957



**cUL Listed**  
Approval ID: FILE E 172140



**KC**  
Approval ID: SW05012-15001A

**UAE-RoHS**  
Approval ID: 22-09-50937

# CB TM1 12A M1 P - Thermomagnetic device circuit breaker



2800855

<https://www.phoenixcontact.com/pc/products/2800855>

**cULus Recognized**

**cULus Listed**

# CB TM1 12A M1 P - Thermomagnetic device circuit breaker



2800855  
<https://www.phoenixcontact.com/pc/products/2800855>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27140401 |
| ECLASS-12.0 | 27140401 |
| ECLASS-13.0 | 27140401 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC003538 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# CB TM1 12A M1 P - Thermomagnetic device circuit breaker



2800855  
<https://www.phoenixcontact.com/pc/products/2800855>

## Environmental product compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)