

CB TM2 12A M1 P - Thermomagnetic device circuit breaker

2800888
<https://www.phoenixcontact.com/pc/products/2800888>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Thermomagnetic device circuit breaker, 2-pos., tripping characteristic M1 (medium-blow), 2 changeover contacts, plug for base element.

Product description

Thermomagnetic device circuit breaker

Commercial data

Item number	2800888
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	CLA124
Catalog page	Page 392 (C-4-2019)
GTIN	4046356690492
Weight per piece (including packing)	70.1 g
Weight per piece (excluding packing)	70.1 g
Customs tariff number	85362010
Country of origin	ID

CB TM2 12A M1 P - Thermomagnetic device circuit breaker



2800888

<https://www.phoenixcontact.com/pc/products/2800888>

Technical data

Notes

General	When mounted in rows, the nominal device current can be limited to just 80% or must be overdimensioned accordingly.
---------	---

Product properties

Type	Male
Product type	Thermomagnetic device circuit breakers
Product family	CB TM
Number of positions	2
No. of channels	1

Insulation characteristics

Degree of pollution	2
---------------------	---

Electrical properties

Fuse type	Automatic device
-----------	------------------

General

Rated voltage	80 V DC (IEC 60934)
	80 V DC (UL 1077)
	80 V DC (UL 508 - with plug-in base)
	240 V AC (Ue according to IEC 60934)
	277 V AC (UL 1077)
	277 V AC (UL 508 - with plug-in base)
Rated insulation voltage U_i	277 V AC (UL 1077)
	250 V AC (IEC 60934)
Rated current I_N	12 A (IEC 60934)
	12 A AC (inductive load according to UL 1077)
	12 A DC (low-induction load according to UL 1077)
	12 A DC (low-induction load according to UL 508 - with plug-in base)
Rated surge voltage	2.5 kV (Increased insulation in actuation area)
Insulation resistance R_{iso}	> 100 M Ω (500 V DC)
Auxiliary circuit	277 V AC / 0.5 A (Low-induction)
	277 V AC / 1 A (Low-induction, maximum of 2000 cycles)
	50 V DC / 1 A (Low-induction)
Type of actuation	S type
Tripping method	TM (thermomagnetic)
Tripping level	Trip-free mechanism (positive)
Device resistance	11 m Ω
Required backup fuse	≥ 48 A ($I > I_{cn}$)
Rated short-circuit switching capacity I_{cn}	400 A (240 V AC)
	600 A (80 V DC)

CB TM2 12A M1 P - Thermomagnetic device circuit breaker



2800888

<https://www.phoenixcontact.com/pc/products/2800888>

Short-circuit switching capacity	1000 A AC (277 V AC)
	1000 A DC (50 V DC)
Dielectric strength	3000 V AC (Actuation area)
	1500 V AC (Main to auxiliary circuit)
	1500 V AC (Open main circuit)
	1000 V AC (Open auxiliary circuit)
	1500 V AC (Position to position)
Switching cycles, max.	6000 (240 V AC / 1 x I _n)
	3000 (80 V DC/1 x I _n)
Fuse	M1 (normal blow)
Power dissipation	2.88 W (in nominal operation per channel)
Voltage drop	0.13 V (at 1 x I _n)


Auxiliary contact

Minimum operating voltage U _{min} DC	10 V
Maximum operating voltage U _{max} DC	240 V
Maximum operating voltage U _{max} AC	240 V
Minimum operating current I _{min}	10 mA
Max. operating current I _{max}	1 A

Connection data

Connection method	pluggable
Connection method	pluggable

Dimensions

Dimensional drawing	
Width	24.6 mm
Height	45 mm
Depth	52 mm

Material specifications

Color	gray (RAL 7042)
	black (RAL 9005)
Flammability rating according to UL 94	V-0
Insulating material group	II

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

CB TM2 12A M1 P - Thermomagnetic device circuit breaker



2800888

<https://www.phoenixcontact.com/pc/products/2800888>

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP30 (Actuation area)
Ambient temperature (operation)	-30 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Humidity test	240 h, 95 % RH, 40 °C
Shock (operation)	30g (IEC 60068-2-27, Test Ea)
Vibration (operation)	8g (IEC 60068-2-6, Test Fc)

Approvals

UL approval

Identification	UL Listed UL 508
	UL/C-UL Recognized UL 1077

CSA

Identification	CSA CAN/CSA-C22.2 No. 235-04
----------------	------------------------------

Shipbuilding approval

Identification	DNV GL
----------------	--------

Standards and regulations

Standards/specifications	EN 60934
--------------------------	----------

Mounting

Mounting type	on base element
Connection method	pluggable


CB TM2 12A M1 P - Thermomagnetic device circuit breaker

2800888

<https://www.phoenixcontact.com/pc/products/2800888>

Drawings

Dimensional drawing




The figure shows the complete module consisting of a base element and connector

CB TM2 12A M1 P - Thermomagnetic device circuit breaker

2800888

<https://www.phoenixcontact.com/pc/products/2800888>


Diagram



Trigger characteristic

Gray: DC range, blue: AC range

Application drawing




CB TM2 12A M1 P - Thermomagnetic device circuit breaker



2800888

<https://www.phoenixcontact.com/pc/products/2800888>

Application drawing



The figure shows the single-position versions

CB TM2 12A M1 P - Thermomagnetic device circuit breaker



2800888

<https://www.phoenixcontact.com/pc/products/2800888>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/2800888>



cUL Recognized
Approval ID: FILE E 140459



UL Recognized
Approval ID: FILE E 140459



EAC
Approval ID: RU C-DE.*09.B.00169



DNV GL
Approval ID: TAE00003C7



VDE Zeichengenehmigung
Approval ID: 40034683



CCC
Approval ID: 2019010307158887



CSA
Approval ID: 2786957



KC
Approval ID: SW05012-15005

UAE-RoHS

Approval ID: 22-09-50937

cULus Recognized

CB TM2 12A M1 P - Thermomagnetic device circuit breaker



2800888
<https://www.phoenixcontact.com/pc/products/2800888>

Classifications

ECLASS

ECLASS-11.0	27140401
ECLASS-12.0	27140401
ECLASS-13.0	27140401

ETIM

ETIM 9.0	EC003538
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

CB TM2 12A M1 P - Thermomagnetic device circuit breaker



2800888
<https://www.phoenixcontact.com/pc/products/2800888>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com