

ST-BE-LA 24 - Component connector



2802374

<https://www.phoenixcontact.com/pc/products/2802374>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Component plug, with light indicator, to connect 2-pos. components into the basic terminal block, height: 19 mm, color: Gray, voltage light indicator: 24 V DC

Commercial data

Item number	2802374
Packing unit	10 pc
Minimum order quantity	10 pc
Product key	BE1Z3X
Catalog page	Page 508 (C-1-2019)
GTIN	4017918074449
Weight per piece (including packing)	7.49 g
Weight per piece (excluding packing)	7.49 g
Customs tariff number	85366990
Country of origin	PL

ST-BE-LA 24 - Component connector



2802374

<https://www.phoenixcontact.com/pc/products/2802374>

Technical data

Product properties

Product type	Component plug terminal block
Pitch	6 mm

Data management status

Article revision	07
------------------	----

Connection data

Nominal cross section	2.5 mm²
-----------------------	---------

Dimensions

Height	19 mm
Length	42 mm
Pitch	6 mm

Material specifications

Color	gray (RAL 7042)
Flammability rating according to UL 94	V0
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Mounting

ST-BE-LA 24 - Component connector



2802374

<https://www.phoenixcontact.com/pc/products/2802374>

Mounting type	Plug-in mounting
---------------	------------------

ST-BE-LA 24 - Component connector



2802374

<https://www.phoenixcontact.com/pc/products/2802374>

Classifications

ECLASS

ECLASS-11.0	27141149
-------------	----------

ETIM

ETIM 8.0	EC002018
----------	----------

UNSPSC

UNSPSC 21.0	39121600
-------------	----------

ST-BE-LA 24 - Component connector



2802374
<https://www.phoenixcontact.com/pc/products/2802374>

Environmental product compliance

China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com