

PT 1X2-48DC-ST - Surge protection plug



2803658

<https://www.phoenixcontact.com/ca/products/2803658>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Protective plug PT with protective circuit for a 2-wire floating signal circuit.

Your advantages

- Easy testing and documentation with CHECKMASTER 2 with pluggable protective modules
- Maximum ease of maintenance, thanks to the 2-piece design
- Easy selection for all possible demands in MCR applications with a complete product portfolio
- The signal is not influenced during maintenance work, thanks to the impedance-neutral insertion and removal of protective plugs

Commercial data

Item number	2803658
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CL32
Product key	CL2111
Catalog page	Page 122 (C-4-2019)
GTIN	4046356299268
Weight per piece (including packing)	20.35 g
Weight per piece (excluding packing)	19.75 g
Customs tariff number	85363010
Country of origin	DE

PT 1X2-48DC-ST - Surge protection plug



2803658
<https://www.phoenixcontact.com/ca/products/2803658>

Technical data

Notes

General	
Note	Technical data is valid in association with the following specified base elements:
	PT 1X2+F-BE 2856126
	PT 1X2-BE 2856113

Product properties

Product type	Surge protection for MCR technology
Product family	PLUGTRAB PT
IEC test classification	C1
	C2
	C3
	D1
Type	Male
Number of positions	2
Surge protection fault message	none
Arrester can be tested with CHECKMASTER from software version:	From SW rev. 3.15
Wire pairs per module	1

Insulation characteristics	
Overvoltage category	III
Pollution degree	2

Electrical properties

Nominal voltage U_N	48 V DC
-----------------------	---------

Connection data

Connection method	Screw connection (in connection with the base element)
Screw thread	M3
Tightening torque	0.5 Nm
Conductor cross section flexible	0.2 mm² ... 2.5 mm²
Conductor cross section rigid	0.2 mm² ... 4 mm²
Conductor cross section AWG	24 ... 12

Dimensions

Dimensional drawing	
---------------------	--

PT 1X2-48DC-ST - Surge protection plug



2803658

<https://www.phoenixcontact.com/ca/products/2803658>

Width	17.7 mm
Height	45 mm
Depth	52 mm
Horizontal pitch	1 Div.
Complete module width	17.7 mm
Complete module height	90 mm
Complete module depth	65.5 mm

Material specifications

Color	black (RAL 9005)
Flammability rating according to UL 94	V-0
Housing material	PA 6.6

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Protective circuit

Direction of action	Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground
Maximum continuous voltage U_C	53 V DC
	37 V AC
Rated current	450 mA (45 °C)
Operating effective current I_C at U_C	$\leq 5 \mu A$
Residual current I_{PE}	$\leq 2 \mu A$ (with PT 1X2-BE)
	$\leq 1 \mu A$ (with PT 1X2+F-BE)
Nominal discharge current I_n (8/20) μs (line-line)	10 kA
Nominal discharge current I_n (8/20) μs (line-ground)	10 kA
Pulse discharge current I_{imp} (10/350) μs	2.5 kA
Total discharge current I_{total} (8/20) μs	20 kA
Max. discharge current I_{max} (8/20) μs maximum (line-line)	10 kA
Max. discharge current I_{max} (8/20) μs maximum (line-earth)	20 kA (in total)
Nominal pulse current I_{an} (10/1000) μs (line-line)	18 A
Output voltage limitation at 1 kV/ μs (line-line) spike	$\leq 70 V$
Output voltage limitation at 1 kV/ μs (line-earth) spike	$\leq 450 V$ (with PT 1X2-BE)
	$\leq 1 kV$ (with PT 1X2+F-BE)
Output voltage limitation at 1 kV/ μs (line-line) static	$\leq 70 V$
Output voltage limitation at 1 kV/ μs (line-earth) static	$\leq 25 V$ (with PT 1X2-BE)
	$\leq 50 V$ (with PT 1X2+F-BE)
Voltage protection level U_p (line-line)	$\leq 80 V$ (C1 - 1 kV / 500 A)
	$\leq 85 V$ (C2 - 2 kV/1 kA)
	$\leq 120 V$ (C2 - 10 kV / 5 kA)
Voltage protection level U_p (line-earth)	$\leq 450 V$ (C1 - 1 kV / 500 A with PT 1X2-BE)
	$\leq 550 V$ (C2 - 2 kV / 1 kA with PT 1X2-BE)

PT 1X2-48DC-ST - Surge protection plug



2803658

<https://www.phoenixcontact.com/ca/products/2803658>

	≤ 600 V (C2 - 10 kV / 5 kA with PT 1X2-BE)
	≤ 800 V (C1 - 1 kV / 500 A with PT 1x2+F-BE)
	≤ 900 V (C2 - 2 kV / 1 kA with PT 1x2+F-BE)
	≤ 1000 V (C2 - 10 kV / 5 kA with PT 1X2+F-BE)
Response time t_A (line-line)	≤ 1 ns
Response time t_A (line-earth)	≤ 100 ns
Input attenuation aE, sym.	typ. 0.5 dB (≤ 2 MHz / 50 Ω) typ. 0.2 dB (≤ 600 kHz / 150 Ω)
Cut-off frequency f_g (3 dB), sym. in 50 Ω system	typ. 10 MHz
Cut-off frequency f_g (3 dB), sym. in 150 Ω system	typ. 3.5 MHz
Capacity (Core-Core)	typ. 1 nF
Capacity (Core-Earth)	typ. 4 pF (with PT 1X2-BE) typ. 2 pF (with PT 1X2+F-BE)
Resistance per path	2.2 Ω ±10 %
Surge protection fault message	none
Max. required back-up fuse	500 mA (T)
Impulse durability (line-line)	C1 - 1 kV / 500 A C2 - 2 kV / 1 kA C2 - 10 kV / 5 kA
Impulse durability (line-earth)	C1 - 1 kV / 500 A C2 - 2 kV / 1 kA C2 - 10 kV / 5 kA D1 - 2.5 kA

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Altitude	≤ 2000 m (amsl)

Standards and regulations

Standards/specifications	IEC 61643-21
Note	2000 + corrigendum 2001 + A1:2008, modified + A2:2012
Standards/specifications	EN 61643-21
Note	2001 + A1:2009 + A2:2013

Mounting

Mounting type	on base element
---------------	-----------------

PT 1X2-48DC-ST - Surge protection plug


2803658

<https://www.phoenixcontact.com/ca/products/2803658>




Drawings

Dimensional drawing



The figure shows the complete module consisting of a base element and connector

Circuit diagram




PT 1X2-48DC-ST - Surge protection plug

2803658

<https://www.phoenixcontact.com/ca/products/2803658>



Diagram



PT 1X2-48DC-ST - Surge protection plug



2803658

<https://www.phoenixcontact.com/ca/products/2803658>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/ca/products/2803658>



EAC

Approval ID: RU C-DE.*09.B.00169

PT 1X2-48DC-ST - Surge protection plug



2803658

<https://www.phoenixcontact.com/ca/products/2803658>

Classifications

ECLASS

ECLASS-11.0	27130807
ECLASS-13.0	27171501

ETIM

ETIM 9.0	EC001625
----------	----------

UNSPSC

UNSPSC 21.0	39121600
-------------	----------

PT 1X2-48DC-ST - Surge protection plug



2803658

<https://www.phoenixcontact.com/ca/products/2803658>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	812bd96f-44cb-4789-b420-6a3c5f8050ab

PT 1X2-48DC-ST - Surge protection plug



2803658

<https://www.phoenixcontact.com/ca/products/2803658>


Mandatory accessories

PT 1X2-BE - Surge protection base-element

2856113

<https://www.phoenixcontact.com/ca/products/2856113>

Base element for protective plug PT with protective circuit for a 2-core floating signal circuit. Mounting on NS 35/7.5 und NS 35/15, housing width: 17.5 mm.




PT 1X2+F-BE - Surge protection base-element

2856126

<https://www.phoenixcontact.com/ca/products/2856126>

Base element for protective plug PT with protective circuit for a 2-core floating signal circuit. Integrated gas arrester as coarse protection between GND and PE. Mounting on NS 35/7.5 und NS 35/15, housing width: 17.5 mm.



Accessories

PT 1X2-48DC-ST - Surge protection plug

2803658

<https://www.phoenixcontact.com/ca/products/2803658>



ZBF 5:UNBEDRUCKT - Zack Marker strip, flat

0808642

<https://www.phoenixcontact.com/ca/products/0808642>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.1 x 5.2 mm, Number of individual labels: 10

ZBF 5/WH-100:UNBEDRUCKT - Zack Marker strip, flat

0808668

<https://www.phoenixcontact.com/ca/products/0808668>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 1000

PT 1X2-48DC-ST - Surge protection plug

2803658

<https://www.phoenixcontact.com/ca/products/2803658>



ZBF 5,LGS:FORTL.ZAHLEN - Zack Marker strip, flat

0808671

<https://www.phoenixcontact.com/ca/products/0808671>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

ZBF 5,LGS:GERADE ZAHLEN - Zack Marker strip, flat

0810821

<https://www.phoenixcontact.com/ca/products/0810821>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive even numbers 2 ... 20, 22 ... 40, etc. up to 82 ... 100, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

PT 1X2-48DC-ST - Surge protection plug

2803658

<https://www.phoenixcontact.com/ca/products/2803658>



ZBF 5,LGS:UNGERADE ZAHLEN - Zack Marker strip, flat

0810863

<https://www.phoenixcontact.com/ca/products/0810863>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: Odd numbers 1 - 19, 21 - 39, etc. up to 81 - 99, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

ZBF 5,QR:FORTL.ZAHLEN - Zack Marker strip, flat

0808697

<https://www.phoenixcontact.com/ca/products/0808697>



Zack Marker strip, flat, Strip, white, labeled, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 10

PT 1X2-48DC-ST - Surge protection plug

2803658

<https://www.phoenixcontact.com/ca/products/2803658>



ZBN 18:UNBEDRUCKT - Zack marker strip

2809128

<https://www.phoenixcontact.com/ca/products/2809128>



Zack marker strip, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: snapped, for terminal block width: 18 mm, lettering field size: 18 x 5 mm, Number of individual labels: 5

SSA 3-6 - Shield connection

2839295

<https://www.phoenixcontact.com/ca/products/2839295>



Shield fast connection for 3 ... 6 mm cable diameter. Potential connecting cable: 200 mm, 1 mm², color: black

PT 1X2-48DC-ST - Surge protection plug

2803658

<https://www.phoenixcontact.com/ca/products/2803658>



SSA 5-10 - Shield connection

2839512

<https://www.phoenixcontact.com/ca/products/2839512>



Shield fast connection for 5 ... 10 mm cable diameter. Potential connecting cable:
200 mm, 1 mm², color: black

X-PEN 0,35 - Marker pen

0811228

<https://www.phoenixcontact.com/ca/products/0811228>



Marker pen without ink cartridge, for manual labeling of markers, labeling
extremely wipe-proof, line thickness 0.35 mm

PT 1X2-48DC-ST - Surge protection plug

2803658

<https://www.phoenixcontact.com/ca/products/2803658>



SZS 0,6X3,5 VDE - Screwdriver

1212602

<https://www.phoenixcontact.com/ca/products/1212602>



Screwdriver, slot-headed, VDE insulated, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd

8240 Parkhill Drive

Milton, Ontario L9T 5V7

1-800-890-2820

cdinfo@phoenixcontact.ca