Specifications

Photo is representative

Eaton 281148

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, 220 V 50/60 Hz, AC, For use with: DILM17, DILM25, DILM32, DILM38

General specifications	
PRODUCT NAME	Eaton Moeller® series DILM replacement coil
CATALOG NUMBER	281148
MODEL CODE	DILM32-XSP(220V50/60HZ)
EAN	4015082811488
PRODUCT LENGTH/DEPTH	64 mm
PRODUCT HEIGHT	49 mm
PRODUCT WIDTH	46 mm
PRODUCT WEIGHT	0.048 kg
CERTIFICATIONS	CSA Class No.: 2411-03, 3211-04 UL 508 CSA-C22.2 No. 14-05 CSA IEC/EN 60947-4-1 UL Category Control No.: NLDX CSA File No.: 012528 UL UL File No.: E29096 CE
GLOBAL CATALOG	281148



Product specifications

Product specifications	
ACCESSORIES	Individual coils
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.

Resources	
	SmartWire-DT Catalog
CATALOGS	<u>eaton-product-overview-</u> <u>for-machinery-catalogue-</u> <u>ca08103003zen-en-us.pdf</u>
	Product Range Catalog Switching and protecting motors
	DA-DC-00004816.pdf
DECLARATIONS OF CONFORMITY	DA-DC-00004783.pdf
	DA-DC-00004776.pdf
DRAWINGS	<u>eaton-contactors-dilm-</u> <u>replacement-coil-3d-</u> <u>drawing.eps</u>
ECAD MODEL	ETN.281148.edz
INSTALLATION INSTRUCTIONS	<u>IL03407036Z</u>
INSTALLATION VIDEOS	<u>WIN-WIN with push-in</u> <u>technology</u>

10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	ls the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	ls the panel builder's responsibility.
10.9.2 POWER- FREQUENCY ELECTRIC STRENGTH	ls the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	ls the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	ls the panel builder's responsibility.
VOLTAGE TYPE	AC
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	220 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	220 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	220 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	220 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	0 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	0 V
PRODUCT CATEGORY	Accessories

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

