

MCR-PSP-DC - Limit value switch



2811925

<https://www.phoenixcontact.com/it/products/2811925>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



MCR threshold value switch, programmable, with electrically isolated input and 2 relay contacts

Commercial data

Item number	2811925
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	CK1
Product key	CK1843
Catalog page	Page 138 (C-7-2015)
GTIN	4017918105549
Weight per piece (including packing)	307.8 g
Weight per piece (excluding packing)	307.8 g
Customs tariff number	85389091
Country of origin	DE

MCR-PSP-DC - Limit value switch



2811925

<https://www.phoenixcontact.com/it/products/2811925>

Technical data

Notes

Utilization restriction

EMC note	EMC: class A product, see manufacturer's declaration in the download area
----------	---

Product properties

Product type	Limit value switch
No. of channels	1
Display resolution	0,1 °C / 0,01 V / 0,01 mA / 0,1 Ω

Electrical properties

Maximum power dissipation for nominal condition	1.8 W
Measuring rate	2 Hz
Test voltage input/power supply	1 kV AC (50 Hz, 60 s)
Protective circuit	Transient protection, polarity protection
Maximum temperature coefficient	≤ 0.01 %/K
Maximum transmission error	0.1 % (of final value)

Supply

Supply voltage range	20 V DC ... 30 V DC
Max. current consumption	< 60 mA

Input data

Signal

Description of the input	electrically isolated
Configurable/programmable	Yes, programmable
Voltage input signal	-30 V ... 30 V
Current input signal	-30 mA ... 30 mA
Available input sources	Resistance temperature detectors in 2-, 3- or 4-conductor technology (in accordance with DIN 43760/DIN IEC 751 or SAMA RC 21-4-1966), e.g., PT sensors, Ni sensors, etc. Thermocouple sensors (in acc. with DIN IEC 584-1/DIN 43710): B, E, J, K, L, N, R, S, T, U Resistance: 0 kΩ ... 8 kΩ (2-conductor circuit only) Current: - 30 mA...+ 30 mA Voltage: - 30 V...+ 30 V
Input resistance of voltage input	200 kΩ
Input resistance current input	50 Ω
Discontinuous control resolution	0,1 °C / 0,01 V / 0,01 mA / 0,1 Ω

Measurement

Sensor type:	-200 °C ... 850 °C (freely adjustable) -200 °C ... 850 °C (freely adjustable)
--------------	--

MCR-PSP-DC - Limit value switch



2811925

<https://www.phoenixcontact.com/it/products/2811925>

	-200 °C ... 850 °C (freely adjustable)
	-200 °C ... 850 °C (freely adjustable)
	-200 °C ... 850 °C (freely adjustable)
	-60 °C ... 180 °C (freely adjustable)
	-60 °C ... 180 °C (freely adjustable)
	-60 °C ... 180 °C (freely adjustable)
	-60 °C ... 180 °C (freely adjustable)
	-60 °C ... 180 °C (freely adjustable)
	-50 °C ... 160 °C (freely adjustable)
	-70 °C ... 500 °C (freely adjustable)
	-200 °C ... 600 °C (freely adjustable)
	-200 °C ... 400 °C (freely adjustable)
	-200 °C ... 900 °C (freely adjustable)
	-210 °C ... 1200 °C (freely adjustable)
	-226 °C ... 1000 °C (freely adjustable)
	-200 °C ... 1372 °C (freely adjustable)
	-200 °C ... 1300 °C (freely adjustable)
	-50 °C ... 1768 °C (freely adjustable)
	-50 °C ... 1768 °C (freely adjustable)
	500 °C ... 1820 °C (freely adjustable)
Linear resistance measuring range	0 Ω ... 8000 Ω

Output data

Switching: Relay

Contact switching type	2 x changeover contacts / 2 switching points each, de-energized/energized (switchable)
Contact material	AgNi 0,15 + HTV (hard gold-plated)
Maximum switching voltage	250 V AC
Max. switching current	2 A AC
Mechanical service life	2x 10 ⁷ cycles
Setting range of the response delay	0 s ... 2 s (adjustable)
Status display	LED display

Connection data

Connection method	Pluggable screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 14

Signaling

Status display	5-position 7-segment display and LEDs
----------------	---------------------------------------


MCR-PSP-DC - Limit value switch

2811925

<https://www.phoenixcontact.com/it/products/2811925>



Dimensions

Dimensional drawing	
	
Width	45 mm
Height	75 mm
Depth	110 mm

Material specifications

Color	green (RAL 6021)
Housing material	ABS

Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-20 °C ... 65 °C

Approvals

CE	
Certificate	CE-compliant
UL, USA/Canada	
Identification	cULus

EMC data

Noise immunity	EN 61000-6-2:2005
Noise emission	EN 61000-6-4

Mounting

Mounting type	DIN rail mounting
Mounting position	any

MCR-PSP-DC - Limit value switch


2811925

<https://www.phoenixcontact.com/lt/products/2811925>




Drawings

Dimensional drawing



Circuit diagram



MCR-PSP-DC - Limit value switch



2811925
<https://www.phoenixcontact.com/lt/products/2811925>

Classifications

ECLASS

ECLASS-11.0	27210120
-------------	----------

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact UAB
Svitrigailos str. 11B
03228 Vilnius
+370 5 2106321
balticinfo@phoenixcontact.com