

Specifications



Photo is representative



Eaton 281231

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 20A, N, frame 1, A20

General specifications

| | |
|-----------------------------|--|
| PRODUCT NAME | Eaton Moeller series NZM molded case circuit breaker thermo-magnetic |
| CATALOG NUMBER | 281231 |
| MODEL CODE | NZMN1-A20 |
| EAN | 4015082812317 |
| PRODUCT LENGTH/DEPTH | 88 mm |
| PRODUCT HEIGHT | 145 mm |
| PRODUCT WIDTH | 90 mm |
| PRODUCT WEIGHT | 1.071 kg |
| COMPLIANCES | RoHS conform |
| CERTIFICATIONS | IEC IEC/EN 60947 |
| GLOBAL CATALOG | 281231 |

Product specifications

| | |
|---|--|
| AMPERAGE RATING | 100 A |
| VOLTAGE RATING | 690 V - 690 V |
| CIRCUIT BREAKER FRAME TYPE | NZM1 |
| FEATURES | Protection unit |
| 10.10 TEMPERATURE RISE | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 SHORT-CIRCUIT RATING | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 ELECTROMAGNETIC COMPATIBILITY | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 MECHANICAL FUNCTION | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |
| 10.2.2 CORROSION RESISTANCE | Meets the product standard's requirements. |
| 10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES | Meets the product standard's requirements. |
| 10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT | Meets the product standard's requirements. |
| 10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS | Meets the product standard's requirements. |
| 10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION | Meets the product standard's requirements. |
| 10.2.5 LIFTING | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 MECHANICAL IMPACT | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 INSCRIPTIONS | Meets the product standard's requirements. |

Resources

BROCHURES

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

CATALOGS

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

[eaton-circuit-breaker-nzm-mccb-characteristic-curve-051.eps](#)

CHARACTERISTIC CURVE

[eaton-circuit-breaker-let-through-current-nzm-mccb-characteristic-curve-002.eps](#)

[eaton-circuit-breaker-nzm-mccb-characteristic-curve.eps](#)

DECLARATIONS OF CONFORMITY

[eaton-molded-case-circuit-breaker-declaration-of-conformity-eu250289en.pdf](#)

DRAWINGS

[eaton-circuit-breaker-switch-nzm-mccb-dimensions-014.eps](#)

[eaton-circuit-breaker-nzm-mccb-dimensions-017.eps](#)

ECAD MODEL

[ETN.281231.edz](#)

INSTALLATION INSTRUCTIONS

[eaton-circut-breaker-switch-disconnector-nzmb-il01203004z.pdf](#)

INSTALLATION VIDEOS

[The new digital NZM Range](#)

[Introduction of the new digital circuit breaker NZM](#)

MCAD MODEL

[eaton-molded-case-switches-mcad-drawings-nzm1-3p.dwg](#)

[eaton-molded-case-switches-mcad-3d-models-nzm1-3p.stp](#)

[DA-CD-nzm1_3p](#)

[DA-CS-nzm1_3p](#)

PEP ECO-PASSPORT

[eaton-molded-case-switches-pep-eato-00225-v0101-en.pdf](#)

| | |
|---|--|
| 10.3 DEGREE OF PROTECTION OF ASSEMBLIES | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 CLEARANCES AND CREEPAGE DISTANCES | Meets the product standard's requirements. |
| 10.5 PROTECTION AGAINST ELECTRIC SHOCK | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS | Is the panel builder's responsibility. |
| 10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS | Is the panel builder's responsibility. |
| 10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH | Is the panel builder's responsibility. |
| 10.9.3 IMPULSE WITHSTAND VOLTAGE | Is the panel builder's responsibility. |
| 10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL | Is the panel builder's responsibility. |
| POLLUTION DEGREE | 3 |
| MOUNTING METHOD | Built-in device fixed built-in technique DIN rail (top hat rail) mounting optional Fixed |
| CLIMATIC PROOFING | Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78 |
| EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT | 9.82 W |
| UTILIZATION CATEGORY | A (IEC/EN 60947-2) |
| ISOLATION | 300 V AC (between the auxiliary contacts) 500 V AC (between auxiliary contacts and main contacts) |
| AMBIENT OPERATING TEMPERATURE - MAX | 70 °C |
| AMBIENT OPERATING TEMPERATURE - MIN | -25 °C |
| AMBIENT STORAGE TEMPERATURE - MAX | 70 °C |
| AMBIENT STORAGE TEMPERATURE - MIN | -40 °C |
| NUMBER OF AUXILIARY | 0 |

| | |
|--|--|
| CONTACTS (CHANGE-OVER CONTACTS) | |
| NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS) | 0 |
| NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS) | 0 |
| PROTECTION AGAINST DIRECT CONTACT | Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110 |
| DEGREE OF PROTECTION | IP20 IP20 (basic degree of protection, in the operating controls area) |
| DIRECTION OF INCOMING SUPPLY | As required |
| ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT | Frame clamp |
| LIFESPAN, MECHANICAL | 20000 operations |
| OVERVOLTAGE CATEGORY | III |
| DEGREE OF PROTECTION (IP), FRONT SIDE | IP40 (with insulating surround) IP66 (with door coupling rotary handle) |
| DEGREE OF PROTECTION (TERMINATIONS) | IP10 (tunnel terminal) IP00 (terminations, phase isolator and strip terminal) |
| NUMBER OF POLES | Three-pole |
| TERMINAL CAPACITY (COPPER STRIP) | Min. 2 segments of 9 mm x 0.8 mm at box terminal Max. 9 segments of 9 mm x 0.8 mm at box terminal |
| LIFESPAN, ELECTRICAL | 7500 operations at 690 V AC-1 10000 operations at 400 V AC-1 10000 operations at 415 V AC-1 |
| FUNCTIONS | System and cable protection |
| TYPE | Circuit breaker |
| SPECIAL FEATURES | <ul style="list-style-type: none"> • Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit |

| | |
|--|--|
| | <p>breaker (Rated short-circuit breaking capacity Icn)</p> <ul style="list-style-type: none"> • Rated current = rated uninterrupted current: 20 A • Terminal capacity hint: Up to 95 mm² can be connected depending on the cable manufacturer. |
| APPLICATION | Use in unearthing supply systems at 690 V |
| SHOCK RESISTANCE | 20 g (half-sinusoidal shock 20 ms) |
| POSITION OF CONNECTION FOR MAIN CURRENT CIRCUIT | Front side |
| RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) | 20 A |
| POWER LOSS | 9.8 W |
| RELEASE SYSTEM | Thermomagnetic release |
| SHORT-CIRCUIT TOTAL BREAKTIME | < 10 ms |
| SHORT-CIRCUIT RELEASE | |
| NON-DELAYED SETTING - MAX | 350 A |
| SHORT-CIRCUIT RELEASE | |
| NON-DELAYED SETTING - MIN | 350 A |
| TERMINAL CAPACITY (CONTROL CABLE) | <p>0.75 mm² - 1.5 mm² (2x)</p> <p>0.75 mm² - 2.5 mm² (1x)</p> |
| TERMINAL CAPACITY (COPPER BUSBAR) | <p>Max. 16 mm x 5 mm direct at switch rear-side connection</p> <p>M6 at rear-side screw connection</p> <p>Min. 12 mm x 5 mm direct at switch rear-side connection</p> |
| TERMINAL CAPACITY (COPPER SOLID CONDUCTOR/CABLE) | <p>4 mm² - 16 mm² (2x) at box terminal</p> <p>16 mm² (1x) at tunnel terminal</p> <p>4 mm² - 16 mm² (2x) direct at switch rear-side connection</p> <p>6 mm² - 16 mm² (1x) direct at switch rear-side</p> |

| | |
|--|--|
| | connection 6 mm ² - 16 mm ² (1x) at box terminal |
| TERMINAL CAPACITY (ALUMINUM SOLID CONDUCTOR/CABLE) | 10 mm ² - 16 mm ² (1x) direct at switch rear-side connection 10 mm ² - 16 mm ² (2x) direct at switch rear-side connection 16 mm ² (1x) at tunnel terminal |
| TERMINAL CAPACITY (COPPER STRANDED CONDUCTOR/CABLE) | 4 mm ² - 25 mm ² (2x) direct at switch rear-side connection 6 mm ² - 70 mm ² (1x) at box terminal 25 mm ² - 95 mm ² (1x) at 1- hole tunnel terminal 4 mm ² - 25 mm ² (2x) at box terminal 6 mm ² - 70 mm ² (1x) direct at switch rear-side connection |
| TERMINAL CAPACITY (ALUMINUM STRANDED CONDUCTOR/CABLE) | 25 mm ² - 35 mm ² (2x) direct at switch rear-side connection 25 mm ² - 95 mm ² (1x) at tunnel terminal 25 mm ² - 35 mm ² (1x) direct at switch rear-side connection |
| HANDLE TYPE | Rocker lever |
| SHORT DELAY CURRENT SETTING (ISD) - MAX | 0 A |
| SHORT DELAY CURRENT SETTING (ISD) - MIN | 0 A |
| INSTANTANEOUS CURRENT SETTING (II) - MAX | 350 A |
| INSTANTANEOUS CURRENT SETTING (II) - MIN | 350 A |
| NUMBER OF OPERATIONS PER HOUR - MAX | 120 |
| OVERLOAD CURRENT SETTING (IR) - MAX | 20 A |
| OVERLOAD CURRENT SETTING (IR) - MIN | 15 A |
| RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 230 V, 50/60 HZ | 85 kA |
| RATED SHORT-CIRCUIT | 50 kA |

BREAKING CAPACITY ICS**(IEC/EN 60947) AT****400/415 V, 50/60 HZ****RATED SHORT-CIRCUIT****BREAKING CAPACITY ICS****(IEC/EN 60947) AT 440 V,
50/60 HZ**

35 kA

RATED SHORT-CIRCUIT**BREAKING CAPACITY ICS****(IEC/EN 60947) AT 525 V,
50/60 HZ**

10 kA

RATED SHORT-CIRCUIT**BREAKING CAPACITY ICS****(IEC/EN 60947) AT 690 V,
50/60 HZ**

7.5 kA

RATED SHORT-CIRCUIT**MAKING CAPACITY ICM****AT 400/415 V, 50/60 HZ**

105 kA

RATED SHORT-CIRCUIT**MAKING CAPACITY ICM****AT 440 V, 50/60 HZ**

74 kA

RATED SHORT-CIRCUIT**MAKING CAPACITY ICM****AT 525 V, 50/60 HZ**

40 kA

RATED SHORT-CIRCUIT**MAKING CAPACITY ICM****AT 690 V, 50/60 HZ**

17 kA

STANDARD TERMINALS

Box terminal

OPTIONAL TERMINALSConnection on rear. Screw
terminal. Tunnel terminal**RATED SHORT-CIRCUIT****MAKING CAPACITY ICM****AT 240 V, 50/60 HZ**

187 kA

RATED IMPULSE**WITHSTAND VOLTAGE****(UIMP) AT AUXILIARY
CONTACTS**

6000 V

RATED IMPULSE**WITHSTAND VOLTAGE****(UIMP) AT MAIN
CONTACTS**

6000 V

VOLTAGE RATING (DC)

450 VDC

RATED INSULATION**VOLTAGE (UI)**

690 V AC

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

