Specifications



Photo is representative

Eaton 281405

Eaton Moeller® series CI Insulated enclosure, for PKZ01, +padlocking feature yellow

General Specifications		
PRODUCT NAME	Eaton Moeller® series Cl Insulated enclosure	
CATALOG NUMBER	281405	
PRODUCT LENGTH/DEPTH	130 mm	
PRODUCT HEIGHT	158 mm	
PRODUCT WIDTH	80 mm	
PRODUCT WEIGHT	0.3 kg	
CERTIFICATIONS	CE	
CATALOG NOTES	Not suitable for PKZM0 PI / PKZM0SPI32	
EAN	4015082814052	
MODEL CODE	CI-PKZ01-SVB	



Product specifications	5
USED WITH	PKZ01
FEATURES	Can be locked in 0 position
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL	Does not apply, since the entire switchgear needs to
IMPACT	be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.

Resources	
BROCHURES	Brochure - CI-K small enclosures
DECLARATIONS OF CONFORMITY	CE ClPKZ Surface mounted enclosures and accessories PKZ
	UKCA CIPKZ Surface mounted enclosures and accessories PKZ
DRAWINGS	eaton-small-enclosures- enclosure-ci-insulated- enclosure-dimensions- 003.eps eaton-manual-motor- starters-mounting-ci- insulated-enclosure-3d- drawing.eps
ECAD MODEL	ETN.CI-PKZ01-SVB
INSTALLATION INSTRUCTIONS	IL03407018Z2021_10.pdf
MCAD MODEL	DA-CD-ci pkz01 svb DA-CS-ci pkz01 svb
WIRING DIAGRAMS	eaton-manual-motor- starters-transformer- pkzm0-wiring-diagram.eps

PROTECTION OF ASSEMBLIES	entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER- FREQUENCY ELECTRIC STRENGTH	ls the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	ls the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
FITTED WITH:	PE(N) terminal
ENCLOSURE MATERIAL	Plastic
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	10 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS	0 W
PRODUCT CATEGORY	Accessories
DEGREE OF PROTECTION	IP65 NEMA Other
MODEL	Surface mounting

SUITABLE FOR	Emergency stop
	2 x M20 (cable entry knockouts at the rear)
	2 x M25 (cable entry
	knockout with thread at
	the bottom)
KNOCKOUTS	2 x M25 (cable entry
	knockout with thread at
	the top)
	Hard mirror with cable
	entry knockouts (can be
	cut out)

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

 $\hbox{@ 2025 Eaton.}$ All Rights Reserved.

Follow us on social media to get the latest product and support information.









