## Specifications



## Eaton 281582

Eaton Moeller series NZM - Molded Case Circuit Breaker. Interlock, mechanical, size 2

General specifications	
PRODUCT NAME	Eaton Moeller series NZM mounting accessory
CATALOG NUMBER	281582
MODEL CODE	NZM2-XMV
EAN	4015082815820
PRODUCT LENGTH/DEPTH	105 mm
PRODUCT HEIGHT	55 mm
PRODUCT WIDTH	125 mm
PRODUCT WEIGHT	0.492 kg
COMPLIANCES	UL/CSA IEC RoHS conform
CERTIFICATIONS	UL (File No. E140305) CSA (Class No. 1437-01) UL489 UL (Category Control Number DIHS) CE marking CSA-C22.2 No. 5-09 CSA (File No. 22086) IEC60947 UL listed CSA certified
GLOBAL CATALOG	281582



Product specification	S
USED WITH	NZM2-4 PN2 N2 NZM2 N2-4 PN2(-4) NS2 NZM2(-4) NZM2-NA N(S)2(-4) PN2-4
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to

Resources	
BROCHURES	eaton-feerum-the-whole- grain-solution-success- story-en-us.pdf
	eaton-digital-nzm- brochure-br013003en-en- us.pdf
CATALOGS	eaton-digital-nzm-catalog- ca013003en-en-us.pdf
DRAWINGS	eaton-circuit-breaker- interlock-nzm-mccb- dimensions-002.eps
	eaton-circuit-breaker- interlock-nzm-mccb- dimensions-010.eps
	eaton-circuit-breaker- interlock-nzm-mccb- dimensions-009.eps
	eaton-circuit-breaker- interlock-nzm-mccb- dimensions-008.eps
	eaton-circuit-breaker- interlock-nzm-mccb-3d- drawing-002.eps
INSTALLATION INSTRUCTIONS	eaton-circuit-breakers- mechanical-interlock- il01219012z.pdf
INSTALLATION VIDEOS	Introduction of the new digital circuit breaker NZM
	The new digital NZM Range
MCAD MODEL	DA-CS-nzm2_xmv
TECHNICAL DATA SHEETS	eaton-nzm-technical- information-sheet

	be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	ls the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	ls the panel builder's responsibility.
10.9.2 POWER- FREQUENCY ELECTRIC STRENGTH	ls the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	ls the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	ls the panel builder's responsibility.
FRAME	NZM2
ACCESSORY/SPARE PART TYPE	Other
ТҮРЕ	Accessory. Mechanical interlock
SPECIAL FEATURES	Allows interlocking of 2, 3 or 4 switches, including different construction sized switches, with NZM-XBZ bowden cables.

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



## **Eaton Corporation plc**

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









