

PT 2+1-S-48DC/FM - Type 3 surge protection device



2817958

<https://www.phoenixcontact.com/au/products/2817958>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Rail-mountable surge arrester as device protection for terminal equipment, fault signal in the plug and signaling contact in the base element, 2-section, pluggable. Design: 48 V DC

Your advantages

- Easy testing and documentation with CHECKMASTER 2 with pluggable protective modules
- Maximum ease of maintenance, thanks to the 2-piece design
- Easy selection for all possible demands in MCR applications with a complete product portfolio
- The signal is not influenced during maintenance work, thanks to the impedance-neutral insertion and removal of protective plugs
- Permanent protective device monitoring with optical signaling via LED

Commercial data

Item number	2817958
Packing unit	10 pc
Minimum order quantity	1 pc
Sales key	CL1411
Product key	CL1411
Catalog page	Page 84 (C-4-2019)
GTIN	4017918574987
Weight per piece (including packing)	67.93 g
Weight per piece (excluding packing)	63.465 g
Customs tariff number	85363090
Country of origin	DE

PT 2+1-S-48DC/FM - Type 3 surge protection device



2817958

<https://www.phoenixcontact.com/au/products/2817958>

Technical data

Product properties

IEC power supply system	DC
Type	DIN rail module, two-section, divisible
Product type	Device protection
Surge protection fault message	Optical, remote indicator contact

Insulation characteristics

Overvoltage category	III
Pollution degree	2
Arrester can be tested with CHECKMASTER from software version:	From SW rev. 1.00
IEC test classification	III
	T3
EN type	T3
Number of ports	One

Electrical properties


Indicator/remote signaling

Connection name	Remote fault indicator contact
Switching function	N/C contact
Operating voltage	7 V DC ... 70 V DC (open collector)
Operating current	5 mA DC ... 15 mA (open collector)

Connection data

Connection method	Screw connection
Screw thread	M3
Tightening torque	0.8 Nm
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section AWG	24 ... 12

Dimensions

Dimensional drawing	
Width	17.7 mm
Height	90 mm
Depth	65.5 mm (incl. DIN rail 7.5 mm)
Horizontal pitch	1 Div.

PT 2+1-S-48DC/FM - Type 3 surge protection device



2817958

<https://www.phoenixcontact.com/au/products/2817958>

Material specifications

Color	black (RAL 9005)
	Copper
Flammability rating according to UL 94	V-0
CTI value of material	600
Insulating material	PA 6.6
Housing material	PA 6.6

Protective circuit

Mode of protection	L-N
	L-PE
	N-PE
	(L+) - (L-)
	(L+/L-) - PE
Direction of action	1L-N & N-PE
Nominal voltage U_N	48 V DC
Maximum continuous voltage U_C	60 V DC
Rated load current I_L	26 A (30 °C)
Residual current I_{PE}	$\leq 10 \mu A$
Nominal discharge current I_n (8/20) μs	500 A
Combination wave U_{OC}	1 kV (2 Ω)
	1 kV (2 Ω)
Voltage protection level U_p	$\leq 120 V$
Response time t_A (L-N)	$\leq 1 ns$
Response time t_A (L-PE)	$\leq 1 ns$
Short-circuit current rating I_{SCCR}	200 A (without backup fuse for U_C)
Max. backup fuse with branch wiring	50 A (gG)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	$\leq 2000 m$ (amsl)
Permissible humidity (operation)	5 % ... 95 %

Standards and regulations

Air clearances and creepage distances

Standards/regulations	DIN VDE 0110-1 / IEC 60664-1 / DIN VDE 0675-6 / IEC 61643-1
Standards/specifications	EN 61643-11
Note	2012
Standards/specifications	IEC 61643-11

Note	2011
------	------

Mounting

Mounting type	DIN rail: 35 mm
---------------	-----------------

PT 2+1-S-48DC/FM - Type 3 surge protection device




2817958


<https://www.phoenixcontact.com/au/products/2817958>

Drawings


Circuit diagram



Dimensional drawing




Diagram



The figure shows the minimum load resistance (R_L) at the transistor output of the remote indication contact depending on the specified input voltage (U_{in}).

Connection diagram



The voltage of the cable to be protected (U_{in}) determines the current driven by the transistor output (I_{FM}).

PT 2+1-S-48DC/FM - Type 3 surge protection device



2817958

<https://www.phoenixcontact.com/au/products/2817958>

Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/au/products/2817958>



EAC

Approval ID: EAC-Zulassung



EAC

Approval ID: RU C-DE.*09.B.00169

PT 2+1-S-48DC/FM - Type 3 surge protection device



2817958

<https://www.phoenixcontact.com/au/products/2817958>

Classifications

ECLASS

ECLASS-11.0	27130806
ECLASS-13.0	27171203

ETIM

ETIM 9.0	EC000942
----------	----------

UNSPSC

UNSPSC 21.0	39121600
-------------	----------

Environmental product compliance

REACH SVHC	Lead 7439-92-1
	Hexahydromethylphthalic anhydride
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd
Unit 7, 2-8 South Street
Rydalmere NSW 2116
1300 786 411
customerservice@phoenixcontact.com.au