Specifications







Eaton 283109

Eaton Moeller® series DILM Reversing wiring kit DILM17 to DILM38

| General specifications | |
|-------------------------|---|
| PRODUCT NAME | Eaton Moeller® series DILM reversing wiring kit |
| CATALOG NUMBER | 283109 |
| MODEL CODE | DILM32-XRL |
| EAN | 4015082831097 |
| PRODUCT LENGTH/DEPTH | 81 mm |
| PRODUCT HEIGHT | 29 mm |
| PRODUCT WIDTH | 40 mm |
| PRODUCT WEIGHT | 0.056 kg |
| CERTIFICATIONS | UL CSA UL Category Control No.: NLRV UL File No.: E36332 CSA File No.: 012528 UL 508 CSA-C22.2 No. 14-05 IEC/EN 60947-4-1 CSA Class No.: 3211-04 CE |
| GLOBAL CATALOG | 283109 |



| Product specifications | |
|--|--|
| 10.10 TEMPERATURE RISE | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 SHORT-CIRCUIT RATING | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 ELECTROMAGNETIC COMPATIBILITY | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 MECHANICAL FUNCTION | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |
| 10.2.2 CORROSION RESISTANCE | Meets the product standard's requirements. |
| 10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES | Meets the product standard's requirements. |
| 10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT | Meets the product standard's requirements. |
| 10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS | Meets the product standard's requirements. |
| 10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION | Meets the product standard's requirements. |
| 10.2.5 LIFTING | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 MECHANICAL IMPACT | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 INSCRIPTIONS | Meets the product standard's requirements. |
| 10.3 DEGREE OF PROTECTION OF ASSEMBLIES | Does not apply, since the entire switchgear needs to be evaluated. |

| Resources | |
|------------------------------|--|
| | SmartWire-DT Catalog |
| CATALOGS | Product Range Catalog Switching and protecting motors |
| | eaton-product-overview- for-machinery-catalogue- ca08103003zen-en-us.pdf |
| | DA-DC-00004776.pdf |
| DECLARATIONS OF CONFORMITY | DA-DC-00004783.pdf |
| | DA-DC-00004816.pdf |
| DRAWINGS | eaton-contactors-wiring- dilm-accessory-3d- drawing-002.eps |
| ECAD MODEL | ETN.283109.edz |
| INSTALLATION INSTRUCTIONS | IL03407031Z2021_07.pdf |
| INSTALLATION VIDEOS | WIN-WIN with push-in technology |
| MCAD MODEL | dil_m32_xrl.stp dil_m32_xrl |

| 10.4 CLEARANCES AND CREEPAGE DISTANCES | Meets the product standard's requirements. |
|---|--|
| 10.5 PROTECTION AGAINST ELECTRIC SHOCK | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS | ls the panel builder's responsibility. |
| 10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS | Is the panel builder's responsibility. |
| 10.9.2 POWER- FREQUENCY ELECTRIC STRENGTH | Is the panel builder's responsibility. |
| 10.9.3 IMPULSE WITHSTAND VOLTAGE | ls the panel builder's responsibility. |
| 10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL | ls the panel builder's responsibility. |
| MODEL | Reversing switching |
| AMBIENT OPERATING TEMPERATURE - MAX | 60 °C |
| AMBIENT OPERATING TEMPERATURE - MIN | -25 °C |
| EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID | 1.8 W |
| HEAT DISSIPATION CAPACITY PDISS | 0 W |
| HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID | 0.6 W |
| RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) | 45 A |
| STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS | 0 W |
| SUITABLE FOR NUMBER OF POLES | 3 |
| PRODUCT CATEGORY | Accessories |
| | |

| PROJECT NAME: | |
|-----------------|--|
| PROJECT NUMBER: | |
| PREPARED BY: | |
| DATE: | |



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









