

FL HUB 8TX-ZF - Ethernet hub



2832551
<https://www.phoenixcontact.com/us/products/2832551>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DIN rail mountable Ethernet hub with eight RJ45 ports supports Ethernet with 10 Mbps as well as with 100 Mbps

Product description

Ethernet hub with eight RJ45 ports. The hub is used for quick and cost-effective Ethernet network expansion. It has eight twisted pair ports, which can be connected to additional network segments or termination devices. The FL HUB 8TX-ZF supports Ethernet with 10 Mbps as well as with 100 Mbps. The hub regenerates the data telegrams received and transmits them to the remaining ports. For port 5, a port assignment switch is located on the hub. The transmit and receive cables are exchanged at port 5 by actuating the switch, while polarity is maintained. Application: Simple expansion of networks without configuration.

Your advantages

- Outcross port
- 10/100 Mbps, can be selected
- High port density

Commercial data

Item number	2832551
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	DN13
Product key	DNN141
Catalog page	Page 399 (C-6-2017)
GTIN	4017918996215
Weight per piece (including packing)	341.1 g
Weight per piece (excluding packing)	140 g
Customs tariff number	85176200
Country of origin	DE

FL HUB 8TX-ZF - Ethernet hub



2832551

<https://www.phoenixcontact.com/us/products/2832551>

Technical data

Dimensions

Width	45 mm
Height	99 mm
Depth	112 mm

Material specifications

Color	green
Housing material	Plastic

Mounting

Mounting type	DIN rail mounting
Connection method	RJ45, shielded

Interfaces

Ethernet

Connection method	RJ45 jack
Transmission speed	10/100 Mbps
Transmission physics	Ethernet RJ45
Transmission length	100 m
Signal LEDs	Data receive, link status
No. of channels	8 (RJ45 ports)

Product properties

Type	Stand-Alone
Product type	Switch
Operating mode	Semi-duplex

Insulation characteristics

Protection class	III (IEC 61140, EN 61140, VDE 0140-1)
------------------	---------------------------------------

Switch functions

Basic functions	Hub/repeater, compliance with IEEE 802.3
Status and diagnostic indicators	LEDs: UL (communications voltage), COL (collision) link and receive LED per port

Security functions

Basic functions	Hub/repeater, compliance with IEEE 802.3
-----------------	--

Electrical properties

Electrical isolation	10BASE-T//100BASE-TX//Supply
Local diagnostics	US Supply voltage Green LED
	COL Telegram collisions LED red
	Link status Green LED

FL HUB 8TX-ZF - Ethernet hub



2832551

<https://www.phoenixcontact.com/us/products/2832551>

Maximum power dissipation for nominal condition	3.456 W
Test section	500 V DC 50 Hz 1 min.
Transmission medium	Copper

Supply

Supply voltage (DC)	24 V DC
Supply voltage range	18.5 V DC ... 30.5 V DC
Power supply connection	Via COMBICON, max. conductor cross section 2.5 mm ²
Residual ripple	3.6 V _{PP} (within the permitted voltage range)
Typical current consumption	typ. 144 mA (at U _S = 24 V DC)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 60 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	30 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	30 % ... 95 % (non-condensing)
Vibration (operation)	in acc. with IEC 60068-2-6: 5g, 150 Hz
Air pressure (operation)	86 kPa ... 108 kPa (1500 m above sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (3500 m above sea level)
Resistance to gases that may endanger the functions, in acc. with DIN 40046-36, DIN 40046-37	Sulfur dioxide (SO ₂) 10 ±0.3 cm ³ /m ³ , hydrogen sulfide (H ₂ S) 1 ±0.3 cm ³ /m ³ , at 25°C and 75% humidity and exposure of four days

Standards and regulations

Free from substances that could impair the application of coating	In acc. with VW specification
Electrical isolation	10BASE-T//100BASE-TX//Supply

EMC data

Conformance with EMC directives	IEC 61000-6-2 IEC 61000-4-2 (ESD) Criterion B
	IEC 61000-4-3 (immunity to radiated interference) Criterion A
	IEC 61000-4-4 (burst) Criterion B
	IEC 61000-4-5 (surge) Class A
	IEC 61000-4-6 (immunity to conducted interference) Criterion A
	IEC 61000-4-8 (immunity to magnetic fields) Criterion A
	EN 55022 (emitted interference) Criterion A
Noise immunity	EN 61000-6-2:2005
Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
Noise emission	EN 61000-6-4

System properties

Functionality

Basic functions	Hub/repeater, compliance with IEEE 802.3
-----------------	--

FL HUB 8TX-ZF - Ethernet hub



2832551

<https://www.phoenixcontact.com/us/products/2832551>

Signaling

Status display	LEDs: UL (communications voltage), COL (collision) link and receive LED per port
----------------	--

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com