

# PT 2XEX(I)-24DC-ST - Surge protection plug



2838225

<https://www.phoenixcontact.com/us/products/2838225>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



PT protective plug with protective circuit for two 2-wire floating Ex i signal circuits. Nominal voltage: 24 V DC, HART-compatible.

## Your advantages

- Easy testing and documentation with CHECKMASTER 2 with pluggable protective modules
- Maximum ease of maintenance, thanks to the 2-piece design
- Easy selection for all possible demands in MCR applications with a complete product portfolio
- The signal is not influenced during maintenance work, thanks to the impedance-neutral insertion and removal of protective plugs

## Commercial data

Item number	2838225
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	CL21
Product key	CL2113
Catalog page	Page 156 (C-4-2019)
GTIN	4017918182861
Weight per piece (including packing)	46.48 g
Weight per piece (excluding packing)	21.09 g
Customs tariff number	85363010
Country of origin	DE

# PT 2XEX(I)-24DC-ST - Surge protection plug



2838225

<https://www.phoenixcontact.com/us/products/2838225>

## Technical data

### Product properties

Product type	Surge protection for MCR technology
Product family	PLUGTRAB PT
IEC test classification	C1
	C2
	C3
	D1
Type	Male
Number of positions	4
Arrester can be tested with CHECKMASTER from software version:	From SW rev. 1.00
Wire pairs per module	2

### Insulation characteristics

Overvoltage category	III
Pollution degree	2

### Electrical properties

Nominal voltage $U_N$	24 V DC
-----------------------	---------

### Connection data

Connection method	Screw connection (in connection with the base element)
Screw thread	M3
Tightening torque	0.5 Nm
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section rigid	0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Conductor cross section AWG	24 ... 14

### Ex data

Maximum inner capacitance $C_i$	1.3 nF
Max. internal inductance $L_i$	1 $\mu$ H
Max. input current $I_i$	325 mA (T4 / $\leq 80^\circ\text{C}$ )
	325 mA (T5 / $\leq 55^\circ\text{C}$ )
	325 mA (T6 / $\leq 40^\circ\text{C}$ )
Max. input voltage $U_i$	30 V DC
max. input power $P_i$	3.00 W
Maximum inner time factor ( $R_i/L_i$ )	$\leq 0.2 \mu\text{s}$
Ambient temperature (operation)	-40 °C ... 80 °C (T4)
	-40 °C ... 55 °C (T5)
	-40 °C ... 40 °C (T6)

### Dimensions

# PT 2XEX(I)-24DC-ST - Surge protection plug



2838225

<https://www.phoenixcontact.com/us/products/2838225>

Dimensional drawing	
Width	17.7 mm
Height	44.8 mm
Depth	51.7 mm
Horizontal pitch	1 Div.
Complete module width	17.7 mm
Complete module height	90 mm
Complete module depth	65.5 mm

## Material specifications

Color	blue (RAL 5015)
Flammability rating according to UL 94	V-0
Housing material	PA 6.6

## Mechanical properties

### Mechanical data

Open side panel	No
-----------------	----

## Protective circuit

Direction of action	Line-Line & Line-Signal Ground/Shield & Signal Ground/Shield-Earth Ground
Maximum continuous voltage $U_C$	30 V DC
	21 V AC
Rated current	325 mA (40 °C)
Operating effective current $I_C$ at $U_C$	$\leq 5 \mu A$
Residual current $I_{PE}$	$\leq 4 \mu A$
Nominal discharge current $I_n$ (8/20) $\mu s$ (line-line)	10 kA
Nominal discharge current $I_n$ (8/20) $\mu s$ (line-ground)	10 kA
Pulse discharge current $I_{imp}$ (10/350) $\mu s$ (line-line)	1 kA
Pulse discharge current $I_{imp}$ (10/350) $\mu s$ (line-earth)	2 kA (in total)
Total discharge current $I_{total}$ (8/20) $\mu s$	20 kA
Total discharge current $I_{total}$ (10/350) $\mu s$	2 kA
Max. discharge current $I_{max}$ (8/20) $\mu s$ maximum (line-line)	10 kA
Max. discharge current $I_{max}$ (8/20) $\mu s$ maximum (line-earth)	20 kA (in total)
Nominal pulse current $I_{an}$ (10/1000) $\mu s$ (line-line)	30 A
Output voltage limitation at 1 kV/ $\mu s$ (line-line) spike	$\leq 45 V$
Output voltage limitation at 1 kV/ $\mu s$ (line-earth) spike	$\leq 1 kV$
Output voltage limitation at 1 kV/ $\mu s$ (line-line) static	$\leq 45 V$
Output voltage limitation at 1 kV/ $\mu s$ (line-earth) static	$\leq 1 kV$
Residual voltage at $I_n$ (conductor-conductor)	$\leq 45 V$

# PT 2XEX(I)-24DC-ST - Surge protection plug



2838225

<https://www.phoenixcontact.com/us/products/2838225>

Residual voltage with I <sub>an</sub> (10/1000) μs (line-line)	≤ 50 V
Voltage protection level U <sub>p</sub> (line-line)	≤ 45 V (C1 - 0.5 kV / 250 A)
	≤ 50 V (C1 - 1 kV / 500 A)
	≤ 60 V (C2 - 2 kV/1 kA)
	≤ 100 V (C2 - 10 kV / 5 kA)
	≤ 50 V (C3 - 10 A)
	≤ 50 V (C3 - 25 A)
	≤ 150 V (D1 - 1 kA)
Voltage protection level U <sub>p</sub> (line-earth)	≤ 1 kV (C1 - 1 kV / 500 A)
	≤ 1 kV (C2 - 2 kV/1 kA)
	≤ 1 kV (C2 - 10 kV / 5 kA)
	≤ 1 kV (D1 - 1 kA)
Response time t <sub>A</sub> (line-line)	≤ 1 ns
Response time t <sub>A</sub> (line-earth)	≤ 100 ns
Input attenuation aE, sym.	typ. 0.5 dB (≤ 900 kHz/50 Ω)
	typ. 0.2 dB (≤ 300 kHz / 150 Ω)
	typ. 0.1 dB (≤ 60 kHz/600 Ω)
Cut-off frequency f <sub>g</sub> (3 dB), sym. in 50 Ω system	typ. 4.5 MHz
Cut-off frequency f <sub>g</sub> (3 dB), sym. in 150 Ω system	typ. 1.6 MHz
Cut-off frequency f <sub>g</sub> (3 dB), sym. in 600 Ω system	typ. 400 kHz
Resistance per path	2.2 Ω ±10 %
Surge protection fault message	none
Max. required back-up fuse	315 mA (T)
Impulse durability (line-line)	C1 - 0.5 kV / 250 A
	C1 - 1 kV / 500 A
	C2 - 2 kV / 1 kA
	C2 - 10 kV / 5 kA
	C3 - 10 A
	C3 - 25 A
	D1 - 1 kA
Impulse durability (line-earth)	C1 - 1 kV / 500 A
	C2 - 2 kV / 1 kA
	C2 - 10 kV / 5 kA
	D1 - 1 kA
Alternating current carrying capacity (line-earth)	10 A - 1 s

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Altitude	≤ 2000 m (amsl)

## Approvals

# PT 2XEX(I)-24DC-ST - Surge protection plug



2838225

<https://www.phoenixcontact.com/us/products/2838225>

## Conformity/Approvals

ATEX	⊕ II 1G Ex ia IIC T4...T6 Ga
	⊕ II 1D Ex ia IIIC T135°C...T85°C Da
IECEX	Ex ia IIC T4...T6 Ga
	Ex ia IIIC T135 °C...T85 °C Da

## Standards and regulations

Standards/specifications	EN 61643-21
Note	A2:2013
Standards/specifications	EN 60079-0
Note	2018
Standards/specifications	EN 60079-11
Note	2012
Standards/specifications	IEC 61643-21
Note	A2:2012
Standards/specifications	IEC 60079-0
Note	2017
Standards/specifications	IEC 60079-11
Note	2011

## Mounting

Mounting type	on base element
---------------	-----------------

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)