

# PT 4X1-24DC-ST - Surge protection plug



2838322

<https://www.phoenixcontact.com/us/products/2838322>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Protective plug PT with protective circuit for 4 conductors of signal circuits grounded on one side.  
Nominal voltage: 24 V DC

## Your advantages

- Easy testing and documentation with CHECKMASTER 2 with pluggable protective modules
- Maximum ease of maintenance, thanks to the 2-piece design
- Easy selection for all possible demands in MCR applications with a complete product portfolio
- The signal is not influenced during maintenance work, thanks to the impedance-neutral insertion and removal of protective plugs

## Commercial data

Item number	2838322
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	CL21
Product key	CL2111
Catalog page	Page 135 (C-4-2019)
GTIN	4017918182717
Weight per piece (including packing)	26.9 g
Weight per piece (excluding packing)	24.574 g
Customs tariff number	85363010
Country of origin	DE

# PT 4X1-24DC-ST - Surge protection plug

2838322

<https://www.phoenixcontact.com/us/products/2838322>

## Technical data

### Product properties

IEC test classification	C1
	C2
	C3
	D1
VDE requirement class	C1
	C2
	C3
	D1
Type	Male
Product type	Surge protection for MCR technology
Product family	PLUGTRAB PT
Surge protection fault message	none
Arrester can be tested with CHECKMASTER from software version:	From SW rev. 1.00

### Insulation characteristics

Overvoltage category	III
Pollution degree	2


### Electrical properties

Nominal voltage $U_N$	24 V DC
-----------------------	---------

### Connection data

Connection method	Screw connection (in connection with the base element)
Screw thread	M3
Tightening torque	0.8 Nm
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section rigid	0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Conductor cross section AWG	24 ... 12

### Dimensions

Dimensional drawing	
Width	17.7 mm
Height	45 mm
Depth	52 mm
Horizontal pitch	1 Div.
Complete module width	17.7 mm

# PT 4X1-24DC-ST - Surge protection plug



2838322

<https://www.phoenixcontact.com/us/products/2838322>

Complete module height	90 mm
Complete module depth	65.5 mm

## Material specifications

Color	black (RAL 9005) Copper
Flammability rating according to UL 94	V-0
Housing material	PA 6.6

## Mechanical properties

### Mechanical data

Open side panel	No
-----------------	----

## Protective circuit

Direction of action	Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground
Maximum continuous voltage $U_C$	28 V DC 20 V AC
Rated current	300 mA (45 °C)
Operating effective current $I_C$ at $U_C$	$\leq 5 \mu A$
Residual current $I_{PE}$	$\leq 1 \mu A$ (with PT 4X1+F-BE) $\leq 20 \mu A$ (Directly grounded)
Nominal discharge current $I_n$ (8/20) $\mu s$ (line-ground)	10 kA
Pulse discharge current $I_{imp}$ (10/350) $\mu s$	2.5 kA (per path)
Total discharge current $I_{total}$ (8/20) $\mu s$	20 kA
Max. discharge current $I_{max}$ (8/20) $\mu s$ maximum (line-earth)	10 kA
Nominal pulse current $I_{an}$ (10/1000) $\mu s$ (line-earth)	30 A
Output voltage limitation at 1 kV/ $\mu s$ (line-earth) spike	$\leq 45 V$
Output voltage limitation at 1 kV/ $\mu s$ (line-earth) static	$\leq 40 V$
Residual voltage at $I_n$ (conductor-ground)	$\leq 40 V$
Voltage protection level $U_p$ (line-earth)	$\leq 80 V$ (C2 - 10 kV / 5 kA)
Response time $t_A$ (line-earth)	$\leq 1 ns$
Input attenuation aE, asym.	0.5 dB ( $\leq 1 MHz$ )
Cut-off frequency $f_g$ (3 dB), asym. (PE) in 50 $\Omega$ system	typ. 6 MHz
Capacity (Core-Earth)	1.4 nF
Resistance per path	4.7 $\Omega$
Surge protection fault message	none
Max. required back-up fuse	315 mA (T)
Impulse durability (line-earth)	C2 - 10 kV / 5 kA D1 - 2.5 kA

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
----------------------	------

# PT 4X1-24DC-ST - Surge protection plug



2838322

<https://www.phoenixcontact.com/us/products/2838322>

Ambient temperature (operation)	-40 °C ... 85 °C
---------------------------------	------------------

## Standards and regulations

VDE requirement class	C1
	C2
	C3
	D1

## Air clearances and creepage distances

Standards/regulations	VDE 0110-1 / IEC 60664-1
-----------------------	--------------------------

## Standards Information technology specification

Standards/regulations	IEC 61643-21
	DIN EN 61643-21
	UL 497B
	IEC 61643-21
	DIN EN 61643-21
	UL 497B
Standards/specifications	IEC 61643-21
Note	2000

## Mounting

Mounting type	on base element
---------------	-----------------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)