

2854212

https://www.phoenixcontact.com/us/products/2854212

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DIN rail housing, Lower housing part with metal foot catch, with FE contact, tall design, with vents, width: 22.6 mm, height: 99 mm, depth: 107.3 mm, color: green (similar RAL 6021), cross connection: integrated bus connector, number of positions cross connector: 10+2, Bus connector: 10 parallel contacts, 2 serial contacts

Your advantages

- · Tool-free mounting
- · Available in overall widths from 12.5 mm to 90 mm, modular extension possible
- · Flammability rating V0 in accordance with UL 94
- · Variety of connection technology
- · Can be mounted on the DIN rail
- With integrated or DIN-rail-mountable bus connector as an option

Commercial data

Item number	2854212
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	AC08
Product key	ACHAAB
Catalog page	Page 663 (C-1-2013)
GTIN	4017918190187
Weight per piece (including packing)	57.293 g
Weight per piece (excluding packing)	57.293 g
Customs tariff number	85369010
Country of origin	DE



2854212

https://www.phoenixcontact.com/us/products/2854212

Technical data

Notes

General	Refer to the data sheet for the range in the download area.
General	Material of contact pads for bus connector, galvanic gold (hard gold)

Product properties

Product type	Enclosure bottom part
Housing type	DIN rail housing
Housing series	ME
Product family	ME 22,5
Туре	Lower housing parts with vents, housing cover necessary to complete the module
Max. number of positions	0)
Туре	Lower housing part with metal foot catch, with FE contact, tall design
Ventilation openings present	yes

Dimensions

Dimensional drawing	d
Width	22.6 mm
Height	99 mm
Depth	107.3 mm
Depth from top edge of DIN rail	100.7 mm
Depth from top edge of DIN rail to support point on upper part	68.5 mm
PCB design	
PCB thickness	1.4 mm 1.8 mm

Material specifications

Color (Housing)	green (RAL 6021)
Material (Housing)	PA
Flammability rating according to UL 94	V0
CTI according to IEC 60112	600
Housing material	Polyamide
Surface characteristics	untreated



2854212

https://www.phoenixcontact.com/us/products/2854212

Environmental and real-life conditions

Power dissipation single housing for 20 °C	
Ambient temperature	20 °C
Reduction factor	1
Mounting position	vertical
Power dissipation	6.1 W
Power dissipation single housing for 30 °C	
Ambient temperature	30 °C
Reduction factor	0.91
Mounting position	vertical
Power dissipation	5.5 W
Power dissipation single housing for 40 °C	
Ambient temperature	40 °C
Reduction factor	0.81
Mounting position	vertical
Power dissipation	4.9 W
Power dissipation single housing for 50 °C	
Ambient temperature	50 °C
Reduction factor	0.7
Mounting position	vertical
Power dissipation	4.3 W
Power dissipation single housing for 60 °C	
Ambient temperature	60 °C
Reduction factor	0.57
Mounting position	vertical
Power dissipation	3.5 W
Power dissipation single housing for 70 °C	
Ambient temperature	70 °C
Reduction factor	0.49
Mounting position	vertical
Power dissipation	3.1 W
Vibration test	
Specification	IEC 60068-2-6:2007-12
Frequency	10 - 150 - 10 Hz
Sweep speed	1 octave/min
Amplitude	0.15 mm (10 Hz 58.1 Hz)
Acceleration	2g (58.1 Hz 150 Hz)
Test duration per axis	2.5 h
Test directions	X-, Y- and Z-axis



2854212

https://www.phoenixcontact.com/us/products/2854212

Outer packaging type

Specification	IEC 60695-2-11:2014-02
Temperature	850 °C
Time of exposure	30 s
hermal stability / ball thrust test	
Specification	IEC 60695-10-2:2014-02
Temperature	125 °C
Test duration	1 h
Force	20 N
Mechanical strength / tumbling barrel	
Specification	IEC 60998-1:2002-12
Height of fall	50 cm
Frequency	10
Shocks	
Specification	IEC 60068-2-27:2008-02
Pulse shape	Half-sine
Acceleration	15g
Shock duration	11 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)
Degree of protection (IP code)	
Specification	IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08
Ambient conditions	
Max. IP code to attain	IP20
Ambient temperature (operation)	-40 °C 105 °C (depending on power dissipation)
Ambient temperature (storage/transport)	-40 °C 55 °C
Ambient temperature (assembly)	-5 °C 100 °C
Relative humidity (storage/transport)	80 %
B data	
Number of PCB holders	1
Type of PCB mount	Insertion (optional latching by PCB stop)
Thickness of the PCB	1.4 mm 1.8 mm
unting	
-	DIM seil se continue
Mounting type	DIN rail mounting
Mounting position	Vertical (horizontal DIN rail)
ckaging specifications	
Type of peakeging	packed in cardboard
Type of packaging	paonou in ouraboura

Carton



2854212

https://www.phoenixcontact.com/us/products/2854212

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com