

https://www.phoenixcontact.com/pc/products/2859330



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Wiring bridge for modules with connecting pitch 17.5 mm, 2-phase, 4-pos.

Your advantages

- · In combination with other devices in the distribution board, such as residual current devices and miniature circuit breakers
- · Practical wiring of all common applications
- · For combinations of lightning and surge arresters
- End covers are used to terminate and insulate individually cut bridges

Commercial data

Item number	2859330
Packing unit	10 pc
Minimum order quantity	1 pc
Product key	CL132Z
GTIN	4046356045445
Weight per piece (including packing)	32.9 g
Weight per piece (excluding packing)	32.9 g
Customs tariff number	85369095
Country of origin	DE



https://www.phoenixcontact.com/pc/products/2859330



Technical data

Product properties

Product type	Bridge
Туре	Comb bridge
Number of positions	4

Electrical properties

Number of phases	2
Nominal current I _N	80 A

Material specifications

Color	light grey (RAL 7035)
	Copper
Housing material	Plastic



https://www.phoenixcontact.com/pc/products/2859330



Classifications

ECLASS

	ECLASS-11.0	27371306
	ECLASS-12.0	27371306
	ECLASS-13.0	27371306
ETIM		
	ETIM 9.0	EC000215
UNSPSC		

U



https://www.phoenixcontact.com/pc/products/2859330



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
ELL DE ACIL CYALC	
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstraße 8 D-32825 Blomberg +49 (0) 5235-3 00 info@phoenixcontact.com