MINI-BAT/12DC/1.6AH - Battery module

2866572

https://www.phoenixcontact.com/pc/products/2866572

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Energy storage device, lead AGM, VRLA technology, 12 V DC, 1.6 Ah.

Product description

MINI-BAT - energy storage with lead AGM technology for maximum buffer times.

Your advantages

Maximum buffer times

Commercial data

Item number	2866572
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	CMUEV3
Catalog page	Page 353 (C-4-2019)
GTIN	4046356476492
Weight per piece (including packing)	829.5 g
Weight per piece (excluding packing)	800 g
Customs tariff number	85072080
Country of origin	CN

PHŒN

MINI-BAT/12DC/1.6AH - Battery module



https://www.phoenixcontact.com/pc/products/2866572



Technical data

Input data	
------------	--

Input voltage	12 V DC
Buffer period	60 min. (1 A)
	6 min. (4 A)
utput data	
Nominal output voltage	12 V DC
Output current I _{max}	10 A
Output fuse	10 A
Connection in parallel	5
Connection in series	No
Battery operation	
Nominal output voltage	12 V DC
Nominal output current (I _N)	10 A
nergy storage	
End-of-charge voltage	13.8 V
Charging current	1 A
Nominal capacity	1.6 Ah
Battery module service life	3 Years (20 °C)
Latest startup (battery only) - range	3 Months (0 °C 20 °C)
	3 Months 1 Months (20 °C 30 °C)
	1 Months (30 °C 40 °C)
Battery technology	VRLA-AGM
Memory medium	Lead rechargeable battery module
Accumulator type	YUASA NP0.8-12
	YUCEL Y0.8-12
	YUVOLT 0.8-12
Number of cells	1
Size designation	Block
Battery pack	yes
Disposal	Used batteries must not be thrown away with household waste, they should instead be disposed of in accordance with applicabl national regulations.
IQ technology	no
Suitable for fast charging	yes

Product properties

Product type	Battery unit
Product family	Battery module
Application	for MINI DC-UPS
Disposal	Used batteries must not be thrown away with household waste,

MINI-BAT/12DC/1.6AH - Battery module



2866572

https://www.phoenixcontact.com/pc/products/2866572

	they should instead be disposed of in accordance with applicable national regulations.
IQ technology	no
Insulation characteristics	
Protection class	III
imensions	
Width	67.5 mm
Height	99 mm
Depth	107 mm
Installation dimensions	
Installation distance right/left	0 mm / 0 mm
Installation distance top/bottom	30 mm / 30 mm
nvironmental and real-life conditions	
Degree of protection	IP20
Ambient temperature (operation)	0 °C 40 °C
Ambient temperature (storage/transport)	0 °C 40 °C
•• • • • • • • • • • • • • • • •	95 %
Max. permissible relative humidity (operation)	
Max. permissible relative humidity (operation)	

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstraße 8 D-32825 Blomberg +49 (0) 5235-3 00 info@phoenixcontact.com