

IB IL AI 4/EF-PAC - Analog module



2878447

<https://www.phoenixcontact.com/in/products/2878447>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Inline, Analog input terminal, Analog inputs: 4, 0 V ... 5 V, -5 V ... 5 V, 0 V ... 10 V, -10 V ... 10 V, 0 mA ... 20 mA, 4 mA ... 20 mA, -20 mA ... 20 mA, connection technology: 2-, 3-, 4-conductor, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connectors and marking fields

Product description

The terminal is designed for use within an Inline station. It is used to acquire analog voltage and current signals.

Your advantages

- 4 differential signal inputs
- Connection of sensors in 2-, 3-, and 4-conductor technology
- Current ranges: 0 mA ... 20 mA, 4 mA ... 20 mA, ± 20 mA
- Voltage ranges: 0 V ... 10 V, ± 10 V, 0 V ... 5 V, ± 5 V
- The channels are parameterized independently of one another via the bus system
- Parameterization via process data or PCP
- Measured values can be represented in four different formats
- Resolution depends on the representation format and the measuring range
- Process data update of all channels in max. 1 ms
- Sensor supply with channel-specific integrated short-circuit and overload protection
- Bus-synchronous provision of input values with very low jitter ($< 10 \mu\text{s}$)

Commercial data

Item number	2878447
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DRI
Product key	DRI141
Catalog page	Page 136 (C-6-2019)
GTIN	4017918996376
Weight per piece (including packing)	252 g
Weight per piece (excluding packing)	210 g
Customs tariff number	85389091
Country of origin	DE

IB IL AI 4/EF-PAC - Analog module


2878447

<https://www.phoenixcontact.com/in/products/2878447>



Technical data

Dimensions

Dimensional drawing		
Width		48.8 mm
Height		135 mm
Depth		71.5 mm
Note on dimensions		Housing dimensions

Notes

Utilization restriction		
CCCex note		Use in potentially explosive areas is not permitted in China.

Interfaces

Inline local bus		
Number of interfaces		2
Connection method		Inline data jumper
Transmission speed		500 kbps

System properties

Module		
ID code (dec.)		223
ID code (hex)		DF
Length code (hex)		05
Length code (dec)		05
Process data channel		80 bit
Input address area		10 Byte
Output address area		10 Byte
Register length		96 bit
Required parameter data		28 Byte
Required configuration data		4 Byte

Input data

Analog		
Input name		Analog inputs
Description of the input		Differential input, including sensor supply (24 V DC)

IB IL AI 4/EF-PAC - Analog module



2878447

<https://www.phoenixcontact.com/in/products/2878447>

Number of inputs	4
A/D conversion time	max. 10 µs
A/D converter resolution	16 bit
Connection method	Inline shield connector
Connection technology	2-, 3-, 4-conductor
Note regarding the connection technology	shielded
Current input signal	0 mA ... 20 mA
	4 mA ... 20 mA
	-20 mA ... 20 mA
Input resistance current input	typ. 110 Ω
Voltage input signal	0 V ... 5 V
	-5 V ... 5 V
	0 V ... 10 V
	-10 V ... 10 V
Input resistance of voltage input	typ. 300 kΩ
Data formats	IB IL, IB ST, standardized representation, S7 compatible
Limit frequency (3 dB)	500 Hz
Measured value resolution	16 bits (15 bits + sign bit)
Protective circuit	Transient protection; Yes, via arresters
	Overload protection of the current inputs; electronic

Product properties

Type	modular
Product type	I/O component
Product family	Inline
Scope of delivery	including Inline connectors and marking fields
Operating mode	Process data mode with 5 words/1 word PCP
Diagnostics messages	Failure of the internal I/O supply I/O error message sent to the bus coupler
	Failure of or insufficient communications power U_L I/O error message sent to the bus coupler
	I/O error Error message in the process data
	User error Error message in the process data

Insulation characteristics

Overvoltage category	II (IEC 60664-1, EN 60664-1)
Pollution degree	2 (IEC 60664-1, EN 60664-1)

Electrical properties

Maximum power dissipation for nominal condition	7.68 W
---	--------

Potentials

Power consumption	typ. 950 mW (entire device)
	max. 1.25 W (entire device)

Potentials: Communications power (U_L)

IB IL AI 4/EF-PAC - Analog module



2878447

<https://www.phoenixcontact.com/in/products/2878447>

Supply voltage	7.5 V DC (via voltage jumper)
Current draw	max. 100 mA
	typ. 85 mA

Potentials: Supply of analog modules (U_{ANA})

Supply voltage	24 V DC (via voltage jumper)
Supply voltage range	19.2 V DC ... 30 V DC (including all tolerances, including ripple)
Current draw	max. 20 mA
	typ. 13 mA

Potentials: Main circuit supply (U_M)

Supply voltage	24 V DC (via voltage jumper)
Supply voltage range	19.2 V DC ... 30 V DC (including all tolerances, including ripple)
Current draw	max. 200 mA
	min. 0 mA (No-load)

Supply:

Designation	Sensor supply U_{IS}
Supply voltage	24 V DC (via feed-in from U_M)
Current consumption	max. 50 mA (per channel)

Electrical isolation/isolation of the voltage ranges

Test voltage: 7.5 V supply (bus logic), 24 V supply U_{ANA} / I/O	500 V AC, 50 Hz, 1 min.
Test voltage: 7.5 V supply (bus logic), 24 V supply U_{ANA} / functional ground	500 V AC, 50 Hz, 1 min.
Test voltage: I/O/functional ground	500 V AC, 50 Hz, 1 min.

Connection data

Connection technology

Connection name	Inline connector
-----------------	------------------

Conductor connection

Connection method	Spring-cage connection
Conductor cross section rigid	0.08 mm ² ... 1.5 mm ²
Conductor cross section flexible	0.08 mm ² ... 1.5 mm ²
Conductor cross section AWG	28 ... 16
Stripping length	8 mm

Inline connector

Connection method	Spring-cage connection
Conductor cross section, rigid	0.08 mm ² ... 1.5 mm ²
Conductor cross section, flexible	0.08 mm ² ... 1.5 mm ²
Conductor cross section AWG	28 ... 16
Stripping length	8 mm

Environmental and real-life conditions

IB IL AI 4/EF-PAC - Analog module



2878447

<https://www.phoenixcontact.com/in/products/2878447>

Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Degree of protection	IP20
Air pressure (operation)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)

Standards and regulations

Protection class	III (IEC 61140, EN 61140, VDE 0140-1)
------------------	---------------------------------------

Mounting

Mounting type	DIN rail mounting
---------------	-------------------


IB IL AI 4/EF-PAC - Analog module



2878447
<https://www.phoenixcontact.com/in/products/2878447>


Drawings

Dimensional drawing



Dimensions (in mm)

Connection diagram



Connection example

IB IL AI 4/EF-PAC - Analog module



2878447

<https://www.phoenixcontact.com/in/products/2878447>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/in/products/2878447>



cUL Recognized
Approval ID: FILE E 140324



UL Recognized
Approval ID: FILE E 140324



EAC
Approval ID: TR TS_D_01921-19



DNV GL
Approval ID: TAA00000BN



LR
Approval ID: LR23398855TA



BV
Approval ID: 20989/B2_BV

BSH
Approval ID: 658a



RINA
Approval ID: ELE121121XG

ABS
Approval ID: 22-2226444-PDA

UAE-RoHS
Approval ID: 22-04-13078



cUL Listed
Approval ID: FILE E 199827

IB IL AI 4/EF-PAC - Analog module



2878447

<https://www.phoenixcontact.com/in/products/2878447>



UL Listed
Approval ID: FILE E 199827

cULus Recognized

cULus Listed

IB IL AI 4/EF-PAC - Analog module



2878447

<https://www.phoenixcontact.com/in/products/2878447>

Classifications

ECLASS

ECLASS-11.0	27242601
ECLASS-12.0	27242601
ECLASS-13.0	27242601

ETIM

ETIM 9.0	EC001596
----------	----------

UNSPSC

UNSPSC 21.0	32151600
-------------	----------

IB IL AI 4/EF-PAC - Analog module



2878447
<https://www.phoenixcontact.com/in/products/2878447>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in