

VAL-CP-350-ST-GY - Type 2 surge protection plug



2882718

Electrical number: 1658170

<https://www.phoenixcontact.com/no/products/2882718>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Replacement plug for VAL-CP surge protective device with high-capacity varistor with a low leakage current.

Commercial data

Item number	2882718
Packing unit	10 pc
Minimum order quantity	1 pc
Sales key	31BCL
Product key	CL1315
Catalog page	Page 74 (C-4-2019)
GTIN	4046356175869
Weight per piece (including packing)	54 g
Weight per piece (excluding packing)	50 g
Customs tariff number	85363090
Country of origin	DE

VAL-CP-350-ST-GY - Type 2 surge protection plug



2882718

Electrical number: 1658170

<https://www.phoenixcontact.com/no/products/2882718>

Technical data

Product properties

IEC test classification	II
	T2
EN type	T2
IEC power supply system	TN
	TT
Type	DIN rail module, two-section, divisible
Product type	Replacement plug
Number of positions	1
Surge protection fault message	optical

Insulation characteristics

Overvoltage category	III
Pollution degree	2

Electrical properties

Nominal frequency f_N	50 Hz (60 Hz)
-------------------------	---------------

Connection data

Connection method	pluggable
-------------------	-----------

Dimensions

Width	11.7 mm
Height	44.8 mm
Depth	56.4 mm
Horizontal pitch	0.6 Div.

Material specifications

Color	light grey (RAL 7035)
	black (RAL 9005)
Flammability rating according to UL 94	V-0
CTI value of material	600
Insulating material	PBT-FR
Material group	I
Housing material	PBT-FR

Protective circuit

Mode of protection	L-N
	L-PEN
Direction of action	L-N / L-PEN
Nominal voltage U_N	240 V AC (TN)

VAL-CP-350-ST-GY - Type 2 surge protection plug



2882718

Electrical number: 1658170

<https://www.phoenixcontact.com/no/products/2882718>

	240 V AC (TT)
Nominal frequency f_N	50 Hz (60 Hz)
Maximum continuous voltage U_C	350 V AC
Nominal discharge current I_n (8/20) μ s	20 kA
Maximum discharge current I_{max} (8/20) μ s	30 kA
Short-circuit current rating I_{SCCR}	25 kA
Voltage protection level U_p	≤ 1.5 kV
Residual voltage U_{res}	≤ 1.5 kV (at I_n)
	≤ 1.3 kV (at 10 kA)
	≤ 1.2 kV (at 5 kA)
	≤ 1.1 kV (at 4 kA)
	≤ 1 kV (at 2 kA)
TOV behavior at U_T	415 V AC (5 s / withstand mode)
	457 V AC (120 min / safe failure mode)
Response time t_A	≤ 25 ns
Max. backup fuse with branch wiring	315 A AC (gG)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m (amsl)
Permissible humidity (operation)	5 % ... 95 %
Shock (operation)	30g (Half-sine / 11 ms / 3x $\pm X$, $\pm Y$, $\pm Z$)
Vibration (operation)	5g (10 ... 500 Hz / 2.5 h / X, Y, Z)

Standards and regulations

Air clearances and creepage distances

Standards/regulations	DIN VDE 0110-1 / IEC 60664-1 / IEC 61643-1
Standards/specifications	IEC 61643-11
Note	2011
Standards/specifications	EN 61643-11
Note	2012

Mounting

Mounting type	on base element
---------------	-----------------

VAL-CP-350-ST-GY - Type 2 surge protection plug

2882718

Electrical number: 1658170

<https://www.phoenixcontact.com/no/products/2882718>



Drawings

Circuit diagram



VAL-CP-350-ST-GY - Type 2 surge protection plug



2882718

Electrical number: 1658170

<https://www.phoenixcontact.com/no/products/2882718>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/no/products/2882718>



EAC

Approval ID: RU C-DE.*09.B.00169

VAL-CP-350-ST-GY - Type 2 surge protection plug



2882718

Electrical number: 1658170

<https://www.phoenixcontact.com/no/products/2882718>

Classifications

ECLASS

ECLASS-11.0	27130890
ECLASS-13.0	27171292

ETIM

ETIM 9.0	EC002496
----------	----------

UNSPSC

UNSPSC 21.0	39121600
-------------	----------

VAL-CP-350-ST-GY - Type 2 surge protection plug



2882718

Electrical number: 1658170

<https://www.phoenixcontact.com/no/products/2882718>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT AS
Strømsveien 344
N-1081 Oslo
+47 22 07 68 00
norge@phoenixcontact.com