

# Industrial Ethernet Switch - FL SWITCH 1001T-4POE - 2891064

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




PoE+ Ethernet switch conforms to IEEE 802.3at. Includes four PoE+ ports and one standard RJ45 port, all with 10/100 Mbps speeds.

## Your advantages

- Auto negotiation
- Autocrossing
- Wide -40° ... +75°C temperature range
- Redundant power supply
- Automatic detection of IEEE 802.3at or 802.3af powered devices
- Wide-range power supply of 18 ... 57 V DC
- POE status LED per port

## Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 764322
GTIN	4046356764322
Weight per Piece (excluding packing)	800.000 g
Custom tariff number	85176200
Country of origin	Taiwan

## Technical data

### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

### Dimensions

Width	55 mm
Height	117 mm
Depth	78 mm

# Industrial Ethernet Switch - FL SWITCH 1001T-4POE - 2891064

## Technical data

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 75 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)
Air pressure (operation)	86 kPa ... 108 kPa (1500 m above sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (3500 m above sea level)

### Interfaces

Interface	Ethernet
No. of ports	1 (RJ45 ports)
Transmission physics	Ethernet RJ45
Transmission speed	10/100 Mbps
Transmission length	100 m (Between transmitter / receiver)
Signal LEDs	LNK/ACT, 100, POE
Interface	Ethernet (PoE)
No. of ports	4 (RJ45 ports)
Connection method	RJ45 socket
Transmission physics	Ethernet RJ45
Transmission speed	10/100 Mbps
Transmission length	100 m (Between transmitter / receiver)
Signal LEDs	LNK/ACT, 100, POE

### Function

Basic functions	PSE, complies with IEEE 802.3at
Additional functions	Autonegotiation
Status and diagnostic indicators	LEDs: $U_{S1}$ , $U_{S2}$ (redundant voltage supply), Alarm (alarm contact), Link/Activity and PoE per Ethernet port
Signal contact control voltage	250 V AC
Signal contact control current	1 A

### Network expansion parameters

Maximum conductor length (twisted pair)	100 m
---	-------

### Supply voltage

Supply voltage	24 V DC
Residual ripple	3.6 V <sub>PP</sub> (within the permitted voltage range)
Supply voltage range	18 V DC ... 57 V DC
Typical current consumption	148 mA (at $U_S = 24$ V DC)
Max. current consumption	6.2 A (Maximum, nominal load)
Inrush current	18 A (57 V DC for 100 µs)

### General

Mounting type	DIN rail
---------------	----------

# Industrial Ethernet Switch - FL SWITCH 1001T-4POE - 2891064

## Technical data

### General

Type AX	Stand-alone
Net weight	800 g
Housing material	Aluminum
Note	Mode B PoE

### Connection data

Connection method	COMBICON plug-in screw terminal block
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section flexible min.	0.2 mm <sup>2</sup>
Conductor cross section flexible max.	2.5 mm <sup>2</sup>
Conductor cross section AWG min.	24
Conductor cross section AWG max.	12
Stripping length	7 mm

### Standards and Regulations

Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
Type of test	Vibration resistance in acc. with EN 60068-2-6/IEC 60068-2-6
Test result	5g, 150 Hz, Criterion 3
Type of test	Shock in acc. with EN 60068-2-27/IEC 60068-2-27
Test result	25g, 11 ms half-sine shock pulse

### Environmental Product Compliance

	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 10;
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

## Classifications

### eCl@ss

eCl@ss 10.0.1	19170402
eCl@ss 4.0	24010504
eCl@ss 4.1	24010504
eCl@ss 5.0	19030117
eCl@ss 5.1	19030100
eCl@ss 6.0	19170100
eCl@ss 7.0	19170106
eCl@ss 8.0	19170106
eCl@ss 9.0	19170106

### ETIM

ETIM 3.0	EC000734
----------	----------

# Industrial Ethernet Switch - FL SWITCH 1001T-4POE - 2891064

## Classifications

### ETIM

ETIM 4.0	EC000734
ETIM 5.0	EC000734
ETIM 6.0	EC000734
ETIM 7.0	EC000734

### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201410
UNSPSC 13.2	43222612

## Approvals


### Approvals


#### Approvals

UL Listed / cUL Listed / EAC / EAC / KC / cULus Listed

#### Ex Approvals

### Approval details

UL Listed		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 140324
mm <sup>2</sup> /AWG/kcmil		30-14	

cUL Listed		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 140324
mm <sup>2</sup> /AWG/kcmil		30-14	

EAC		EAC-Zulassung
-----	---	---------------

# Industrial Ethernet Switch - FL SWITCH 1001T-4POE - 2891064

## Approvals

EAC		RU *- DE.A*30.B.01735
-----	--	--------------------------

KC		<a href="http://eng.kcc.go.kr/user/ehpMain.do">http://eng.kcc.go.kr/user/ehpMain.do</a>	MSIP-REI- PCK-2891064
----	--	---	--------------------------

cULus Listed		
--------------	--	--

## Accessories

### Accessories

#### Patch cable

Patch cable - FL CAT5 PATCH 0,3 - 2832250

Patch cable, CAT5, assembled, 0.3 m

---

Patch cable - FL CAT5 PATCH 10,0 - 2832629

Patch cable, CAT5, assembled, 10 m

#### Power over Ethernet devices

Ethernet module - FL PD 1001 T GT - 2891042



Factoryline Power over Ethernet splitter (PD) for separating power and data according to IEEE 802.3af and at, no configuration required, can be used with 10, 100, 1000 Mbps networks, 24 V DC output voltage

#### Power supply

Power supply unit - QUINT4-PS/1AC/24DC/5 - 2904600



Primary-switched QUINT POWER power supply with free choice of output characteristic curve, SFB (selective fuse breaking) technology, and NFC interface, input: 1-phase, output: 24 V DC/5 A

## Industrial Ethernet Switch - FL SWITCH 1001T-4POE - 2891064

### Accessories

---

#### Power supply unit - QUINT4-PS/1AC/24DC/10 - 2904601



Primary-switched QUINT POWER power supply with free choice of output characteristic curve, SFB (selective fuse breaking) technology, and NFC interface, input: 1-phase, output: 24 V DC/10 A

---

#### Power supply unit - TRIO-PS-2G/1AC/24DC/5 - 2903148



Primary-switched TRIO POWER power supply with push-in connection for DIN rail mounting, input: 1-phase, output: 24 V DC/5 A

---

#### Power supply unit - TRIO-PS-2G/1AC/24DC/10 - 2903149



Primary-switched TRIO POWER power supply with push-in connection for DIN rail mounting, input: single phase, output: 24 V DC/10 A

---

#### Power supply unit - UNO-PS/1AC/24DC/150W - 2904376



Primary-switched UNO power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/150 W

---

#### Power supply unit - UNO-PS/1AC/24DC/240W - 2904372



Primary-switched UNO power supply for DIN rail mounting, input: single-phase, output: 24 V DC/240 W

---

### Surge protection for information technology

## Industrial Ethernet Switch - FL SWITCH 1001T-4POE - 2891064

### Accessories

Surge protection device - DT-LAN-CAT.6+ - 2881007



Surge protection in accordance with Class E<sub>A</sub> (CAT6<sub>A</sub>), for Gigabit Ethernet (up to 10 Gbps), token ring, FDDI/CDDI, ISDN, and DS1. Suitable for Power over Ethernet (PoE+) "Mode A" and "Mode B". RJ45 attachment plug with separate grounding cable and ground connection snap-on foot for NS 35 DIN rails.

---

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>