

FL MEM PLUG/MRM - Configuration memory



2891275

<https://www.phoenixcontact.com/pc/products/2891275>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Exchangeable configuration memory of the device settings for simple device exchange and set-up In addition, the Media Redundancy Manager (MRM) license for use is stored within the Media Redundancy protocol (MRP).

Commercial data

Item number	2891275
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	DNN1ZM
Catalog page	Page 331 (C-6-2019)
GTIN	4046356165433
Weight per piece (including packing)	19 g
Weight per piece (excluding packing)	19 g
Customs tariff number	84717098
Country of origin	DE

FL MEM PLUG/MRM - Configuration memory



2891275

<https://www.phoenixcontact.com/pc/products/2891275>

Technical data

Product properties

Product type	Storage medium
Type	fine granularity

System properties

Memory type	FLASH-EPROM 64 kByte
-------------	----------------------

Functionality

Basic functions	Configuration memory and manager for the media redundancy protocol (MRP)
-----------------	--

Electrical properties

Maximum power dissipation for nominal condition	max. 0.02 W
---	-------------

Supply

Power supply connection	from FL SWITCH MCS/SMCS
-------------------------	-------------------------

Interfaces

Protocols supported	Manager for MRP
---------------------	-----------------

Dimensions

Width	16 mm
Height	49 mm

Material specifications

Color	green
-------	-------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 55 °C (non-condensing)
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)

EMC data

Conformance with EMC directives	IEC 61000-6-2 IEC 61000-4-2 (ESD) Criterion B
	IEC 61000-4-3 (immunity to radiated interference) Criterion A
	IEC 61000-4-4 (burst) Criterion A
	IEC 61000-4-5 (surge) Criterion A
	IEC 61000-4-6 (immunity to conducted interference) Criterion A
	IEC 61000-4-8 (immunity to magnetic fields) Criterion A
	EN 55022 (emitted interference) Criterion A

FL MEM PLUG/MRM - Configuration memory



2891275

<https://www.phoenixcontact.com/pc/products/2891275>

Noise immunity	EN 61000-6-2:2005
Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
Noise emission	EN 61000-6-3/-4

Mounting

Mounting type	In the host system
---------------	--------------------

FL MEM PLUG/MRM - Configuration memory



2891275

<https://www.phoenixcontact.com/pc/products/2891275>

Classifications

ECLASS

ECLASS-11.0	27242212
ECLASS-12.0	27242212
ECLASS-13.0	27242212

ETIM

ETIM 9.0	EC000192
----------	----------

UNSPSC

UNSPSC 21.0	32101600
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(c), 7(c)-I
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	bc25d9a9-91af-4543-acb8-2dabc5aa5c16