

FL SWITCH SFN 6GT/2LX-20 - Industrial Ethernet Switch



2891563

<https://www.phoenixcontact.com/au/products/2891563>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Ethernet switch, 6 RJ45 ports, 10/100/1000 Mbps on all RJ45 ports, 2 single mode SC-D ports with especially high range, 1 Gbps full duplex, auto negotiation (RJ45), autocrossing function, with signal contact and QoS, extended temperature range

Your advantages

- All ports offer transmission speeds of 1000 Mbps
- Jumbo frame support (frame size up to 9600 bytes/frame)
- Local diagnostic indicators with LEDs
- The switch also offers cable locking and port blocking
- Relay contact for alarm processing of voltage states
- Auto negotiation and autocrossing detection simplifies installation and setup

Commercial data

Item number	2891563
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DNN113
Product key	DNN113
Catalog page	Page 295 (C-6-2019)
GTIN	4046356116626
Weight per piece (including packing)	478.5 g
Weight per piece (excluding packing)	435 g
Customs tariff number	85176200
Country of origin	TW

FL SWITCH SFN 6GT/2LX-20 - Industrial Ethernet Switch



2891563

<https://www.phoenixcontact.com/au/products/2891563>

Technical data

Dimensions

Width	50 mm
Height	120 mm
Depth	70 mm

Material specifications

Housing material	Aluminum
------------------	----------

Mounting

Mounting type	DIN rail mounting
---------------	-------------------

Interfaces

Ethernet (RJ45)

Connection method	RJ45
Note on the connection method	Auto negotiation and autocrossing
Transmission speed	10/100/1000 Mbps
Transmission physics	Ethernet in RJ45 twisted pair
No. of channels	6 (RJ45 ports)

Fiber optic interface

Connection method	SC
Transmission speed	1000 Mbps (full duplex)
Transmission physics	Single-mode fiberglass
Transmission length	20000 m (Fiberglass 9/125)
Wavelength	1310 nm
No. of channels	2 (SC single mode)

Potential-free signaling contact

Connection method	Plug-in/screw connection via COMBICON
-------------------	---------------------------------------

Product properties

Type	Block design
Product type	Switch
Product family	Unmanaged Switch SFN
MTTF	36.4 Years (MIL-HDBK-217F standard, temperature 25°C, operating cycle 100%)

Insulation characteristics

Protection class	III (IEC 61140, EN 61140, VDE 0140-1)
------------------	---------------------------------------

Switch functions

Basic functions	Unmanaged switch / auto negotiation, complies with IEEE 802.3, store and forward switching mode
Signal contact control voltage	Monitoring of the redundant supply voltage

FL SWITCH SFN 6GT/2LX-20 - Industrial Ethernet Switch



2891563

<https://www.phoenixcontact.com/au/products/2891563>

PROFINET conformance class	Conformance-Class A
Status and diagnostic indicators	LEDs: U _{S1} , U _{S2} (redundant voltage supply), link and activity per port
Additional functions	Autonegotiation
	Jumbo frames (max. 9,600 bytes)

Security functions

Basic functions	Unmanaged switch / auto negotiation, complies with IEEE 802.3, store and forward switching mode
-----------------	---

Electrical properties

Local diagnostics	US1/2 Supply voltage Green LED
	100/ACT Link status/data transmission Yellow LED
	1000/ACT Link status/data transmission Yellow LED
Maximum power dissipation for nominal condition	8.64 W
Test section	500 V DC 1 min.
Transmission medium	Copper
	FO

Supply

Supply voltage (DC)	24 V DC (redundant)
Supply voltage range	9 V DC ... 32 V DC
Residual ripple	3.6 V _{PP} (within the permitted voltage range)
Typical current consumption	360 mA (at U _S = 24 V DC)

Function

Signal contact control voltage	Monitoring of the redundant supply voltage
--------------------------------	--

Connection data

Connection method	Screw connection
Conductor cross section, rigid	0.2 mm ² ... 2.5 mm ²
Conductor cross section, flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12
Stripping length	7 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 60 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)
Vibration (operation)	in acc. with IEC 60068-2-6: 5g, 150 Hz
Air pressure (operation)	86 kPa ... 108 kPa (up to 1500 m above sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (up to 3500 m above sea level)

FL SWITCH SFN 6GT/2LX-20 - Industrial Ethernet Switch



2891563

<https://www.phoenixcontact.com/au/products/2891563>

Resistance to gases that may endanger the functions, in acc. with DIN 40046-36, DIN 40046-37

Sulfur dioxide (SO₂) 10 ±0.3 cm³/m³, hydrogen sulfide (H₂S) 1 ±0.3 cm³/m³, at 25°C and 75% humidity and exposure of four days

EMC data

Noise immunity

EN 61000-6-2:2005

Electromagnetic compatibility

Conformance with EMC Directive 2004/108/EC

Noise emission

EN 61000-6-4

System properties

Functionality

Basic functions

Unmanaged switch / auto negotiation, complies with IEEE 802.3, store and forward switching mode

Signaling

Status display

LEDs: U_{S1}, U_{S2} (redundant voltage supply), link and activity per port

FL SWITCH SFN 6GT/2LX-20 - Industrial Ethernet Switch



2891563

<https://www.phoenixcontact.com/au/products/2891563>

Classifications

ECLASS

ECLASS-11.0

19170402

UNSPSC

UNSPSC 21.0

43222612

FL SWITCH SFN 6GT/2LX-20 - Industrial Ethernet Switch



2891563

<https://www.phoenixcontact.com/au/products/2891563>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 10;
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd
Unit 7, 2-8 South Street
Rydalmere NSW 2116
1300 786 411
customerservice@phoenixcontact.com.au