## Specifications



Photo is representative

## Eaton 289806

Eaton Moeller series NZM - Molded Case Circuit Breaker. Main switch assembly kit, handle black, on the left side

General specification	ıs
PRODUCT NAME	Eaton Moeller series NZM operating element
CATALOG NUMBER	289806
MODEL CODE	NZM4-XS-L
EAN	4015082898069
PRODUCT LENGTH/DEPTH	250 mm
PRODUCT HEIGHT	165 mm
PRODUCT WIDTH	165 mm
PRODUCT WEIGHT	2.715 kg
COMPLIANCES	IEC UL/CSA RoHS conform
CERTIFICATIONS	CSA (File No. 22086) CSA (Class No. 1437-01) UL (File No. E140305) CSA-C22.2 No. 5-09 CSA certified UL (Category Control Number DIHS) CE marking UL listed UL489 IEC60947
GLOBAL CATALOG	289806



Product specification	S
USED WITH	NZM4(-4) N(S)4(-4)
FEATURES	Lockable Standard: black / gray Actuation of the switch on the control panel side wall Switch mounting on mounting plate
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL	Does not apply, since the

Resources	
BROCHURES	eaton-digital-nzm- brochure-br013003en-en- us.pdf
	eaton-feerum-the-whole- grain-solution-success- story-en-us.pdf
CATALOGS	eaton-digital-nzm-catalog- ca013003en-en-us.pdf
DRAWINGS	eaton-circuit-breaker- switch-nzm-mccb- dimensions-004.eps
INSTALLATION INSTRUCTIONS	eaton-circuit-breaker-side- wall-actuator-nzm4- il01219029z.pdf
INSTALLATION VIDEOS	The new digital NZM Range Introduction of the new
MCAD MODEL	digital circuit breaker NZM  DA-CD-nzm4 xs r l
	DA-CS-nzm4 xs r l
TECHNICAL DATA SHEETS	<u>eaton-nzm-technical-</u> <u>information-sheet</u>

IMPACT	entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	ls the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER- FREQUENCY ELECTRIC STRENGTH	ls the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
COLOR	Black
FITTED WITH:	Black and yellow lightning symbol NZMXV4 extension shaft  Door coupling rotary handle External warning plate/marking plate in German/English
FRAME	Padlock NZM4
ACTIVATION TYPE	Actuation on the left
ACTIVATION TYPE	
SUITABLE FOR	Power circuit breaker Switch disconnector
COVER/DOOR TYPE	Door interlock lockable on OFF with max. 3 padlocks Door interlock can also be modified in I position
ТҮРЕ	Accessory Main switch assembly kit for side panel mounting

External warning plate/designation label can be clipped on. For enhanced busbar tag shroud on the incomer side, please order IP2X protection against contact with a finger. Kit for use as

a main switch

IP66 **DEGREE OF PROTECTION** / NEMA ENCLOSURE TYPE 4X. 12

**SPECIAL FEATURES** 

**PROJECT NAME:** 

**PROJECT NUMBER:** 

PREPARED BY:

DATE:



**Eaton Corporation plc** 

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









