

2901528

<https://www.phoenixcontact.com/us/products/2901528>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Gateway for the connection of up to 32 INTERFACE system devices via Modbus/TCP to a higher-level controller. The INTERFACE system devices are connected to the Gateway via DIN rail connectors, the DIN rail connectors are provided.

Commercial data

Item number	2901528
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C477
Product key	CK7713
Catalog page	Page 20 (C-5-2019)
GTIN	4046356607087
Weight per piece (including packing)	201.1 g
Weight per piece (excluding packing)	184.3 g
Customs tariff number	85176200
Country of origin	DE

Technical data

Notes

Utilization restriction

EMC note	EMC: class A product, see manufacturer's declaration in the download area
----------	---

Product properties

Product type	Gateways/Proxies
Operating mode	100% operating factor

Insulation characteristics

Overvoltage category	III
Pollution degree	2

Electrical properties

Supply

Rated control circuit supply voltage U_S	24 V DC -20 % ... +25 %
Rated control supply current I_S	85 mA (plus load current of the outputs)
Protective circuit	Reverse polarity protection
	Surge protection

Input data

Digital

Number	8
Rated actuating voltage U_C	24 V DC ± 20 %
Rated actuating current I_C	3 mA
Protective circuit	Reverse polarity protection
	Surge protection

Output data

Digital: Switching outputs

Number	4
Residual voltage	1 V
Maximum switching voltage	23 V DC ($U_B - U_{resid.}$ of the output)
Max. switching current	500 mA
Protective circuit	Parallel protection against polarity reversal, pay attention to the fuse (Fusing with max. 8 A F-fuse)

Connection data

Supply

Connection method	Screw connection
-------------------	------------------

EM-MODBUS-GATEWAY-IFS - Data interface



2901528

<https://www.phoenixcontact.com/us/products/2901528>

Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm ² ... 2 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Programming connection

Connection method	S-PORT (socket)
Number of connections	1
Number of positions	12

INTERFACE system

Connection method	DIN rail bus connectors
Number of connections	1
Number of positions	5

Modbus/TCP

Connection method	RJ45
Number of connections	1

Interfaces

Data: Interface-System

Data rate	76800 Baud
Serial transmission speed	76.8 kbps
Connection method	DIN rail bus connectors
	S-PORT (male connector)

Data: Modbus/TCP

Serial transmission speed	10/100 Mbps
Connection method	RJ45 jack

Data: Network interface

Communication protocol	Modbus/TCP
Connection method	RJ45 jack
Number of connections	1
Transmission speed	10 Mbps
	100 Mbps

Data: Service interface

Communication protocol	INTERFACE-System
Connection method	S-PORT (socket)
Number of connections	1
Number of positions	12

Data: Device bus

Communication protocol	INTERFACE-System
Connection method	DIN rail bus connectors

2901528

<https://www.phoenixcontact.com/us/products/2901528>

Number of connections	1
Number of positions	5
Transmission speed	76.8 kbps

Dimensions

Width	22.5 mm
Height	107.8 mm
Depth	113.8 mm

Material specifications

Color	gray (RAL 7042)
Housing material	Polyamide PA non-reinforced

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-35 °C ... 50 °C
Ambient temperature (storage/transport)	-35 °C ... 80 °C

Approvals

UKCA

Certificate	UKCA-compliant
-------------	----------------

Standards and regulations


Standards/regulations	EN 50178
-----------------------	----------

Mounting


Mounting type	DIN rail mounting
Assembly instructions	in rows with zero spacing
Mounting position	any

Approvals


To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2901528>



EAC
Approval ID: RU C-DE.A*30.B.01082



UL Listed
Approval ID: FILE E 140324



cUL Listed
Approval ID: FILE E 140324

cULus Listed

Classifications

ECLASS

ECLASS-11.0	27242608
ECLASS-12.0	27242608
ECLASS-13.0	27242608

ETIM

ETIM 9.0	EC001604
----------	----------

UNSPSC

UNSPSC 21.0	32151600
-------------	----------

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com