

# RIF-4-RPT-LV-120AC/3X21 - Relay Module



2903277

<https://www.phoenixcontact.com/pc/products/2903277>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Preamsembled relay module with Push-in connection, consisting of: relay base, power contact relay, plug-in display/interference suppression module, and retaining bracket. Contact switching type: 3 changeover contacts. Input voltage: 120 V AC

## Product description

The pluggable electromechanical and solid-state relays in the RIFLINE complete product range and the base are recognized and approved in accordance with UL 508. The relevant approvals can be called up at the individual components in question.

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 2903277                        |
| Packing unit                         | 5 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Product key                          | CK652C                         |
| Catalog page                         | Page 351 (C-5-2019)            |
| GTIN                                 | 4046356731669                  |
| Weight per piece (including packing) | 210.4 g                        |
| Weight per piece (excluding packing) | 210.4 g                        |
| Customs tariff number                | 85364900                       |
| Country of origin                    | CN                             |

# RIF-4-RPT-LV-120AC/3X21 - Relay Module



2903277


<https://www.phoenixcontact.com/pc/products/2903277>

## Set consists of

### RIF-4-BPT/3X21 - Relay base

2900961

<https://www.phoenixcontact.com/pc/products/2900961>



Relay base RIF-4..., for high-power relay with 2 or 3 changeover contacts or 3 N/O contacts, Push-in connection, plug-in option for input/interference suppression modules, for mounting on NS 35/7,5

---

### REL-PR3-120AC/3X21 - Single relay

2903704

<https://www.phoenixcontact.com/pc/products/2903704>



Plug-in high-power relay with power contacts, 3 changeover contacts, coil voltage: 120 V AC

# RIF-4-RPT-LV-120AC/3X21 - Relay Module



2903277

<https://www.phoenixcontact.com/pc/products/2903277>

## RIF-LV-120-230 AC/110 DC - Plug-in module

2900944

<https://www.phoenixcontact.com/pc/products/2900944>



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with varistor and yellow LED, input voltage: 120 V AC... 230 V AC / 110 V DC  $\pm 20$  %

---

## RIF-RH-4 - Retaining bracket

2900956

<https://www.phoenixcontact.com/pc/products/2900956>



Relay retaining bracket, with holder for marking material, suitable for RIF-4 relay base, for high-power relay

# RIF-4-RPT-LV-120AC/3X21 - Relay Module



2903277

<https://www.phoenixcontact.com/pc/products/2903277>

## Technical data

### Product properties

|                         |                       |
|-------------------------|-----------------------|
| Product type            | Relay Module          |
| Product family          | RIFLINE complete      |
| Application             | Universal             |
| Operating mode          | 100% operating factor |
| Mechanical service life | approx. $10^7$ cycles |

### Insulation characteristics

|            |                  |
|------------|------------------|
| Insulation | Basic insulation |
|------------|------------------|

### Insulation characteristics

|                      |                  |
|----------------------|------------------|
| Insulation           | Basic insulation |
| Overvoltage category | III              |
| Pollution degree     | 2                |

### Electrical properties

|                                                 |                                                        |
|-------------------------------------------------|--------------------------------------------------------|
| Maximum power dissipation for nominal condition | 2.88 W                                                 |
| Test voltage (Winding/contact)                  | 2.5 kV <sub>rms</sub> (50 Hz, 1 min., winding/contact) |
| Test voltage (Contact/contact)                  | 2.5 kV <sub>rms</sub> (50 Hz, 1 min., contact/contact) |
| Rated insulation voltage                        | 250 V AC                                               |
| Rated surge voltage                             | 4 kV                                                   |

### Input data

#### Coil side

|                                           |                               |
|-------------------------------------------|-------------------------------|
| Nominal input voltage $U_N$               | 120 V AC                      |
| Input voltage range                       | 102 V AC ... 132 V AC (20 °C) |
| Input voltage range in reference to $U_N$ | see diagram                   |
| Mains frequency                           | 50/60 Hz                      |
| Drive and function                        | monostable                    |
| Drive (polarity)                          | polarized                     |
| Typical input current at $U_N$            | 24 mA                         |
| Typical response time                     | 5 ms ... 25 ms                |
| Typical release time range                | 5 ms ... 20 ms                |
| Coil voltage                              | 120 V AC                      |
| Protective circuit                        | Varistor                      |
| Operating voltage display                 | Yellow LED                    |

### Output data

#### Switching

|                        |                       |
|------------------------|-----------------------|
| Contact switching type | 3 changeover contacts |
| Type of switch contact | Single contact        |

# RIF-4-RPT-LV-120AC/3X21 - Relay Module



2903277

<https://www.phoenixcontact.com/pc/products/2903277>

|                                                |                                                |
|------------------------------------------------|------------------------------------------------|
| Contact material                               | AgNi                                           |
| Maximum switching voltage                      | 440 V AC                                       |
|                                                | 250 V DC                                       |
| Minimum switching voltage                      | 10 V (24 mA)                                   |
| Limiting continuous current                    | 8 A (see diagram)                              |
| Maximum inrush current                         | 50 A (20 ms, N/O contacts)                     |
| Min. switching current                         | 10 mA (24 V)                                   |
| Interrupting rating (ohmic load) max.          | 216 W (24 V DC)                                |
|                                                | 124 W (48 V DC)                                |
|                                                | 108 W (60 V DC)                                |
|                                                | 52 W (110 V DC)                                |
|                                                | 70 W (220 V DC)                                |
|                                                | 2250 VA (250 V AC)                             |
|                                                | 4000 VA (440 V AC)                             |
| 3-phase motor load                             | 1500 W                                         |
| Motor load according to UL 508                 | 1/3 HP, 120 V AC (single-phase AC motor)       |
|                                                | 1/2 HP, 240 V AC (single-phase AC motor)       |
|                                                | 1/2 HP, 240 V AC (three-phase induction motor) |
| Utilization category CB Scheme (IEC 60947-5-1) | AC15, 1.5 A/240 V (N/O contact)                |
|                                                | DC13, 2 A/240 V (N/O contact)                  |

## Connection data

### Coil side

|                                  |                                                                                                                   |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Connection method                | Push-in connection                                                                                                |
| Stripping length                 | 8 mm                                                                                                              |
| Conductor cross section rigid    | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                                                      |
| Conductor cross section flexible | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                                                      |
|                                  | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (Ferrule with plastic sleeve)                                        |
|                                  | 0.14 mm <sup>2</sup> ... 1 mm <sup>2</sup> (Ferrule with plastic sleeve, two conductors on double terminal block) |
| Conductor cross section AWG      | 26 ... 16 (solid)                                                                                                 |
|                                  | 26 ... 16 (flexible)                                                                                              |

### Contact side

|                                  |                                                                                                                   |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Connection method                | Push-in connection                                                                                                |
| Stripping length                 | 10 mm                                                                                                             |
| Conductor cross section rigid    | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                                                                      |
| Conductor cross section flexible | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                                                                      |
|                                  | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (Ferrule with plastic sleeve)                                        |
|                                  | 0.14 mm <sup>2</sup> ... 1 mm <sup>2</sup> (Ferrule with plastic sleeve, two conductors on double terminal block) |
| Conductor cross section AWG      | 26 ... 14 (solid)                                                                                                 |
|                                  | 26 ... 14 (flexible)                                                                                              |

## Dimensions

# RIF-4-RPT-LV-120AC/3X21 - Relay Module



2903277

<https://www.phoenixcontact.com/pc/products/2903277>

## Drill hole

|          |        |
|----------|--------|
| Diameter | 3.2 mm |
| Width    | 43 mm  |
| Height   | 111 mm |
| Depth    | 90 mm  |

## Material specifications

|                                        |                 |
|----------------------------------------|-----------------|
| Color                                  | gray (RAL 7042) |
| Flammability rating according to UL 94 | V2 (Housing)    |

## Environmental and real-life conditions

### Ambient conditions

|                                         |                   |
|-----------------------------------------|-------------------|
| Degree of protection (Relay base)       | IP20 (Relay base) |
| Degree of protection (Relay)            | RT I (Relay)      |
| Ambient temperature (operation)         | -40 °C ... 40 °C  |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C  |

## Approvals

### Corrosive gas test

|                |                            |
|----------------|----------------------------|
| Identification | ISA-S71.04. G3 Harsh Group |
|                | EN 60068-2-60              |

## Standards and regulations


|                       |               |
|-----------------------|---------------|
| Standards/regulations | IEC 60947-5-1 |
|-----------------------|---------------|

## Mounting

|                       |                           |
|-----------------------|---------------------------|
| Mounting type         | DIN rail mounting         |
| Assembly instructions | in rows with zero spacing |
| Mounting position     | any                       |


Drawings

Diagram



Service life reduction factor


Diagram



Contact derating




Diagram



Operating voltage range

Diagram




① AC, ohmic load

② DC, ohmic load


Interrupting rating

Diagram



① 250 V AC, Ohmic load

Electrical service life



Permissible humidity for operation and storage.


The maximum permissible ambient temperature as specified in the data sheet must be observed.

Area A: Ice buildup at ambient temperatures  $\leq 0^{\circ}\text{C}$  must be prevented

Area B: Condensation at ambient temperatures  $> 0^{\circ}\text{C}$  must be prevented

On 30 full days that are naturally distributed across an entire year, a humidity level of 95% is permissible at an ambient temperature  $\leq 25^{\circ}\text{C}$ .

Circuit diagram



# RIF-4-RPT-LV-120AC/3X21 - Relay Module



2903277

<https://www.phoenixcontact.com/pc/products/2903277>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/2903277>



**CSA**

Approval ID: 76787



**EAC**

Approval ID: TR\_TS\_D\_00573\_c



**DNV GL**

Approval ID: TAA000018V



**EAC**

Approval ID: RU\*C-DE.\*08.B.00010



**DNV GL**

Approval ID: TAA000018V

# RIF-4-RPT-LV-120AC/3X21 - Relay Module



2903277

<https://www.phoenixcontact.com/pc/products/2903277>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27371601 |
| ECLASS-12.0 | 27371601 |
| ECLASS-13.0 | 27371601 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001437 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39122300 |
|-------------|----------|

# RIF-4-RPT-LV-120AC/3X21 - Relay Module



2903277  
<https://www.phoenixcontact.com/pc/products/2903277>

## Environmental product compliance

|                                         |                                                                                                                                                                                                                                   |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS                                 |                                                                                                                                                                                                                                   |
| Fulfills EU RoHS substance requirements | Yes                                                                                                                                                                                                                               |
| Exemption                               | 7(a), 7(c)-I                                                                                                                                                                                                                      |
| China RoHS                              |                                                                                                                                                                                                                                   |
| Environment friendly use period (EFUP)  | EFUP-50                                                                                                                                                                                                                           |
|                                         | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |
| EU REACH SVHC                           |                                                                                                                                                                                                                                   |
| REACH candidate substance (CAS No.)     | Lead(CAS: 7439-92-1)                                                                                                                                                                                                              |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)