

# CABLE-FCN40/1X50/ 3,0M/IP/MEL - Cable



2903479

<https://www.phoenixcontact.com/pc/products/2903479>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Round cable set; controller: Mitsubishi Electric MELSEC L, MELSEC Q, Honeywell MasterLogic ML200; connection 1: Fujitsu connector (1x 40-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 3 m

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 2903479                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Product key                          | CK226M                         |
| Catalog page                         | Page 483 (C-5-2019)            |
| GTIN                                 | 4046356743303                  |
| Weight per piece (including packing) | 359.8 g                        |
| Weight per piece (excluding packing) | 101 g                          |
| Customs tariff number                | 85444290                       |
| Country of origin                    | DE                             |

# CABLE-FCN40/1X50/ 3,0M/IP/MEL - Cable



2903479

<https://www.phoenixcontact.com/pc/products/2903479>

## Technical data

### Product properties

|                        |              |
|------------------------|--------------|
| Product type           | System cable |
| Data management status |              |
| Article revision       | 03           |

### Environmental and real-life conditions

#### Ambient conditions

|                                              |                                                                                   |
|----------------------------------------------|-----------------------------------------------------------------------------------|
| Degree of protection                         | IP00                                                                              |
| Degree of protection (Installation location) | ≥ IP54 (Installation location)                                                    |
| Ambient temperature (operation)              | -40 °C ... 70 °C (fixed installation)<br>-10 °C ... 70 °C (flexible installation) |
| Ambient temperature (storage/transport)      | -40 °C ... 80 °C                                                                  |
| Altitude                                     | ≤ 2000 m                                                                          |

### Electrical properties

|                          |                                  |
|--------------------------|----------------------------------|
| Operating voltage (AC)   | ≤ 30 V AC                        |
| Operating voltage (DC)   | ≤ 60 V DC                        |
| Nominal operating mode   | 100% operating factor            |
| Current (Per path, 50°C) | ≤ 1 A (Uncoiled, see derating)   |
| Current (Per path, 70°C) | ≤ 0.6 A (Uncoiled, see derating) |

#### Supported controller MITSUBISHI MELSEC Q

|                   |         |
|-------------------|---------|
| Suitable I/O card | QX71    |
|                   | QX72    |
|                   | QX82    |
|                   | QX82-S1 |

#### Supported controller MITSUBISHI MELSEC L

|                   |        |
|-------------------|--------|
| Suitable I/O card | LX41C4 |
|                   | LX42C4 |

#### Supported controller HONEYWELL MasterLogic 200

|                   |           |
|-------------------|-----------|
| Suitable I/O card | 2MLI-D24A |
|                   | 2MLI-D28B |
|                   | 2MLF-SOEA |

### Cable/line

|                     |           |
|---------------------|-----------|
| Cable length        | 3 m       |
| 34X0.14 [PVC]       |           |
| UL AWM Style        | 2464/1061 |
| Number of positions | 34        |

# CABLE-FCN40/1X50/ 3,0M/IP/MEL - Cable



2903479

<https://www.phoenixcontact.com/pc/products/2903479>

|                                               |                                               |
|-----------------------------------------------|-----------------------------------------------|
| Shielded                                      | no                                            |
| Cable type                                    | 34X0.14 [PVC]                                 |
| Conductor type                                | Round cable set                               |
| Conductor structure signal line               | 7x 0.16 mm                                    |
| AWG signal line                               | 26                                            |
| Conductor cross section                       | 34x 0.14 mm <sup>2</sup>                      |
| Wire diameter incl. insulation                | 1 mm ±0.03 mm                                 |
| External cable diameter                       | 8.70 mm ±0.3 mm                               |
| Outer sheath, material                        | Semi-rigid PVC                                |
| External sheath, color                        | gray                                          |
| Conductor material                            | Tin-plated Cu litz wires                      |
| Cable resistance                              | ≤ 145 Ω/km (20 °C)                            |
| Insulation resistance                         | ≥ 20 MΩ*km (20 °C)                            |
| Smallest bending radius, fixed installation   | 72 mm                                         |
| Smallest bending radius, movable installation | 135 mm                                        |
| Halogen-free                                  | no                                            |
| Flame resistance                              | IEC 60332-1-2 (raw cable)                     |
|                                               | VDE 0842, Part 332-1-2 (raw cable)            |
|                                               | IEC 60332-3-22 (raw cable)                    |
|                                               | UL VW-1                                       |
|                                               | CSA FT-1                                      |
| Resistance to oil                             | can withstand occasional splashes (raw cable) |
| Cable type                                    | Cable for one module                          |

## Color code

|              |                                  |
|--------------|----------------------------------|
| black        | Fujitsu40 (B1) = IDC/FLK50 (11)  |
| brown        | Fujitsu40 (B2) = IDC/FLK50 (48)  |
| red          | Fujitsu40 (A5) = IDC/FLK50 (46)  |
| orange       | Fujitsu40 (B5) = IDC/FLK50 (22)  |
| yellow       | Fujitsu40 (A6) = IDC/FLK50 (45)  |
| green        | Fujitsu40 (B6) = IDC/FLK50 (21)  |
| blue         | Fujitsu40 (A7) = IDC/FLK50 (44)  |
| violet       | Fujitsu40 (B7) = IDC/FLK50 (20)  |
| gray         | Fujitsu40 (A8) = IDC/FLK50 (43)  |
| white        | Fujitsu40 (B8) = IDC/FLK50 (19)  |
| white-black  | Fujitsu40 (A9) = IDC/FLK50 (42)  |
| white-brown  | Fujitsu40 (B9) = IDC/FLK50 (18)  |
| white-red    | Fujitsu40 (A10) = IDC/FLK50 (41) |
| white-orange | Fujitsu40 (B10) = IDC/FLK50 (17) |
| white-yellow | Fujitsu40 (A11) = IDC/FLK50 (40) |
| white-green  | Fujitsu40 (B11) = IDC/FLK50 (16) |
| white-blue   | Fujitsu40 (A12) = IDC/FLK50 (39) |
| white-violet | Fujitsu40 (B12) = IDC/FLK50 (15) |
| white-gray   | Fujitsu40 (A13) = IDC/FLK50 (34) |

# CABLE-FCN40/1X50/ 3,0M/IP/MEL - Cable



2903479

<https://www.phoenixcontact.com/pc/products/2903479>

|              |                                  |
|--------------|----------------------------------|
| brown-black  | Fujitsu40 (B13) = IDC/FLK50 (10) |
| brown-red    | Fujitsu40 (A14) = IDC/FLK50 (33) |
| brown-orange | Fujitsu40 (B14) = IDC/FLK50 (9)  |
| brown-yellow | Fujitsu40 (A15) = IDC/FLK50 (32) |
| brown-green  | Fujitsu40 (B15) = IDC/FLK50 (8)  |
| brown-blue   | Fujitsu40 (A16) = IDC/FLK50 (31) |
| brown-violet | Fujitsu40 (B16) = IDC/FLK50 (7)  |
| brown-gray   | Fujitsu40 (A17) = IDC/FLK50 (30) |
| brown-white  | Fujitsu40 (B17) = IDC/FLK50 (6)  |
| green-black  | Fujitsu40 (A18) = IDC/FLK50 (29) |
| green-brown  | Fujitsu40 (B18) = IDC/FLK50 (5)  |
| green-red    | Fujitsu40 (A19) = IDC/FLK50 (28) |
| green-orange | Fujitsu40 (B19) = IDC/FLK50 (4)  |
| green-blue   | Fujitsu40 (A20) = IDC/FLK50 (27) |
| green-violet | Fujitsu40 (B20) = IDC/FLK50 (3)  |

## Connection data

### Connection 1

|                             |                   |
|-----------------------------|-------------------|
| Connection method           | Fujitsu connector |
| Type                        | FCN 367           |
| Number of connections       | 1                 |
| Number of positions         | 40                |
| Insertion/withdrawal cycles | > 50              |
| Pitch                       | 2.54 mm           |

### Connection 2


|                                  |                       |
|----------------------------------|-----------------------|
| Connection in acc. with standard | based on IEC 60603-13 |
| Connection method                | IDC/FLK socket strip  |
| Number of connections            | 1                     |
| Number of positions              | 50                    |
| Insertion/withdrawal cycles      | > 50                  |
| Pitch                            | 2.54 mm               |

## Notes

|                    |                                                                                                                                                                                                                                                                                |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Notes on operation | For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met. |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Drawings

Diagram



Maximum permissible current per path in uncoiled state

# CABLE-FCN40/1X50/ 3,0M/IP/MEL - Cable



2903479

<https://www.phoenixcontact.com/pc/products/2903479>

Connection diagram

| Fujitsu<br>FCN 40 | FLK 50 | Fujitsu<br>FCN 40 | FLK 50                          |
|-------------------|--------|-------------------|---------------------------------|
| PIN A1            |        | PIN B16           | PIN 7                           |
| PIN B1            | PIN 11 | PIN A17           | PIN 30                          |
| PIN A2            |        | PIN B17           | PIN 6                           |
| PIN B2            | PIN 48 | PIN A18           | PIN 29                          |
| PIN A3            |        | PIN B18           | PIN 5                           |
| PIN B3            |        | PIN A19           | PIN 28                          |
| PIN A4            |        | PIN B19           | PIN 4                           |
| PIN B4            |        | PIN A20           | PIN 27                          |
| PIN A5            | PIN 46 | PIN B20           | PIN 3                           |
| PIN B5            | PIN 22 |                   | PIN 12 <input type="checkbox"/> |
| PIN A6            | PIN 45 |                   | PIN 23 <input type="checkbox"/> |
| PIN B6            | PIN 21 |                   | PIN 24 <input type="checkbox"/> |
| PIN A7            | PIN 44 |                   | PIN 35 <input type="checkbox"/> |
| PIN B7            | PIN 20 |                   | PIN 36 <input type="checkbox"/> |
| PIN A8            | PIN 43 |                   | PIN 47 <input type="checkbox"/> |
| PIN B8            | PIN 19 |                   |                                 |
| PIN A9            | PIN 42 |                   |                                 |
| PIN B9            | PIN 18 |                   |                                 |
| PIN A10           | PIN 41 |                   |                                 |
| PIN B10           | PIN 17 |                   |                                 |
| PIN A11           | PIN 40 |                   |                                 |
| PIN B11           | PIN 16 |                   |                                 |
| PIN A12           | PIN 39 |                   |                                 |
| PIN B12           | PIN 15 |                   |                                 |
| PIN A13           | PIN 34 |                   |                                 |
| PIN B13           | PIN 10 |                   |                                 |
| PIN A14           | PIN 33 |                   |                                 |
| PIN B14           | PIN 9  |                   |                                 |
| PIN A15           | PIN 32 |                   |                                 |
| PIN B15           | PIN 8  |                   |                                 |
| PIN A16           | PIN 31 |                   |                                 |

# CABLE-FCN40/1X50/ 3,0M/IP/MEL - Cable



2903479

<https://www.phoenixcontact.com/pc/products/2903479>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/2903479>



**EAC**  
Approval ID: RU\*-DE.HB\*35.B00385

|                                                                                   |                                          |                       |                   |                             |
|-----------------------------------------------------------------------------------|------------------------------------------|-----------------------|-------------------|-----------------------------|
|  | <b>UL Listed</b><br>Approval ID: E238705 |                       |                   |                             |
|                                                                                   | Nominal voltage $U_N$                    | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                                                                   | 125 V                                    | 1 A                   | -                 | -                           |

|                                                                                   |                                           |                       |                   |                             |
|-----------------------------------------------------------------------------------|-------------------------------------------|-----------------------|-------------------|-----------------------------|
|  | <b>cUL Listed</b><br>Approval ID: E238705 |                       |                   |                             |
|                                                                                   | Nominal voltage $U_N$                     | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                                                                   | 125 V                                     | 1 A                   | -                 | -                           |

**cULus Listed**

# CABLE-FCN40/1X50/ 3,0M/IP/MEL - Cable



2903479

<https://www.phoenixcontact.com/pc/products/2903479>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27242220 |
| ECLASS-12.0 | 27242220 |
| ECLASS-13.0 | 27242220 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000237 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|



# CABLE-FCN40/1X50/ 3,0M/IP/MEL - Cable



2903479

<https://www.phoenixcontact.com/pc/products/2903479>

## Environmental product compliance

|                                         |      |
|-----------------------------------------|------|
| EU RoHS                                 |      |
| Fulfills EU RoHS substance requirements | Yes  |
| Exemption                               | 6(c) |

|                                        |                                                                                                                                                                                                                                   |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| China RoHS                             |                                                                                                                                                                                                                                   |
| Environment friendly use period (EFUP) | EFUP-50                                                                                                                                                                                                                           |
|                                        | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

|                                     |                                      |
|-------------------------------------|--------------------------------------|
| EU REACH SVHC                       |                                      |
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1)                 |
| SCIP                                | e663b69d-9c95-49d0-bd01-607510583aba |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)