

# CABLE-FCN40/1X50/ 8,0M/IP/MEL - Cable



2903482

<https://www.phoenixcontact.com/us/products/2903482>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Round cable set; controller: Mitsubishi Electric MELSEC L, MELSEC Q, Honeywell MasterLogic ML200; connection 1: Fujitsu connector (1x 40-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 8 m

## Commercial data

Item number	2903482
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	C421
Product key	CK2143
Catalog page	Page 483 (C-5-2019)
GTIN	4046356742917
Weight per piece (including packing)	333.33 g
Weight per piece (excluding packing)	333.33 g
Customs tariff number	85444290
Country of origin	DE

# CABLE-FCN40/1X50/ 8,0M/IP/MEL - Cable



2903482

<https://www.phoenixcontact.com/us/products/2903482>

## Technical data

### Product properties

Product type	System cable
Insulation characteristics	
Insulation	Functional insulation
Insulation characteristics: Air clearances and creepage distances	
Insulation	Functional insulation
Overvoltage category	II
Pollution degree	2

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP00
Degree of protection (Installation location)	≥ IP54 (Installation location)
Ambient temperature (operation)	-40 °C ... 70 °C (fixed installation) -10 °C ... 70 °C (flexible installation)
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m

### Electrical properties

Operating voltage (AC)	≤ 25 V AC
Operating voltage (DC)	≤ 60 V DC
Nominal operating mode	100% operating factor
Current (Per path, 50°C)	≤ 1 A
Current (Per path)	≤ 0.6 A

#### Air clearances and creepage distances

Rated insulation voltage	63 V
Rated surge voltage	0.6 kV

#### Supported controller MITSUBISHI MELSEC Q

Suitable I/O card	QX71
	QX72
	QX82
	QX82-S1

#### Supported controller MITSUBISHI MELSEC L

Suitable I/O card	LX41C4
	LX42C4

#### Supported controller HONEYWELL MasterLogic 200

Suitable I/O card	2MLI-D24A
	2MLI-D28B

# CABLE-FCN40/1X50/ 8,0M/IP/MEL - Cable



2903482

<https://www.phoenixcontact.com/us/products/2903482>

	2MLF-SOEA
--	-----------

## Cable/line

Cable length	8 m
--------------	-----

### 34X0.14 [PVC]

UL AWM Style	2464/1061
Number of positions	34
Shielded	no
Cable type	34X0.14 [PVC]
Conductor type	Round cable set
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Conductor cross section	34x 0.14 mm <sup>2</sup>
Wire diameter incl. insulation	1 mm ±0.03 mm
External cable diameter	8.70 mm ±0.3 mm
Outer sheath, material	Semi-rigid PVC
External sheath, color	gray
Conductor material	Tin-plated Cu litz wires
Cable resistance	≤ 145 Ω/km (20 °C)
Insulation resistance	≥ 20 MΩ*km (20 °C)
Smallest bending radius, fixed installation	72 mm
Smallest bending radius, movable installation	135 mm
Max. bending cycles	5000 (at a radius of ≥ 15x outside diameter)
Halogen-free	no
Flame resistance	IEC 60332-1-2 (raw cable)
	VDE 0842, Part 332-1-2 (raw cable)
	IEC 60332-3-22 (raw cable)
	UL VW-1
	CSA FT-1
Resistance to oil	can withstand occasional splashes (raw cable)
Fujitsu40 (A1)	() =
Fujitsu40 (B1)	IDC/FLK50 (11) = black
Fujitsu40 (A2)	() =
Fujitsu40 (B2)	IDC/FLK50 (48) = brown
Fujitsu40 (A3)	() =
Fujitsu40 (B3)	() =
Fujitsu40 (A4)	() =
Fujitsu40 (B4)	() =
Fujitsu40 (A5)	IDC/FLK50 (46) = red
Fujitsu40 (B5)	IDC/FLK50 (22) = orange
Fujitsu40 (A6)	IDC/FLK50 (45) = yellow
Fujitsu40 (B6)	IDC/FLK50 (21) = green
Fujitsu40 (A7)	IDC/FLK50 (44) = blue

# CABLE-FCN40/1X50/ 8,0M/IP/MEL - Cable



2903482

<https://www.phoenixcontact.com/us/products/2903482>

Fujitsu40 (B7)	IDC/FLK50 (20) = violet
Fujitsu40 (A8)	IDC/FLK50 (43) = gray
Fujitsu40 (B8)	IDC/FLK50 (19) = white
Fujitsu40 (A9)	IDC/FLK50 (42) = white-black
Fujitsu40 (B9)	IDC/FLK50 (18) = white-brown
Fujitsu40 (A10)	IDC/FLK50 (41) = white-red
Fujitsu40 (B10)	IDC/FLK50 (17) = white-orange
Fujitsu40 (A11)	IDC/FLK50 (40) = white-yellow
Fujitsu40 (B11)	IDC/FLK50 (16) = white-green
Fujitsu40 (A12)	IDC/FLK50 (39) = white-blue
Fujitsu40 (B12)	IDC/FLK50 (15) = white-violet
Fujitsu40 (A13)	IDC/FLK50 (34) = white-gray
Fujitsu40 (B13)	IDC/FLK50 (10) = brown-black
Fujitsu40 (A14)	IDC/FLK50 (33) = brown-red
Fujitsu40 (B14)	IDC/FLK50 (9) = brown-orange
Fujitsu40 (A15)	IDC/FLK50 (32) = brown-yellow
Fujitsu40 (B15)	IDC/FLK50 (8) = brown-green
Fujitsu40 (A16)	IDC/FLK50 (31) = brown-blue
Fujitsu40 (B16)	IDC/FLK50 (7) = brown-violet
Fujitsu40 (A17)	IDC/FLK50 (30) = brown-gray
Fujitsu40 (B17)	IDC/FLK50 (6) = brown-white
Fujitsu40 (A18)	IDC/FLK50 (29) = green-black
Fujitsu40 (B18)	IDC/FLK50 (5) = green-brown
Fujitsu40 (A19)	IDC/FLK50 (28) = green-red
Fujitsu40 (B19)	IDC/FLK50 (4) = green-orange
Fujitsu40 (A20)	IDC/FLK50 (27) = green-blue
Fujitsu40 (B20)	IDC/FLK50 (3) = green-violet
Cable type	Cable for one module

## Connection data

### Field level

Connection in acc. with standard	IEC 60603-13
Connection method	IDC/FLK socket strip
Number of connections	1
Number of positions	50
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

### Controller level

Connection method	Fujitsu connector
Number of connections	1
Number of positions	40
Insertion/withdrawal cycles	> 50

# CABLE-FCN40/1X50/ 8,0M/IP/MEL - Cable



2903482

<https://www.phoenixcontact.com/us/products/2903482>

## Standards and regulations

Air clearances and creepage distances

Standards/regulations	DIN EN 50178
-----------------------	--------------

## Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
---------	--

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)