

REL-PR2-120AC/2X21 - Single relay



2903700

<https://www.phoenixcontact.com/pc/products/2903700>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Plug-in high-power relay with power contacts, 2 changeover contacts, coil voltage: 120 V AC



Commercial data

Item number	2903700
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	CK6193
Catalog page	Page 312 (C-5-2019)
GTIN	4046356759120
Weight per piece (including packing)	82.6 g
Weight per piece (excluding packing)	82.6 g
Customs tariff number	85364900
Country of origin	PL

REL-PR2-120AC/2X21 - Single relay



2903700

<https://www.phoenixcontact.com/pc/products/2903700>

Technical data

Product properties

Product type	Single relay
Set comprises	2903280 RIF-4-RPT-LV-120AC/2X21
	2903290 RIF-4-RSC-LV-120AC/2X21
Operating mode	100% operating factor
Mechanical service life	approx. 10^7 cycles

Insulation characteristics

Insulation	Basic insulation
------------	------------------

Insulation characteristics

Insulation	Basic insulation
Overvoltage category	III
Pollution degree	3

Electrical properties

Service life electrical	see diagram
Maximum power dissipation for nominal condition	2.76 W
Test voltage (Winding/contact)	2.5 kV _{rms} (50 Hz, 1 min., winding/contact)
Test voltage (Contact/contact)	2.5 kV _{rms} (50 Hz, 1 min., contact/contact)
Test voltage (Changeover contact/changeover contact)	2.5 kV _{rms} (50 Hz, 1 min., changeover contact/changeover contact)
Rated insulation voltage	250 V AC
Rated surge voltage	4 kV

Input data

Coil side

Nominal input voltage U_N	120 V AC
Input voltage range	102 V AC ... 132 V AC (20 °C)
Mains frequency	50/60 Hz
Drive and function	monostable
Typical input current at U_N	23 mA
Typical response time	5 ms ... 25 ms (depending on phase relation)
Typical release time range	5 ms ... 20 ms (depending on phase relation)

Output data

Switching

Contact switching type	2 changeover contacts
Type of switch contact	Single contact
Contact material	AgNi
Maximum switching voltage	440 V AC
	250 V DC

REL-PR2-120AC/2X21 - Single relay



2903700

<https://www.phoenixcontact.com/pc/products/2903700>

Minimum switching voltage	10 V (At 24 mA)
Limiting continuous current	16 A
Maximum inrush current	50 A (20 ms, N/O contacts)
Min. switching current	10 mA (at 24 V)
Interrupting rating (ohmic load) max.	384 W (at 24 V DC)
	124 W (at 48 V DC)
	108 W (at 60 V DC)
	52 W (at 110 V DC)
	70 W (at 220 V DC)
	4000 VA (for 250 V AC)
Switching capacity	4000 VA (at 440 V AC)
	2 A (at 24 V, DC13)
	0.22 A (at 120 V, DC13)
	0.11 A (at 250 V, DC13)
	3 A (at 120 V, AC15)
Single-phase motor load	1.5 A (at 240 V, AC15)
	800 W (at 230 V, AC3)
Motor load according to UL 508	1/3 HP, 120 V AC (N/O contact)
	1/2 HP, 240 V AC (N/O contact)

Connection data

Connection method	Plug-in connection
-------------------	--------------------

Dimensions

Width	38.6 mm
Height	36.1 mm
Depth	45.5 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection	RT I
Ambient temperature (operation)	-40 °C ... 55 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

Approvals

Corrosive gas test

Identification	ISA-S71.04. G3 Harsh Group
	EN 60068-2-60

Standards and regulations

Standards/regulations	IEC 60664
	IEC 61810

Mounting

REL-PR2-120AC/2X21 - Single relay




2903700

<https://www.phoenixcontact.com/pc/products/2903700>

Mounting position	any
-------------------	-----

Drawings

Diagram



① AC, ohmic load

② DC, ohmic load

Interrupting rating


REL-PR2-120AC/2X21 - Single relay



2903700

<https://www.phoenixcontact.com/pc/products/2903700>


Diagram



① 250 V AC, Ohmic load

Electrical service life

Diagram



- ① Maximum continuous voltage at limiting continuous current = 16 A
- ② Minimum operate voltage
For pre-excitation with UN and limiting continuous current = 16 A


Operating voltage range

REL-PR2-120AC/2X21 - Single relay

2903700


<https://www.phoenixcontact.com/pc/products/2903700>

Diagram



Service life reduction factor

Circuit diagram



REL-PR2-120AC/2X21 - Single relay



2903700

<https://www.phoenixcontact.com/pc/products/2903700>

Classifications

ECLASS

ECLASS-11.0

27371601

ETIM

ETIM 8.0

EC001437

UNSPSC

UNSPSC 21.0

39122300

REL-PR2-120AC/2X21 - Single relay



2903700

<https://www.phoenixcontact.com/pc/products/2903700>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com