

VIP-2/PT/D15SUB/F - Interface module



2903780

<https://www.phoenixcontact.com/us/products/2903780>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE module, with push-in connection and D-SUB miniature socket strip, for mounting on NS 35 rails, 15-pos.

Commercial data

Item number	2903780
Packing unit	1 pc
Sales key	C423
Product key	CK2421
Catalog page	Page 554 (C-5-2019)
GTIN	4046356796552
Weight per piece (including packing)	111.9 g
Weight per piece (excluding packing)	110.2 g
Customs tariff number	85366990
Country of origin	US

VIP-2/PT/D15SUB/F - Interface module



2903780

<https://www.phoenixcontact.com/us/products/2903780>

Technical data

Product properties

Product type	Interface module
Product family	VARIOFACE Professional
Number of positions	15
No. of channels	15

Insulation characteristics

Overvoltage category	II
Pollution degree	2

Electrical properties

No. of channels	15
Nominal voltage U_N	25 V AC
	60 V DC
Max. current carrying capacity per branch	2 A
Rated surge voltage	1.2 kV

Connection data

Field level

Connection method	Push-in connection
Stripping length	8 mm
Conductor cross section rigid	0.14 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.14 mm ² ... 2.5 mm ²
Conductor cross section AWG	26 ... 14

Controller level

Connection method	D-SUB socket strip
Number of connections	1
Number of positions	15

Signaling

Status display	No
Status display present	No

Dimensions

Item dimensions

Width	46.9 mm
Height	72.1 mm
Depth	63 mm

Material specifications

Color	gray (RAL 7042)
-------	-----------------

VIP-2/PT/D15SUB/F - Interface module



2903780

<https://www.phoenixcontact.com/us/products/2903780>

Housing insulation material	Polyamide 6.6 green
-----------------------------	---------------------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Standards and regulations

Standards/regulations	IEC 60664
	DIN EN 50178

Mounting

Mounting type	DIN rail mounting
Mounting position	any

Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
---------	--

VIP-2/PT/D15SUB/F - Interface module


2903780

<https://www.phoenixcontact.com/us/products/2903780>



Drawings

Circuit diagram



VIP-2/PT/D15SUB/F - Interface module



2903780

<https://www.phoenixcontact.com/us/products/2903780>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2903780>

 CSA Approval ID: 2122203				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	105 V	2 A	26 - 14	-

 cUL Recognized Approval ID: FILE E 238705				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	125 V	2 A	26 - 14	-

 UL Recognized Approval ID: FILE E 238705				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	125 V	2 A	26 - 14	-

 CSAus Approval ID: 2122203				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	105 V	2 A	28 - 14	-

cULus Recognized				
-------------------------	--	--	--	--

cCSAus				
---------------	--	--	--	--

VIP-2/PT/D15SUB/F - Interface module



2903780

<https://www.phoenixcontact.com/us/products/2903780>

Classifications

ECLASS

ECLASS-11.0	27141152
ECLASS-13.0	27141152
ECLASS-12.0	27141152

ETIM

ETIM 9.0	EC002780
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

VIP-2/PT/D15SUB/F - Interface module



2903780
<https://www.phoenixcontact.com/us/products/2903780>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com