

VIP-3/PT/PDM-2/32 - Potential distributors



2903799

<https://www.phoenixcontact.com/pc/products/2903799>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE module, with two equipotential busbars (P1, P2) for potential distribution, for mounting on NS 35 rails. Module width: 67.3 mm

Commercial data

Item number	2903799
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	CK24D1
Catalog page	Page 579 (C-5-2019)
GTIN	4046356796736
Weight per piece (including packing)	180.7 g
Weight per piece (excluding packing)	180.7 g
Customs tariff number	85369010
Country of origin	US

Technical data

Notes

General	Polyamide PA non-reinforced
General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.

Product properties

Product type	Potential distributor
Product family	VARIOFACE Professional
Potential connections	Per potential (P1, P2) 2 power/16 distributor terminal blocks

Insulation characteristics

Overvoltage category	II
Pollution degree	2

Electrical properties

Nominal voltage U_N	250 V AC/DC
Max. current carrying capacity per branch	8 A
Max. total current of all branches	30 A (per potential)

Input data

Potential connections	Per potential (P1, P2) 2 power/16 distributor terminal blocks
-----------------------	---

Connection data

Service Entrance

Connection method	Push-in connection
Stripping length	15 mm
Number of connections	2
Conductor cross section rigid	0.25 mm ² ... 6 mm ²
Conductor cross section flexible	0.25 mm ² ... 4 mm ²
Conductor cross section AWG	24 ... 10

Distribution

Connection method	Push-in connection
Stripping length	8 mm
Number of connections	16
Number of positions	2
Conductor cross section rigid	0.14 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.14 mm ² ... 2.5 mm ²
Conductor cross section AWG	26 ... 14


VIP-3/PT/PDM-2/32 - Potential distributors



2903799

<https://www.phoenixcontact.com/pc/products/2903799>

Dimensions

Dimensional drawing	
Width	67.3 mm
Height	75.8 mm
Depth	63 mm

Material specifications

Color	gray (RAL 7042)
-------	-----------------

Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-20 °C ... 50 °C (NOTE: At maximum relative humidity < 90%.)
Ambient temperature (storage/transport)	-20 °C ... 70 °C (NOTE: At maximum relative humidity < 90%.)
Altitude	< 2000 m
Permissible humidity (operation)	90 %
Permissible humidity (storage/transport)	90 %

Standards and regulations

Standards/regulations	IEC 60664
	DIN EN 50178

Mounting

Mounting type	DIN rail mounting
Mounting position	any


VIP-3/PT/PDM-2/32 - Potential distributors

2903799


<https://www.phoenixcontact.com/pc/products/2903799>

Drawings

Circuit diagram



Dimensional drawing



VIP-3/PT/PDM-2/32 - Potential distributors



2903799

<https://www.phoenixcontact.com/pc/products/2903799>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/2903799>



CSA

Approval ID: 2122203



cUL Recognized

Approval ID: FILE E 238705

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Output	250 V	15 A	26 - 14	-
Input	250 V	15 A	24 - 8	-



UL Recognized

Approval ID: FILE E 238705

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Output	250 V	15 A	26 - 14	-
Input	250 V	15 A	24 - 8	-



EAC

Approval ID: RU C-DE.BL08.B.00511

cULus Recognized

VIP-3/PT/PDM-2/32 - Potential distributors



2903799

<https://www.phoenixcontact.com/pc/products/2903799>

Classifications

ECLASS

ECLASS-11.0	27400609
ECLASS-12.0	27400609
ECLASS-13.0	27400609

ETIM

ETIM 9.0	EC001894
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

VIP-3/PT/PDM-2/32 - Potential distributors



2903799

<https://www.phoenixcontact.com/pc/products/2903799>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com