

# VIP-2/PT/HD15SUB/F - Interface module



2904272

<https://www.phoenixcontact.com/pc/products/2904272>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

VARIOFACE module, with push-in connection and high density D-SUB miniature socket strip, for mounting on NS 35, no. of pos.: 15



## Commercial data

Item number	2904272
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	CK2451
Catalog page	Page 558 (C-5-2019)
GTIN	4046356814812
Weight per piece (including packing)	110 g
Weight per piece (excluding packing)	110 g
Customs tariff number	85366990
Country of origin	US

# VIP-2/PT/HD15SUB/F - Interface module



2904272

<https://www.phoenixcontact.com/pc/products/2904272>

## Technical data

### Product properties

Product type	Interface module
Product family	VARIOFACE Professional
Number of positions	15

### Insulation characteristics

Overvoltage category	II
Pollution degree	2

### Electrical properties

Nominal voltage $U_N$	25 V AC
	60 V DC
Max. current carrying capacity per branch	1 A
Rated surge voltage	1.2 kV

### Connection data

#### Field level

Connection in acc. with standard	IEC / EN
Connection method	Push-in connection
Stripping length	8 mm
Screw thread	M3
Number of positions	15
Conductor cross section rigid	0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section flexible	0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 12

#### Controller level

Connection method	High-density D-SUB socket strip
Number of connections	1
Number of positions	15

### Signaling

Status display	No
Status display present	No

### Dimensions

#### Item dimensions

Width	46.9 mm
Height	72.1 mm
Depth	46.6 mm

### Material specifications

# VIP-2/PT/HD15SUB/F - Interface module



2904272

<https://www.phoenixcontact.com/pc/products/2904272>

Color	gray (RAL 7042)
Housing insulation material	Polyamide 6.6 green

## Environmental and real-life conditions

### Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

## Standards and regulations

Standards/regulations	EN 50178
-----------------------	----------

## Mounting

Mounting type	DIN rail mounting
Mounting position	any

## Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
---------	--

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)