

ST-OV2- 24DC/ 60DC/1 - Solid-state relay



2905035

<https://www.phoenixcontact.com/us/products/2905035>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug-in power solid-state relay, with LED and protective circuit in input and output circuits, input: 24 V DC, output: 12 - 60 V DC/max. 1 A, can be plugged into basic terminal blocks

Commercial data

Item number	2905035
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	C460
Product key	CK61B2
Catalog page	Page 90 (IF-2005)
GTIN	4017918079178
Weight per piece (including packing)	25.74 g
Weight per piece (excluding packing)	25.04 g
Customs tariff number	85364190
Country of origin	DE

ST-OV2- 24DC/ 60DC/1 - Solid-state relay



2905035

<https://www.phoenixcontact.com/us/products/2905035>

Technical data

Product properties

Product type	Single solid-state relay
--------------	--------------------------

Electrical properties

Test voltage (Input/output)	2.5 kV AC (Input/output)
-----------------------------	--------------------------

Input data

Nominal input voltage U_N	24 V DC
Input voltage range in reference to U_N	0.8 ... 1.2
Input voltage range	19.2 V DC ... 28.8 V DC
Switching threshold "0" signal in reference to U_N	≤ 0.4
Switching threshold "1" signal in reference to U_N	≥ 0.8
Typical input current at U_N	7 mA
Typical response time	20 μ s
Typical turn-off time	200 μ s
Status display	Yellow LED
Protective circuit	Reverse polarity protection; Polarity protection diode Surge protection
Transmission frequency	500 Hz

Output data

Design of digital output	electronic
Output voltage range	12 V DC ... 60 V DC
Limiting continuous current	1 A (see derating curve)
Surge current	5 A ($t = 1$ s)
Peak offstate voltage	60 V DC (Collector-emitter reverse voltage)
Voltage drop at max. limiting continuous current	1.2 V
Output circuit	2-conductor, floating
Protective circuit	Reverse polarity protection; Polarity protection diode Surge protection

Dimensions

Width	14.6 mm
Height	33 mm
Depth	66.5 mm

Material specifications

Color	green (RAL 6021)
-------	------------------

Environmental and real-life conditions

Ambient conditions

ST-OV2- 24DC/ 60DC/1 - Solid-state relay



2905035

<https://www.phoenixcontact.com/us/products/2905035>

Ambient temperature (operation)	-20 °C ... 60 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Standards and regulations

Standards/regulations	DIN VDE 0110b, Gr. C for 250 V DC
	DIN VDE 0160 (in relevant parts)

Mounting

Mounting position	any
-------------------	-----

ST-OV2- 24DC/ 60DC/1 - Solid-state relay




2905035

<https://www.phoenixcontact.com/us/products/2905035>

Drawings

Circuit diagram




ST-OV2- 24DC/ 60DC/1 - Solid-state relay

2905035

<https://www.phoenixcontact.com/us/products/2905035>



Diagram



- ① In rows with zero spacing
- ② stand-alone device


ST-OV2- 24DC/ 60DC/1 - Solid-state relay

2905035

<https://www.phoenixcontact.com/us/products/2905035>



Circuit diagram



ST-OV2- 24DC/ 60DC/1 - Solid-state relay



2905035

<https://www.phoenixcontact.com/us/products/2905035>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2905035>



EAC

Approval ID: TR_TS_D_00573_c



EAC

Approval ID: RU*C-DE.*08.B.00010

ST-OV2- 24DC/ 60DC/1 - Solid-state relay



2905035

<https://www.phoenixcontact.com/us/products/2905035>

Classifications

ECLASS

ECLASS-11.0	27371604
ECLASS-12.0	27371604
ECLASS-13.0	27371604

ETIM

ETIM 8.0	EC001504
----------	----------

UNSPSC

UNSPSC 21.0	39122300
-------------	----------

ST-OV2- 24DC/ 60DC/1 - Solid-state relay



2905035

<https://www.phoenixcontact.com/us/products/2905035>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
	Hexahydromethylphthalic anhydride
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com