

ME B-22,5 MSTBO GN - Filler plug



2907156
<https://www.phoenixcontact.com/pc/products/2907156>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DIN rail housing, Filler plug for unoccupied terminal points (MSTBO), width: 20 mm, height: 19.05 mm, depth: 12.3 mm, color: green (similar RAL 6021)

Your advantages

- Easy, tool-free mounting
- Flammability rating V0 in accordance with UL 94

Commercial data

Item number	2907156
Packing unit	10 pc
Minimum order quantity	10 pc
Product key	ACHAAZ
Catalog page	Page 675 (C-1-2013)
GTIN	4017918126643
Weight per piece (including packing)	1.26 g
Weight per piece (excluding packing)	1.1 g
Customs tariff number	39269097
Country of origin	DE

ME B-22,5 MSTBO GN - Filler plug



2907156

<https://www.phoenixcontact.com/pc/products/2907156>

Technical data

Product properties

Product type	Filler plug
Product family	ME B..MSTBO
Housing series	ME
Type	Filler plug for unoccupied terminal points (MSTBO)
Housing type	DIN rail housing
Ventilation openings present	no

Dimensions

Width	20 mm
Height	19.05 mm
Depth	12.3 mm

Material specifications

Color (Housing)	green (RAL 6021)
Flammability rating according to UL 94	V0
CTI according to IEC 60112	600
Housing material	Polyamide
Surface characteristics	untreated

Environmental and real-life conditions

Vibration test

Specification	IEC 60068-2-6:2007-12
Frequency	10 - 150 - 10 Hz
Sweep speed	1 octave/min
Amplitude	0.15 mm (10 Hz ... 58.1 Hz)
Acceleration	2g (58.1 Hz ... 150 Hz)
Test duration per axis	2.5 h
Test directions	X-, Y- and Z-axis

Glow-wire test

Specification	IEC 60695-2-11:2014-02
Temperature	850 °C
Time of exposure	30 s

Thermal stability / ball thrust test

Specification	IEC 60695-10-2:2014-02
Temperature	125 °C
Test duration	1 h
Force	20 N

Mechanical strength / tumbling barrel

ME B-22,5 MSTBO GN - Filler plug



2907156

<https://www.phoenixcontact.com/pc/products/2907156>

Specification	IEC 60998-1:2002-12
Height of fall	50 cm
Frequency	10

Shocks

Specification	IEC 60068-2-27:2008-02
Pulse shape	Half-sine
Acceleration	15g
Shock duration	11 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)

Degree of protection (IP code)

Specification	IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08
---------------	---

Ambient conditions

Max. IP code to attain	IP20
Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport)	-40 °C ... 55 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Relative humidity (storage/transport)	80 %

Mounting

Mounting type	Latching
---------------	----------

ME B-22,5 MSTBO GN - Filler plug



2907156

<https://www.phoenixcontact.com/pc/products/2907156>

Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/2907156>



UL Recognized

Approval ID: FILE E 240868

ME B-22,5 MSTBO GN - Filler plug



2907156

<https://www.phoenixcontact.com/pc/products/2907156>

Classifications

ECLASS

ECLASS-11.0	27182702
ECLASS-13.0	27190605

ETIM

ETIM 9.0	EC001031
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

ME B-22,5 MSTBO GN - Filler plug

2907156

<https://www.phoenixcontact.com/pc/products/2907156>



Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com