

# TMC 83B 08A - Miniature Circuit Breaker



2907547

<https://www.phoenixcontact.com/us/products/2907547>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Miniature Circuit Breaker, number of positions: 3, cross section: 1 mm<sup>2</sup>- 35 mm<sup>2</sup>, AWG: 18 - 2, mounting type: DIN rail: 35 mm

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 2907547                        |
| Packing unit                         | 48 pc                          |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | CL08                           |
| Product key                          | CLA125                         |
| GTIN                                 | 4055626216133                  |
| Weight per piece (including packing) | 222.222 g                      |
| Weight per piece (excluding packing) | 222.222 g                      |
| Customs tariff number                | 85362010                       |
| Country of origin                    | CN                             |

# TMC 83B 08A - Miniature Circuit Breaker



2907547  
<https://www.phoenixcontact.com/us/products/2907547>

## Technical data

### Product properties

|                         |                                        |
|-------------------------|----------------------------------------|
| Product type            | Thermomagnetic device circuit breakers |
| Product family          | TMC 8                                  |
| Type                    | DIN rail module, one-piece             |
| Number of positions     | 3                                      |
| Mechanical service life | 20000                                  |

### Data management status

|                  |    |
|------------------|----|
| Article revision | 04 |
|------------------|----|

### Electrical properties

|                         |      |
|-------------------------|------|
| Service life electrical | 6000 |
|-------------------------|------|


### General

|                                                 |                           |
|-------------------------------------------------|---------------------------|
| Operating voltage                               | 240 V AC (277/480Y, 240D) |
| Rated current $I_N$                             | 8 A                       |
| Tripping method                                 | TM (thermomagnetic)       |
| Rated short-circuit switching capacity $I_{cn}$ | 10 kA (IC)                |
| Fuse                                            | B                         |

### Connection data

|                                       |                                          |
|---------------------------------------|------------------------------------------|
| Conductor cross section rigid         | 1 mm <sup>2</sup> ... 35 mm <sup>2</sup> |
| Cross section AWG                     | 18 ... 2 (converted acc. to IEC)         |
| Conductor cross section flexible      | 1 mm <sup>2</sup> ... 35 mm <sup>2</sup> |
| Connection method                     | Screw connection                         |
| Tightening torque, min                | 2 Nm                                     |
| Stripping length                      | 11 mm ... 12 mm                          |
| Conductor cross section flexible max. | 35 mm <sup>2</sup>                       |
| Conductor cross section, rigid max.   | 35 mm <sup>2</sup>                       |

### Dimensions

|                     |                                                                                      |
|---------------------|--------------------------------------------------------------------------------------|
| Dimensional drawing |  |
| Width               | 52.9 mm                                                                              |
| Height              | 116 mm                                                                               |
| Depth               | 76.6 mm (incl. DIN rail 7.5 mm)                                                      |

### Material specifications

|       |                       |
|-------|-----------------------|
| Color | light gray (RAL 7035) |
|       | gray (RAL 7042)       |

# TMC 83B 08A - Miniature Circuit Breaker



2907547

<https://www.phoenixcontact.com/us/products/2907547>

## Environmental and real-life conditions

### Ambient conditions

|                                 |                                                                 |
|---------------------------------|-----------------------------------------------------------------|
| Ambient temperature (operation) | -35 °C ... 70 °C                                                |
| Humidity test                   | 48 h, 95% RH, 40°C (IEC 60068-2-78)                             |
| Shock (operation)               | 30g (11 ms) (IEC 60068-2-11)                                    |
| Vibration (operation)           | ±0.38 mm (10-57 Hz), 5g (57...500 Hz) (IEC 60068-2-6, Fc, sine) |

## Standards and regulations

|                          |             |
|--------------------------|-------------|
| Standards/specifications | UL 489      |
| Standards/specifications | IEC 60947-2 |

## Mounting

|               |                 |
|---------------|-----------------|
| Mounting type | DIN rail: 35 mm |
|---------------|-----------------|

# TMC 83B 08A - Miniature Circuit Breaker


2907547

<https://www.phoenixcontact.com/us/products/2907547>



## Drawings

Diagram




# TMC 83B 08A - Miniature Circuit Breaker

2907547

<https://www.phoenixcontact.com/us/products/2907547>



Dimensional drawing



# TMC 83B 08A - Miniature Circuit Breaker



2907547

<https://www.phoenixcontact.com/us/products/2907547>

## Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2907547>



**UL Listed**

Approval ID: FILE E 320373



**cUL Listed**

Approval ID: FILE E 320373



**TÜV Rheinland**

Approval ID: R 50531587

**cULus Listed**

# TMC 83B 08A - Miniature Circuit Breaker



2907547

<https://www.phoenixcontact.com/us/products/2907547>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141116 |
| ECLASS-12.0 | 27141116 |
| ECLASS-13.0 | 27140401 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC003538 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121410 |
|-------------|----------|

# TMC 83B 08A - Miniature Circuit Breaker



2907547  
<https://www.phoenixcontact.com/us/products/2907547>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)