

TMC 82C 15A - Thermomagnetic device circuit breaker



2907594

<https://www.phoenixcontact.com/nz/products/2907594>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Thermomagnetic device circuit breaker, number of positions: 2, cross section: 1 mm²- 35 mm², AWG: 18 - 2, fuse type: Automatic device, mounting type: DIN rail: 35 mm

Commercial data

Item number	2907594
Packing unit	6 pc
Minimum order quantity	6 pc
Sales key	CLA125
Product key	CLA125
GTIN	4055626215532
Weight per piece (including packing)	268.133 g
Weight per piece (excluding packing)	262 g
Country of origin	CN

TMC 82C 15A - Thermomagnetic device circuit breaker



2907594

<https://www.phoenixcontact.com/nz/products/2907594>

Technical data

Product properties

Type	DIN rail module, one-piece
Product type	Thermomagnetic device circuit breakers
Product family	TMC 8
Number of positions	2
Mechanical service life	20000

Electrical properties

Fuse type	Automatic device
Service life electrical	6000


General

Operating voltage	240 V AC (277/480Y, 240D)
	125 V DC (two poles in series)
Rated current I_N	15 A
Tripping method	TM (thermomagnetic)
Rated short-circuit switching capacity I_{cn}	10 kA (IC)
Fuse	C

Connection data

Conductor cross section rigid	1 mm ² ... 35 mm ²
Cross section AWG	18 ... 2 (converted acc. to IEC)
Conductor cross section flexible	1 mm ² ... 35 mm ²
Connection method	Screw connection
Tightening torque, min	2 Nm
Stripping length	11 mm ... 12 mm
Conductor cross section flexible max.	35 mm ²
Conductor cross section, rigid max.	35 mm ²

Dimensions

Dimensional drawing	
Width	35.3 mm
Height	116 mm
Depth	76.6 mm (incl. DIN rail 7.5 mm)

Material specifications

Color	light grey (RAL 7035)
	gray (RAL 7042)

TMC 82C 15A - Thermomagnetic device circuit breaker



2907594

<https://www.phoenixcontact.com/nz/products/2907594>

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-35 °C ... 70 °C
Humidity test	48 h, 95% RH, 40°C (IEC 60068-2-78)
Shock (operation)	30g (11 ms) (IEC 60068-2-11)
Vibration (operation)	±0.38 mm (10-57 Hz), 5g (57...500 Hz) (IEC 60068-2-6, Fc, sine)

Standards and regulations

Standards/specifications	UL 489
	IEC 60947-2

Mounting

Mounting type	DIN rail: 35 mm
---------------	-----------------

TMC 82C 15A - Thermomagnetic device circuit breaker



2907594

<https://www.phoenixcontact.com/nz/products/2907594>

Drawings



Diagram



TMC 82C 15A - Thermomagnetic device circuit breaker



2907594

<https://www.phoenixcontact.com/nz/products/2907594>

Approvals

📄 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/nz/products/2907594>



UL Listed

Approval ID: FILE E 320373



cUL Listed

Approval ID: FILE E 320373



TÜV Rheinland

Approval ID: R 50531587

cULus Listed

TMC 82C 15A - Thermomagnetic device circuit breaker



2907594

<https://www.phoenixcontact.com/nz/products/2907594>

Classifications

ECLASS

ECLASS-11.0	27141116
ECLASS-12.0	27141116
ECLASS-13.0	27140401

ETIM

ETIM 8.0	EC000899
----------	----------

UNSPSC

UNSPSC 21.0	39121410
-------------	----------

TMC 82C 15A - Thermomagnetic device circuit breaker



2907594

<https://www.phoenixcontact.com/nz/products/2907594>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Unit 15C, 906-930 Great South Road, Penrose
Auckland 1061
0508 474 636
sales@phoenixcontact.co.nz