

# TMC 82C 40A - Miniature Circuit Breaker



2907602

<https://www.phoenixcontact.com/au/products/2907602>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Miniature Circuit Breaker, number of positions: 2, cross section: 1 mm<sup>2</sup>- 35 mm<sup>2</sup>, AWG: 18 - 2, mounting type: DIN rail: 35 mm

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 2907602       |
| Packing unit                         | 6 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | CLA125        |
| Product key                          | CLA125        |
| GTIN                                 | 4055626215464 |
| Weight per piece (including packing) | 273 g         |
| Weight per piece (excluding packing) | 268 g         |
| Customs tariff number                | 85362010      |
| Country of origin                    | CN            |

# TMC 82C 40A - Miniature Circuit Breaker



2907602

<https://www.phoenixcontact.com/au/products/2907602>

## Technical data

### Product properties

|                         |                                        |
|-------------------------|----------------------------------------|
| Product type            | Thermomagnetic device circuit breakers |
| Product family          | TMC 8                                  |
| Type                    | DIN rail module, one-piece             |
| Number of positions     | 2                                      |
| Mechanical service life | 20000                                  |

### Electrical properties

|                         |      |
|-------------------------|------|
| Service life electrical | 6000 |
|-------------------------|------|


#### General

|                                                 |                                |
|-------------------------------------------------|--------------------------------|
| Operating voltage                               | 240 V AC (120/240S, 240D)      |
|                                                 | 125 V DC (two poles in series) |
| Rated current $I_N$                             | 40 A                           |
| Tripping method                                 | TM (thermomagnetic)            |
| Rated short-circuit switching capacity $I_{cn}$ | 10 kA (IC)                     |
| Fuse                                            | C                              |

### Connection data

|                                       |                                          |
|---------------------------------------|------------------------------------------|
| Conductor cross section rigid         | 1 mm <sup>2</sup> ... 35 mm <sup>2</sup> |
| Cross section AWG                     | 18 ... 2 (converted acc. to IEC)         |
| Conductor cross section flexible      | 1 mm <sup>2</sup> ... 35 mm <sup>2</sup> |
| Connection method                     | Screw connection                         |
| Tightening torque, min                | 2 Nm                                     |
| Stripping length                      | 11 mm ... 12 mm                          |
| Conductor cross section flexible max. | 35 mm <sup>2</sup>                       |
| Conductor cross section, rigid max.   | 35 mm <sup>2</sup>                       |

### Dimensions

|                     |                                                                                      |
|---------------------|--------------------------------------------------------------------------------------|
| Dimensional drawing |  |
| Width               | 35.3 mm                                                                              |
| Height              | 116 mm                                                                               |
| Depth               | 76.6 mm (incl. DIN rail 7.5 mm)                                                      |

### Material specifications

|       |                       |
|-------|-----------------------|
| Color | light grey (RAL 7035) |
|       | gray (RAL 7042)       |

### Environmental and real-life conditions

# TMC 82C 40A - Miniature Circuit Breaker



2907602

<https://www.phoenixcontact.com/au/products/2907602>

## Ambient conditions

|                                 |                                                                 |
|---------------------------------|-----------------------------------------------------------------|
| Ambient temperature (operation) | -35 °C ... 70 °C                                                |
| Humidity test                   | 48 h, 95% RH, 40°C (IEC 60068-2-78)                             |
| Shock (operation)               | 30g (11 ms) (IEC 60068-2-11)                                    |
| Vibration (operation)           | ±0.38 mm (10-57 Hz), 5g (57...500 Hz) (IEC 60068-2-6, Fc, sine) |

## Standards and regulations

|                          |             |
|--------------------------|-------------|
| Standards/specifications | UL 489      |
|                          | IEC 60947-2 |

## Mounting

|               |                 |
|---------------|-----------------|
| Mounting type | DIN rail: 35 mm |
|---------------|-----------------|

# TMC 82C 40A - Miniature Circuit Breaker

2907602

<https://www.phoenixcontact.com/au/products/2907602>



## Drawings



Diagram



# TMC 82C 40A - Miniature Circuit Breaker



2907602

<https://www.phoenixcontact.com/au/products/2907602>

## Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/au/products/2907602>



**UL Listed**

Approval ID: FILE E 320373



**cUL Listed**

Approval ID: FILE E 320373



**TÜV Rheinland**

Approval ID: R 50531587

**cULus Listed**

# TMC 82C 40A - Miniature Circuit Breaker



2907602

<https://www.phoenixcontact.com/au/products/2907602>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141116 |
| ECLASS-12.0 | 27141116 |
| ECLASS-13.0 | 27140401 |

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121410 |
|-------------|----------|

# TMC 82C 40A - Miniature Circuit Breaker



2907602  
<https://www.phoenixcontact.com/au/products/2907602>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd  
Unit 7, 2-8 South Street  
Rydalmere NSW 2116  
1300 786 411  
[customerservice@phoenixcontact.com.au](mailto:customerservice@phoenixcontact.com.au)