

## Cable - CAB-TE MR24F/OE/24/TP/S/ 5M - 2909685

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Assembled shielded round cable; controller: Bailey INFI 90; connection 1: Twisted pair (24-position) (The wires are marked and fitted with ferrules); connection 2: Miniature rectangular (MR) connector (1x 24-position); cable length: 5 m

### Your advantages

- Individual wire marking: 1, 2, 3, 4, etc.
- Twisted-pair wires fitted with ferrules
- Open end at one end
- MR connector at one end
- 1:1 connection

### Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4055626682280
Weight per Piece (excluding packing)	720.000 g
Country of origin	United States

### Technical data

#### Dimensions

Length	5 m
--------	-----

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

#### General

## Cable - CAB-TE MR24F/OE/24/TP/S/ 5M - 2909685

### Technical data

#### General

Max. permissible operating voltage	125 V AC
	125 V DC
Max. current carrying capacity per path	1 A

#### Connection data

Connection name	Field level
Connection method	Miniature rectangular (MR) connector
Number of connections	1
Number of positions	24

#### Connection data 2

Connection name	Controller level
Connection method	Twisted pair
Number of positions	24
Note	The wires are marked and fitted with ferrules

#### Supported controller

Controller	Bailey INFI 90
------------	----------------

#### Color code

Connector 1 = connector 2 (optional) = wire color	MR24 (1) = white-blue
	MR24 (2) = blue-white
	MR24 (3) = white-orange
	MR24 (4) = orange-white
	MR24 (5) = white-green
	MR24 (6) = green-white
	MR24 (7) = white-brown
	MR24 (8) = brown-white
	MR24 (9) = white-grey
	MR24 (10) = grey-white
	MR24 (11) = red-blue
	MR24 (12) = blue-red
	MR24 (13) = red-orange
	MR24 (14) = orange-red
	MR24 (15) = red-green
	MR24 (16) = green-red
	MR24 (17) = red-brown
	MR24 (18) = brown-red
	MR24 (19) = red-grey

## Cable - CAB-TE MR24F/OE/24/TP/S/ 5M - 2909685

### Technical data

#### Color code

	MR24 (20) = grey-red
	MR24 (21) = black-blue
	MR24 (22) = blue-black
	MR24 (23) = black-orange
	MR24 (24) = orange-black

### Classifications

#### eCl@ss

eCl@ss 10.0.1	27242220
eCl@ss 11.0	27242220
eCl@ss 9.0	27242220

### Accessories

#### Accessories

#### Marker carrier cable

Cable marker carrier - KME - 0807083



Cable marker carrier, white, unlabeled, mounting type: Assembly with cable binders, cable diameter: > 5 mm, lettering field size: 20 mm x 8 mm