

CAB-TE MR36F/OE/24/S/ 3M - Cable



2909732

<https://www.phoenixcontact.com/us/products/2909732>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Migration cable for Bailey INFI 90 to modern control platforms. Open-end cable for universal configurations, 36 conductors, 3.0 m

Your advantages

- Individual wire marking: 1, 2, 3, 4, etc.
- Individual wires fitted with ferrules
- Open end at one end
- MR connector at one end
- 1:1 connection

Commercial data

| | |
|--------------------------------------|--------------------------------|
| Item number | 2909732 |
| Packing unit | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | C429 |
| Product key | CK2BL4 |
| GTIN | 4055626682570 |
| Weight per piece (including packing) | 0.01 g |
| Weight per piece (excluding packing) | 0.01 g |
| Customs tariff number | 85444290 |
| Country of origin | US |

CAB-TE MR36F/OE/24/S/ 3M - Cable



2909732

<https://www.phoenixcontact.com/us/products/2909732>

Technical data

Product properties

| | |
|--------------|--------------|
| Product type | System cable |
|--------------|--------------|

Environmental and real-life conditions

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

Electrical properties

| | |
|------------------------|------------|
| Operating voltage (AC) | ≤ 125 V AC |
| Operating voltage (DC) | ≤ 125 V DC |
| Current (Per path) | ≤ 1 A |

Cable/line

| | |
|-------------------------|--------------------------------|
| Cable length | 3 m |
| Number of positions | 37 |
| Shielded | yes |
| Conductor type | Assembled shielded round cable |
| AWG signal line | 24 |
| Conductor cross section | 37x 0.25 mm ² |
| External cable diameter | 10.50 mm |
| Halogen-free | no |

Color code

| | |
|--------------|-----------------|
| black | MR36F (1) = () |
| white | MR36F (2) = () |
| red | MR36F (3) = () |
| green | MR36F (4) = () |
| orange | MR36F (5) = () |
| blue | MR36F (6) = () |
| white-black | MR36F (7) = () |
| red-black | MR36F (8) = () |
| green-black | MR36F (9) = () |
| orange-black | MR36F (10) = () |
| blue-black | MR36F (11) = () |
| black-white | MR36F (12) = () |
| red-white | MR36F (13) = () |
| green-white | MR36F (14) = () |
| blue-white | MR36F (15) = () |
| black-red | MR36F (16) = () |
| white-red | MR36F (17) = () |

CAB-TE MR36F/OE/24/S/ 3M - Cable



2909732

<https://www.phoenixcontact.com/us/products/2909732>

| | |
|--------------|-----------------|
| orange-red | MR36F (18) = () |
| blue-red | MR36F (19) = () |
| red-green | MR36F (20) = () |
| orange-green | MR36F (21) = () |
| black-white | MR36F (22) = () |
| white-black | MR36F (23) = () |
| red-black | MR36F (24) = () |
| green-black | MR36F (25) = () |
| orange-black | MR36F (26) = () |
| blue-black | MR36F (27) = () |
| black-red | MR36F (28) = () |
| white-red | MR36F (29) = () |
| red-black | MR36F (30) = () |
| green-black | MR36F (31) = () |
| orange-black | MR36F (32) = () |
| blue-white | MR36F (33) = () |
| black-white | MR36F (34) = () |
| white-red | MR36F (35) = () |
| orange-white | MR36F (36) = () |

Connection data

Field level

| | |
|-----------------------|--------------------------------------|
| Connection method | Miniature rectangular (MR) connector |
| Number of connections | 1 |
| Number of positions | 36 |

Controller level

| | |
|---------------------|--|
| Connection method | Single wires |
| Number of positions | 37 |
| Note | The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end. |

Notes

| | |
|--------------------|--|
| Notes on operation | For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met. |
|--------------------|--|

CAB-TE MR36F/OE/24/S/ 3M - Cable



2909732

<https://www.phoenixcontact.com/us/products/2909732>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2909732>



EAC

Approval ID: RU*-DE.HB*35.B00385

CAB-TE MR36F/OE/24/S/ 3M - Cable



2909732

<https://www.phoenixcontact.com/us/products/2909732>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27242220 |
| ECLASS-12.0 | 27242220 |
| ECLASS-13.0 | 27242220 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC000237 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

CAB-TE MR36F/OE/24/S/ 3M - Cable



2909732

<https://www.phoenixcontact.com/us/products/2909732>

Environmental product compliance

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com