WP 04T - Web panel

2913632

https://www.phoenixcontact.com/us/products/2913632



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Web panel with 8.9 cm (3.5") graphics-capable TFT display, 320 x 240 pixels, 1x Ethernet, 2x USB, and integrated micro browser

Your advantages

- Energy efficient due to LED backlighting
- · Easy device replacement the visualization project is saved on the PLC (web server)
- · Micro browser (WebVisit client) integrated as standard in all devices
- Display available in sizes from 8.9 cm (3.5") to 38.1 cm (15")
- Short startup time
- · Easy installation, low installation depth, and compact design
- · Low maintenance costs projects are only adapted once

Commercial data

Item number	2913632
Packing unit	1 pc
Sales key	DR17
Product key	DRCABD
Catalog page	Page 470 (C-6-2019)
GTIN	4046356460422
Weight per piece (including packing)	494.4 g
Weight per piece (excluding packing)	494.4 g
Customs tariff number	84714100
Country of origin	DE

WP 04T - Web panel

2913632

https://www.phoenixcontact.com/us/products/2913632



Technical data

Product properties

Product type	Operator panel
Computer data	
Processor	Arm9™, 200 MHz
Operating system	Windows [®] CE 5.0
RAM	64 MB SDRAM
Data storage system	Flash, 32 MB
Display	
Display type	8,9 cm / 3,5"-TFT
Screen resolution	320 x 240 Pixel(s) (QVGA)
Touch technology	analog resistive (polyester)
Display lighting type	LED
Brightness	350 cd/m², typical (adjustable)
MTBF	40000 h
Color spectrum	65536 colors
Software	
User software	MicroBrowser
Interfaces	
Interfaces	2x USB Host 2.0
Network	1 x Ethernet (10/100 Mbps), RJ45
Bus system	without
System properties	
User software	MicroBrowser
Electrical properties	
Supply	
Supply Power supply unit	24 V DC ±20 %
Typical current consumption	0.3 A
- JErser serrer serrer inen	
Mounting	
Mounting type	Front mounting
Material specifications	
Material front plate	Aluminum (natural anodized)
Housing material	Steel sheet, zinc-plated

Environmental and real-life conditions

WP 04T - Web panel

2913632

https://www.phoenixcontact.com/us/products/2913632



Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
	NEMA 4X
Ambient temperature (operation)	0 °C 50 °C
Ambient temperature (storage/transport)	-25 °C 70 °C
Permissible humidity (operation)	20 % 85 % (non-condensing)
Permissible humidity (storage/transport)	10 % 95 % (non-condensing)
Shock	DIN EN 60068-2-27
Vibration (operation)	DIN EN 60068-2-6
Width	120 mm
Width	120 mm
Height	90 mm
Height Depth	90 mm 40 mm
Depth	
Depth	
Depth xternal dimensions Width / Height / Depth	40 mm
Depth external dimensions	40 mm

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com