

PT 2X1+F-BE/FM - Surge protection base-element

2920049

<https://www.phoenixcontact.com/pc/products/2920049>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Base element to accept a protective plug with diagnostic and status indicator for two signal wires with common reference potential, integrated spark gap to provide a high-resistance connection between the ground of the protective circuit of the plug and ground potential.



Your advantages

- Maximum ease of maintenance, thanks to the 2-piece design
- Easy selection for all possible demands in MCR applications with a complete product portfolio
- The signal is not influenced during maintenance work, thanks to the impedance-neutral insertion and removal of protective plugs
- Easy integration into the control room via floating remote indication contact

Commercial data

Item number	2920049
Packing unit	10 pc
Minimum order quantity	1 pc
Product key	CL2112
Catalog page	Page 91 (TT-2011)
GTIN	4046356154086
Weight per piece (including packing)	56.96 g
Weight per piece (excluding packing)	56.82 g
Customs tariff number	85363010
Country of origin	DE

PT 2X1+F-BE/FM - Surge protection base-element

2920049

<https://www.phoenixcontact.com/pc/products/2920049>



Technical data

Notes

General	In the base elements PT...+F-BE/FM, the connections 9/10 (GND) are linked to the mounting foot via a gas-filled surge arrester.
---------	---

Product properties

Type	Base element, DIN rail mounting
Product type	Base element
Product family	PLUGTRAB PT
Number of positions	2

Electrical properties

Indicator/remote signaling	
Maximum operating voltage $U_{max. AC}$	250 V AC
Max. operating current I_{max}	0.2 A (250 V AC)
	0.2 A (220 V DC)
	1 A (60 V AC)
	1 A (60 V DC)

Connection data

Connection method	Screw connection
Screw thread	M3
Tightening torque	0.8 Nm
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section AWG	24 ... 12

Dimensions

Dimensional drawing	
Width	17.5 mm
Height	90 mm
Depth	51.7 mm
Horizontal pitch	1 Div.
Complete module width	17.7 mm
Complete module height	90 mm
Complete module depth	65.5 mm

PT 2X1+F-BE/FM - Surge protection base-element

2920049

<https://www.phoenixcontact.com/pc/products/2920049>



Material specifications

Color	black (RAL 9005)
Flammability rating according to UL 94	V-0

Mechanical properties

Mechanical data	
Open side panel	No

Protective circuit

Direction of action	Signal Ground/Shield-Earth Ground
---------------------	-----------------------------------

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP20
Ambient temperature (operation)	40 °C ... 85 °C

Mounting

Mounting type	DIN rail: 35 mm
---------------	-----------------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com