

2942959

https://www.phoenixcontact.com/pc/products/2942959

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Electronic housing set, consisting of electronic housings and printed circuit termination blocks

### Commercial data

Item number	2942959
Packing unit	10 pc
Minimum order quantity	1 pc
Product key	ACHCBA
Catalog page	Page 708 (C-1-2013)
GTIN	4017918080914
Weight per piece (including packing)	20.77 g
Weight per piece (excluding packing)	20.77 g
Customs tariff number	85369010
Country of origin	DE



2942959

https://www.phoenixcontact.com/pc/products/2942959

#### Set consists of

### EMG 10-LG - Electronics housing

2947747

https://www.phoenixcontact.com/pc/products/2947747



Electronic housing, with universal foot, without screw connection terminal blocks and cover

#### MKDS 3/2-EMG 10 - PCB terminal block

1712342

https://www.phoenixcontact.com/pc/products/1712342



PCB terminal block, nominal current: 24 A, rated voltage (III/2): 400 V, nominal cross section: 2.5 mm², number of potentials: 2, number of rows: 1, number of positions per row: 2, product range: MKDS 3, pitch: 5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: green, Pin layout: Linear pinning, Solder pin [P]: 5 mm, number of solder pins per potential: 1, type of packaging: packed in cardboard. Matches EMG 10 component housing



https://www.phoenixcontact.com/pc/products/2942959




### Technical data

### Product properties

Product type	Stackable housing set
Housing type	Component housing
Product family	EMGLG
Туре	Lower housing part, removable cover as option, connection system integrated
Number of positions	4
Pitch	5 mm
Туре	Lower and upper part, with universal foot, including PCB terminal blocks

#### **Dimensions**



### Material specifications

Color	green
Flammability rating according to UL 94	V0
Housing material	Polycarbonate fiber reinforced

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-40 °C 125 °C


2942959

https://www.phoenixcontact.com/pc/products/2942959



## Drawings

### Dimensional drawing



1 = Top edge of the PCB


B = Housing width



https://www.phoenixcontact.com/pc/products/2942959



### Dimensional drawing



#### Pitch 5 mm

a = Area for mounting components, 38 mm in the hood

b = Area for mounting components, 45 mm in the housing



2942959

https://www.phoenixcontact.com/pc/products/2942959

## Classifications

	ECLASS-11.0	27182702	
ΕΊ	ГІМ		
	ETIM 8.0	EC001031	
1U	NSPSC	SC	
	UNSPSC 21.0	31261500	



2942959

https://www.phoenixcontact.com/pc/products/2942959

### Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstraße 8 D-32825 Blomberg +49 (0) 5235-3 00 info@phoenixcontact.com